THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

NOTES:

1. CONFORMS TO EIA--310-D SPECIFICATIONS FOR RACKS AND CABINETS.
2. THE BONDING CAGE NUT AND BONDING SCREW MUST BE USED TOGETHER TO ACHIEVE BONDING BETWEEN EQUIPMENT MOUNTING FLANGES AND CAGE NUT RAILS. DO NOT SUBSTITUTE THE BONDING CAGE NUT OR BONDING SCREW WITH ANY OTHERS.

SERRATIONS ON BONDING CAGE NUT PROVIDE BONDING TO THE CAGE NUT RAIL



SERRATIONS UNDER HEAD OF BONDING SCREW PROVIDE BONDING TO THE EQUIPMENT FLANGE



COMPONENT DESCRIPTION	PART NUMBERS	
	CNB4K	CNBK
	QUANTITY	
BONDING CAGE NUT CAGE NUT RAIL THICKNESS TOLERANCE: 0.064 TO 0.105 in. [1.63mm TO .27 mm] GREEN	4	50
GREEN BONDING SCREW, 1/2 in. [12.7 mm] LONG COMBO HEAD UTILIZES, #2 PHILLIPS OR SLOTTED SCREWDRIVER OR 5/16 in. OR 8mm SOCKET DRIVE	4	50

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
04	3/13	JHNU	JHNU	RGB	REVISED TITLE BLOCK	N10966BD-C41747

TITLE: BONDING CAGE NUT KIT (CNB4K, CNBK) CUSTOMER DRAWING

ITEM REVISION NAME: N10966BD-C41747/04

DATASET FILE NAME: C41747/04.SLDDRW

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]
.X ± .XXX ±
.XX ± ANGLES ±

THIRD ANGLE PROJECTION

MATERIAL

DRAWING NUMBER: C41747_04

DRAWN BY	DATE	CHK	SCALE	SHEET	SIZE
JHNU	4/08	JMAR	NONE	SHEET 1 0F 1	A