



CT-1160 TOOL SHOWN

NOTES, UNLESS OTHERWISE SPECIFIED:

SPECIFICATIONS:

PANDUIT TOOL NO: CT-1160 and CT-1170

- CT-1160 Controlled Cycle Ferrule Crimp Tool
Crimps ferrule with Hexagon profile for 28-5 AWG (0,08 - 16 mm²) insulated and non-insulated single wire ferrules and 23-10 AWG (2 x 0.25mm² - 2x 6mm²) insulated twin ferrules. CT-1160 uses a grey locator as identifier for hex profile terminations.

- CT-1170 Controlled Cycle Ferrule Crimp Tool
Crimps ferrule with Square profile for 28-5 AWG (0,08 - 16 mm²) insulated and non-insulated single wire ferrules and 23-10 AWG (2 x 0.25mm² - 2x 6mm²) insulated twin ferrules. CT-1170 uses a black locator as identifier for square profile terminations.

TOOL WEIGHT: (WITHOUT FERRULES) 17.6 oz (0,50kg)

THIS TOOL'S FEATURES INCLUDE:

- Easy handling
- Integrated, releasable ratchet guarantees complete crimping
- Ergonomically developed soft-grips with slip-off protection
- Integral (and reversible) ferrule locator for easy crimping

Fully recyclable
RoHS Directive 2011/65/EU compliant

DIMENSIONS SHOWN ARE FOR BOTH THE CT-1160 and CT-1170 TOOLS;
AND ARE FOR REFERENCE ONLY.
DIMENSIONS IN PARENTHESES ARE (MM) METRIC.

- A = 8.50 (215) OVERALL LENGTH
- B = 2.95 (75) OVERALL HEIGHT
- C = 0.75 (19) OVERALL DEPTH

File Location: Teamcenter

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	DRAWN BY:	DATE:	CHK	SCALE	SHT 1 OF 1	SIZE
00	9-07-16	BLR	BJPU	JADE	RELEASED	10218	BLR	9-07-16	BJPU	NONE		B
							CT-1160 and CT-1170 TOOL					
							CUSTOMER DRAWING					
							ITEM REVISION NAME: TF28186B01_00			PANDUIT		
							UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.x) ± --- (.xxx) ± --- (.xx) ± --- ANGLES ± ---			MATERIAL: -----		
							THIRD ANGLE PROJECTION			DRAWING NUMBER: TF28186B01		