



CT-3001/CCP • CT-3001/CCPINT • CT-3001/CCPUK
 • CT-3001/CCPAUS • CT-3001/CCPTO
 MULTI-USE (CRIMP • CUT • PUNCH) TOOL

This tool meets requirements of Safety for Hand Held, Motor-Operated Electric Tools specification UL 60745-1 and CSA C22.2 No 60745-1. Tool is listed under CSA file number 268531.

NOTES, UNLESS OTHERWISE SPECIFIED:

The CT-3001/CCP, CT-3001/CCPINT, CT-3001/CCPUK, CT-3001/CCPAUS and CT-3001/CCPTO Battery Operated Multi-Use Tools are designed to crimp and cut:

- Crimps Panduit Copper and Aluminum compression connectors using Panduit Crimping Dies. Go to www.panduit.com for more information.
- Cuts Aluminum and Copper code conductor cable up to 1" [25mm].
- Cuts Aluminum and Mild Steel Threaded Rod; M5 to M12, and 1/4 to 1/2 UNC Thread.
- Punch Capacity of 2" (50 mm) conduit size in 10 Gauge (3.41 mm) mild steel with standard Greenlee punches and Panduit Punch Drive Adapter.

The CT-3001/CCP, CT-3001/CCPINT, CT-3001/CCPUK and CT-3001/CCPAUS Tools include:

Qty.	Description / Item								
1	Battery Operated Hydraulic Multi-Use (Crimp, Cut) Tool								
2	Rechargeable Battery (Makita Lithium-Ion 18VDC, 3Ah)								
1	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">/CCP </td> <td style="text-align: center;">/CCPINT </td> <td style="text-align: center;">/CCPUK </td> <td style="text-align: center;">/CCPAUS </td> </tr> <tr> <td style="text-align: center;">Plug Type A (North America)</td> <td style="text-align: center;">Plug Type C (International)</td> <td style="text-align: center;">Plug Type G (UK)</td> <td style="text-align: center;">Plug Type I (Australia)</td> </tr> </table>	/CCP 	/CCPINT 	/CCPUK 	/CCPAUS 	Plug Type A (North America)	Plug Type C (International)	Plug Type G (UK)	Plug Type I (Australia)
/CCP 	/CCPINT 	/CCPUK 	/CCPAUS 						
Plug Type A (North America)	Plug Type C (International)	Plug Type G (UK)	Plug Type I (Australia)						
	Makita Battery Charger – Regional (reference images above for regional plug type)								
1	Tool Case								
1	Set of "UAW" Die Adapters								

The CT-3001/CCPTO Tool includes:

Qty.	Description / Item
1	Battery Operated Hydraulic Multi-use (Crimp, Cut, Punch) Tool
1	Set of "UAW" Die Adapters

Technical Information:

Tool Weight (including battery)	7.1 lbs. (3.2 kg)
Dimensions (including battery)	17.5" L x 4.6" H x 3.0" W [444 L x 116 H x 75 W] mm
Crimping Force	6.7 tons (60 kN)

Tools are to be used with Panduit crimp dies, cable cutters, threaded rod cutters, and punch drive adapters are sold separately. Go to www.panduit.com for more information.

"UAM" adapter for cable cutting applications is sold separately.

A copy of operation manual and accessory information can be found at: www.panduit.com.

Dimensions in [brackets] are in millimeters. All dimensions are for reference only.

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	CT-3001/CCP, CT-3001/CCPINT, CT-3001/CCPUK, CT-3001/CCPAUS and CT-3001/CCPTO				CUSTOMER DRAWING	
00	7-25-16	BKA	ACC	JADE	DRAWING RELEASED	010819	ITEM REVISION NAME: 00084SLG_DC/00				PANDUIT	
							UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.x) ± --- (.xxx) ± --- (.xx) ± --- ANGLES ± ---				MATERIAL: -----	
							THIRD ANGLE PROJECTION				DRAWING NUMBER: 00084SLG_DC	
							DRAWN BY: BKA	DATE: 7-21-16	CHK ACC	SCALE NONE	SHT 1 OF 1	SIZE B