


2

1

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



SECTION A-A

SCALE 6:1

NOTES:

1. APPLICATION TOOLS - GS4MT, PPTMT, ST2MT, ST3MT, HTMT
2. MINIMUM LOOP TENSILE STRENGTH - 450 LBS. (2000 NEWTONS) WHEN TESTED ON A 1.5" MANDREL.
3. BRACKETS [] DENOTE DIMENSIONS IN MILLIMETERS, AND ARE SHOWN FOR REFERENCE ONLY
4. TOLERANCES:
.XXX = ±.010 [.25] .XX = ±.02 [.5]
.X = ±.03 [.8] ANGLES = ±2°
5. MATERIAL: 304 STAINLESS STEEL

PANDUIT PART NO.	PACKAGE QTY	MAX BUNDLE DIAMETER	LENGTH "L" ±.3 [7]
MLT2H-LP	50	2" [51]	7.9" [201]
MLT2.7H-LP	50	2.7" [69]	10.2" [259]
MLT4H-LP	50	4" [102]	14.3" [362]
MLT6H-LP	50	6" [152]	20.5" [521]
MLT8H-LP	50	8" [203]	26.8" [679]
MLT10H-LP	50	10" [254]	33.0" [838]
MLT12H-Q	25	12" [304]	39.3" [998]
MLT14H-Q	25	14" [355]	45.5" [1156]
MLT2H-TL	250	2" [51]	7.9" [201]
MLT4H-TL	250	4" [102]	14.3" [362]

TITLE

METAL LOCKING TIE - HEAVY SERIES - 304 STAINLESS STEEL

CONTROL DRAWING

ITEM REVISION NAME

N41115BS/07

DATASET FILE NAME

N41115BS_DC/07A

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE: IN [mm]

.X ± .1 [2.54]

.XXX ± .005 [.127]

.XX ± .01 [.25]

ANGLES ± 5°

MATERIAL:

304 STAINLESS STEEL

DRAWING NUMBER:

N41115BS_DC

DRAWN BY

DATE

CHK

SCALE

SIZE

JAMB

2/12

DPN

2:1

SHT 1 OF 1

A

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
07	02.19.15	BDK	SKB	RGR0	UPDATE TITLE BLOCK AND BORDER	N41115BS_DC

2

1