


PANDUIT PART NUMBER	MAX BUNDLE DIAMETER	"L" LENGTH ±.3" [7]
MLTC2H-LP316	2" [51]	7.9" [201]
MLTC2.7H-LP316	2.7" [69]	10.15" [258]
MLTC4H-LP316	4" [102]	14.3" [362]
MLTC6H-LP316	6" [152]	20.5" [521]
MLTC8H-LP316	8" [203]	26.8" [679]
MLTC10H-LP316	10" [254]	33.0" [838]



NYLON 11 COATING



SECTION A - A
SCALE 4 : 1

1. APPLICATION TOOLS - GS4MT, PPTMT, HTMT, & ST3MT
2. MINIMUM LOOP TENSILE STRENGTH - 250 lbs. [1112 NEWTONS]
3. BRACKETS [] DENOTE DIMENSIONS IN MILLIMETERS, AND ARE SHOWN FOR REFERENCE ONLY
4. TOLERANCES:
 .X = $\pm .030$ [.8] .XX = $\pm .020$ [.5]
 .XXX = $\pm .010$ [.25]
5. MATERIAL: 316 STAINLESS STEEL
6. COATING: NYLON 11
 COATING THICKNESS: .003"/.005" [0.08-0.13] PER SIDE

2