



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



PANDUIT PART NO.	WEIGHT (APPROX.)
NK6PPG24Y	1.25 lb (567 g)

NOTES:

- MATERIAL:
 PANEL HOUSING: STEEL
 RJ45 MODULE: THERMOPLASTIC RESIN UL94V-0
 PUNCHDOWN BLOCKS: THERMOPLASTIC RESIN UL94V-0
 BEZEL ASSEMBLY: THERMOPLASTIC RESIN UL94H-B
 RETENTION CAP: THERMOPLASTIC RESIN UL94V-0
- 24 PORT PATCH PANEL 8 POSITION 8 WIRE.
- THE PATCH PANEL IS DESIGNED FOR MOUNTING TO 19" UNIVERSAL RACKS.
- FOUR (4) 12-24 X 1/2" ROUND HEAD SCREWS ARE PROVIDED FOR FASTENING TO RACKS.
- DIMENSIONS IN PARENTHESES ARE IN METRIC.
- USE 110 STYLE TERMINATION TOOL FOR PUNCH DOWN.
- RETENTION CAPS (ONE PER CONNECTOR) PROVIDED FOR SNAP-IN ON TERMINATED CONNECTORS.



PART NUMBER		NK6PPG24Y	
TITLE		NETKEY CAT6 24 PORT PATCH PANEL	
		CUSTOMER DRAWING	
ITEM REVISION NAME		M02479JL/01	
DATASET FILE NAME		M02479JL_DC248/01A	
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN (mm)		MATERIAL:	
.x ± .xxx ± .010 (.3)		SEE NOTE 1	
.xx ± .03 (.8) ANGLES ±		DRAWING NUMBER:	
THIRD ANGLE PROJECTION		02479-248	
DRAWN BY	DATE	CHK	SCALE
LZ	3-4-06	REFR	.25-1
SHT 1 OF 1		A	

2	9-27-18	BAME	KRKE	MMR	B. REMOVED M6 SCREWS	M09000HW
1	5-15-14	MDJR	REFR	JCK	A. UPDATED TITLE BLOCK.	02479-248
R	3-4-06	LZ			RELEASED TO PRODUCTION	02479-248
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN

CID**-C & CIP**-C, PHONE OR DATA ICON LOCATED HERE, IDENTIFIES INDIVIDUAL PORT. OPTIONAL, NOT SUPPLIED.

D10100DA/14