


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.


Part Number	Width in. (mm)	Length ft. (m)	Thickness in. (mm)	Package per Roll	Description	Insulation Color	Weight oz. (gram)
ST15-085-66GRYL	.75 (19)	66 (20)	.005 (.13)	CELLO WRAP	GENERAL PURPOSE ST15 GREEN/YELLOW, .75"X66'X.005"	GREEN/YELLOW	2.3 (64)

- NOTES:
- VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A LIST OF CURRENT PARTS APPLICABLE FOR USE WITH THIS PRODUCT.
 - ALL MATERIALS AND COMPONENTS USED MEET THE MATERIAL RESTRICTIONS OF RoHS (EUROPEAN DIRECTIVE 2002/95/EC ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE RoHS TECHNICAL ADAPTATION COMMITTEE.
 - MATERIAL: RUBBER ADHESIVE PRESSURE SENSITIVE VINYL TAPE.
 - SUITABLE FOR USES UNDER 600 V OR 80 °C (176°F)
 - FLAME RETARDANT.
 - MEETS UL-510A.
 - COMPLIANT TO CALIFORNIA PROP. 65
 - THE LENGTH TOLERANCE IS MIN. 0.1 METER, MAX. 0.40 METER. THE THICKNESS TOLERANCE IS 0.05 MM. THE WIDTH TOLERANCE IS ± 2 MM.

TAPE WIDTH



TAPE THICKNESS



Component Tapes

PART NUMBER ST15-075-66BK		PACKAGING SPEC PKG-516	
PRODUCT SPEC PS-SH-02			
TITLE Stronghold Insulating Tape-General Purpose ST15 Tape			
CUSTOMER DRAWING			
ITEM REVISION NAME 00351EBT/00		PANDUIT	
DATASET FILE NAME 00351EBT_DC/00			
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN (mm)		MATERIAL: SEE NOTE3	
.x ± .1 [2.54] .xxx ± .005 [.127]		DRAWING NUMBER: 00351EBT_DC	
.xx ± .01 [.25] ANGLES ± 1°			
		THIRD ANGLE PROJECTION	
DRAWN BY JSUN	DATE 4/29/2019	CHK ADAH	SCALE NONE
SHT 1 OF 1		SIZE A	

ANGLOBAL-ASIZE

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
00	4/29/2019	JSUN	ADAH	JHAC	INITIAL RELEASE	046173/00