



NOTES:

1. PRODUCT INCLUDES ONE VERISAFE ABSENCE OF VOLTAGE TESTER
2. RETROFIT BOX ALLOWS REMOTE INSTALLATION OF INDICATOR AND ISOLATION MODULE
3. BOX MEETS UL508A TYPE 3R, 4, 12, AND 13 CSA TYPE 3R, 4, 12, AND 13 COMPLIES WITH NEMA TYPE 3R, 4, 12, AND 13 IEC 60529, IP66
4. CONDUIT FITTING SIZE IS 1/2" NPT OR SIMILAR.

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
1	8/16/18	DFA	KJM	MSAD	ADDED HOLE DIA DIM. AND NOTE 4.	GAECN05337
0	6/26/18	DFA	DPG	MSAD	INITIAL RELEASE	GAECN05302

PRODUCT SPEC	PACKAGING SPEC				
PART NUMBER VS-AVT-RBOX	WORK INSTRUCTION				
INSPECTION INSTRUCTION NUMBER	FMEA & CONTROL PLAN NUMBER				
TITLE VERISAFE RETROFIT BOX					
CUSTOMER DRAWING					
ITEM REVISION NAME 18Z111BW/01	PANDUIT				
DATASET FILE NAME 18Z111BW_DC/01					
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]					
.x : .1 [2.54]	.xxx : .005 [.127]				
.xx : .01 [.25]	ANGLES : 5°				
THIRD ANGLE PROJECTION					
DRAWING NUMBER: 18Z111BW_DC					
DRAWN BY DFA	DATE 6/26/18	CHK MSAD	SCALE NONE	SHT 1 OF 1	SIZE B