THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.


## NOTES:

030

- 1. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A LIST OF CURRENT PARTS APPLICABLE FOR USE WITH THIS PRODUCT AND INSTRUCTION SHEET (VO0028CA).
- 2. DIMENSIONS IN PARENTHESES ARE METRIC [ mm ].
- 3. CAN BE USED WITH ANY 19" CEA STANDARD PANEL.
- 4. PARTS SUPPLIED:
  - 26RU DUAL HINGE NEMA 4/12 ENCLOSURE
  - KEYLOCKING WING KNOBS ARE INCLUDED PROVIDING ACCESS CONTROL TO THE ENCLOSURE.

    (2) KEYS ARE INCLUDED WITH EACH ENCLOSURE.
  - ACCOMODATIONS FOR AN OPTIONAL AIR CONDITIONER.
  - RAL 7035 LIGHT-GRAY, LOW GLOSS, LIGHTLY TEXTURED POLYESTER POWDER COAT
  - INSTALLED FRONT AND REAR CAGE NUT RAILS
  - IN OPTIMIZED POSITIONS FOR EQUIPMENT MOUNTING.
  - INSTALLED POWER RECEPTACLE
  - INSTALLED FIBER ENCLOSURE (72 FIBER CAPACITY)
  - INSTALLED (2)48-PORT PATCH PANELS
  - INSTALLED CABLE MANAGEMENT
  - INSTALLED DOOR GROUND WHIPS, EQUIPMENT GROUND WHIPS (ONE END)
  - INSTALLED GROUND BAR
  - INFRASTRUCTURE GROUND CABLE
  - POWER CORDS, LABELED AND LENGTH OPTIMIZED
  - 10" LONG DIN RAIL MOUNTING PROVISION
  - CABLE/FIBER/POWER PENETRATION
  - RECOMMENDATION TEMPLATE
- INSTRUCTIONS FOR CABLE ROUTING AND MANAGEMENT
- 5. CENTER HINGED SECTION
  MAXIMUM LOAD RATING: 350 LBS [158.8 kg].

SHIPPING LENGTH	57"
SHIPPING WIDTH	39"
SHIPPING HEIGHT	35-1/4"
SHIPPING WEIGHT	270 lbs. 122.5 kg.
ENCLOSURE WEIGHT	218 lbs. 98.9 kg.



ZDF48-RA PRECONFIGURED 48" INDUSTRIAL DISTRIBUTION FRAME

CUSTOMER DRAWING

						13V397AD_DC_03C					
						UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [ mm ]		1			
						l .			5 °		
/4/18	JB0	NWW	TIMH	RELEASED TO PRODUCTION	13V397AD	. E			IRD ANGLE	DRAWING NUMBER:	
ATE	BY	CHK	APR	DESCRIPTION	ECN	DAJP	05/05/2014	NWW	NONE	SHT 1 0F 4	SIZE
						/4/18 JBO NWW TIMH RELEASED TO PRODUCTION 13V397AD	DIMEN  .x ± .xx ±	UNLESS OTHERW DIMENSIONAL TOLER  .x ± .1 [ 2.54 ] .xx ± .03 [ 0.76 ]  4/18 JBO NWW TIMH RELEASED TO PRODUCTION  13V397AD  DRAWN BY DATE	13V397AD_DC_03(  UNLESS OTHERWISE SPE DIMENSIONAL TOLERANCES A  .x ± .1 [ 2.54 ] .xxx ± .xx ± .03 [ 0.76 ] ANGLES ±  (4/18 JB0 NWW TIMH RELEASED TO PRODUCTION 13V397AD  DRAWN BY DATE CHK	13V397AD_DC_03C  UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]  .x ± .1 [2.54] .xxx ± .015 [0.38]  .xx ± .03 [0.76] ANGLES ± 5°  (4/18 JBO NWW TIMH RELEASED TO PRODUCTION 13V397AD THIRD ANGLE PROJECTION  DRAWN BY DATE CHK SCALE	13V397AD_DC_03C  UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]  .x ± .1 [2.54] .xxx ± .015 [0.38]  .xx ± .03 [0.76] ANGLES ± 5°  V4/18 JBO NWW TIMH RELEASED TO PRODUCTION  13V397AD  DRAWING NUMBER: 13V397AD_DC

TITLE

ITEM REVISION NAME

13V397AD/03

7

