



Best-in-Class Outlet Density

Optimal Form Factors

Superior Reliability

Smartzone™ G5

PDU Pocket Guide

NORTH AMERICA

PANDUIT®

infrastructure for a connected world

Welcome to the Panduit G5 Series of PDU's and Accessories



Quality & Reliability

3-Year standard and 5-Year extended warranty.



High Temperature

Built with premium components to withstand 140°F (60°C) at full load.



High Density Power

Unique outlets design for high outlet density.



Hot-Swappable & Upgradable

Hot-Swappable Controller with large OLED display.



Hardened Security

Enhanced security with certificate-based advanced asymmetric encryption, validated and hardened with multiple security scanning tools.



1GB On Board Ethernet Connection

Reduces deployment time and labor as PDU auto negotiates to 1GB network switches.



Real-Time Monitor

Real-time Monitoring of Power, Environmental & Cabinet Security.



Plug & Play Accessories

Variety Environmental & Cabinet Access Control Accessories.



Multi-Device WebGUI

Enhanced User-Experience with a self adjusting WebGUI that senses the device you are on.



Multi-Color

A variety of colored PDU chassis, power cords, and cable ties.

Product Families

Monitored Input (MI Series)

Input power monitoring.

Monitored Switched (MS Series)

Input power monitoring and outlet switching.

Monitored Per Outlet (MPO Series)

Input and Outlet level power monitoring.

Monitored & Switched Per Outlet (MSP0 Series)

Input and Outlet level power monitoring and outlet switching.

Note: All intelligent PDU's include environmental monitoring with rack access control.

Basic PDU's

Reliable power distribution (non-network).

Accessories

Offering a variety of Environmental Sensors; Security Devices and Power Cords.



For more information and support visit
www.panduit.com/pdu

G5 iPDU

Low Profile Design
saves rack space
Increase airflow

High Density
Best-in-Class outlet
density to match the
increased density of
rack IT equipment

**Hot-Swappable
Network Module**
with Power Share



**Power and Energy
Metering**
+/- 1% billing-grade
accuracy

**High Operating
Temperature**
140°F (60°C) with
Full Load Rating



Daisy-Chain Capabilities
Up to 4 PDU's
and 32 sensors



1GB Ethernet
with Redundant
Network Access
(RNA)

USB Port
Firmware Upgrade and
Automatic Rack Light

Color Coded Outlets
and Circuit Breakers
for load balancing



Environmental & Security
Advanced SmartZone™ Security
Handle featuring threshold based
beacon alerts and 200 users

**Premium Hydraulic-
Magnetic Circuit Breakers**
Stable trip characteristics at
extreme temperatures

Locking IEC Outlets
with Power Cords



Sensors connect to
SmartZone™ Security Handle






















Monitored Input (MI Series)

	Input Current per phase	Form Factor	Input Plug Type	Apparent Power (kVA)	Outlet Count
100-240VAC, 1-Phase	15	1U	5-15P	1.4	8
	20	1U	5-20P	1.9	8
	20	1U	L5-20P	1.9	8
	20	1U	L6-20P	3.3	12
	15	0U HALF	5-15P	1.4	16
	20	0U HALF	5-20P	1.9	16
	20	0U HALF	L5-20P	1.9	16
	30	0U MID	L5-30P	2.9	24
	20	0U MID	L6-20P	3.3	24
	30	2U	L5-30P	2.9	16
200-240VAC, 1-Phase	30	2U	L6-30P	5.0	16
	30	0U MID	L6-30P	5.0	24
	30	0U FULL	L6-30P	5.0	38
	50	0U FULL	CS8265C	8.3	36

Outlet Configuration	Length (inches)	Width (inches)	Depth (inches) at Outlet position	Panduit Part No.
⊙ (8)5-20R	1.7	17.5	10.6	P08D09M
⊙ (8)5-20R	1.7	17.5	10.6	P08D10M
⊙ (8)5-20R	1.7	17.5	10.6	P08D11M
⊙ (12)C13	1.7	17.5	10.6	P12D13M
⊙ (16)5-20R	32.2	2.0	2.1	P16D20M
⊙ (16)5-20R	32.2	2.0	2.1	P16D21M
⊙ (16)5-20R	32.2	2.0	2.1	P16D22M
⊙ (24)5-20R	58.7	2.0	2.1	P24D23M
⊙ (20)C13, ⊙ (4)C19	58.7	2.0	2.1	P24D24M
⊙ (16)5-20R	3.4	17.5	10.6	P16D12M
⊙ (12)C13, ⊙ (4)C19	3.4	17.5	10.6	P16D14M
⊙ (20)C13, ⊙ (4)C19	58.7	2.0	2.1	P24D07M
⊙ (32)C13, ⊙ (6)C19	68.9	2.0	2.1	P38D25M
⊙ (30)C13, ⊙ (6)C19	68.9	2.0	2.1	P36D26M

























Monitored Input (MI Series)

	Input Current per phase	Form Factor	Input Plug Type	Apparent Power (kVA)	Outlet Count
100-120/200-240VAC, 3-Phase	30	1U	L21-30P	8.6	6
	30	0U MID	L21-30P	8.6	24
	30	0U FULL	L21-30P	8.6	30
	30	0U FULL	L21-30P	8.6	38
208VAC, 3-Phase	30	1U	L15-30P	8.6	6
	50	1U	CS8365C	14.4	6
	30	0U MID	L15-30P	8.6	24
	30	0U FULL	L15-30P	8.6	36
	50	0U FULL	CS8365C	10.0	36
	50	0U FULL	CS8365C	14.4	24
	60	0U FULL	IEC 60309 3P+E 9h (IP44)	17.3	24

Outlet Type	Length (inches)	Width (inches)	Depth (inches) at Outlet position	Panduit Part No.
 (6)C19	1.7	17.5	10.6	P06D17M
 (18)C13,  (6)C19	58.7	2.0	2.1	P24D01M
 (18)C13,  (6)C19,  (6)5-20R	68.9	2.0	2.1	P30D02M
 (30)C13,  (6)C19,  (2)5-20R	68.9	2.0	2.1	P38D28M
 (6)C19	1.7	17.5	10.6	P06D16M
 (6)C19	1.7	17.5	10.6	P06D18M
 (18)C13,  (6)C19	58.7	2.0	2.1	P24D27M
 (30)C13,  (6)C19	68.9	2.0	2.1	P36D08M
 (30)C13,  (6)C19	68.9	2.0	2.1	P36D29M
 (12)C13,  (12)C19	68.9	2.0	2.1	P24D31M
 (12)C13,  (12)C19	68.9	2.0	2.1	P24D34M

Monitored Input (MI Series)

	Input Current per phase	Form Factor	Input Plug Type	Apparent Power (kVA)	Outlet Count
415VAC, 3-Phase	30	1U	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	6
	30	1U	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	6
	30	1U	NEMA L22-30P	17.3	6
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	24
	30	0U FULL	NEMA L22-30P	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	36
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	36
	30	0U FULL	NEMA L22-30P	17.3	36
	30	0U FULL - Wide	NEMA L22-30P	17.3	48
	30	0U FULL - Wide	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	48
	30	0U FULL - Wide	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	48
	30	0U FULL +	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	42
	30	0U FULL +	NEMA L22-30P	17.3	42
	30	0U FULL +	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	42

Outlet Type	Length (inches)	Width (inches)	Depth (inches) at Outlet position	Panduit Part No.
 (6)C19	1.7	17.5	10.6	P06D01M
 (6)C19	1.7	17.5	10.6	P06D03M
 (6)C19	1.7	17.5	10.6	P06D02M
 (12)C13,  (12)C19	68.9	2.0	2.1	P24D02M
 (12)C13,  (12)C19	68.9	2.0	2.1	P24D05M
 (12)C13,  (12)C19	68.9	2.0	2.1	P24D04M
 (24)C13,  (12)C19	68.9	2.0	2.1	P36D01M
 (24)C13,  (12)C19	68.9	2.0	2.1	P36D03M
 (24)C13,  (12)C19	68.9	2.0	2.1	P36D02M
 (48)C13,	68.9	3.3	2.1	P48D03M
 (48)C13,	68.9	3.3	2.1	P48D04M
 (48)C13,	68.9	3.3	2.1	P48D08M
 (36)C13,  (6)C19	74.6	2.0	2.1	P42D05M
 (36)C13,  (6)C19	74.6	2.0	2.1	P42D07M
 (36)C13,  (6)C19	74.6	2.0	2.1	P42D08M




























Monitored Switched (MS Series)

	Input Current per phase	Form Factor	Input Plug Type	Apparent Power (kVA)	Outlet Count
100-240VAC, 1-Phase	15	1U	5-15P	1.4	8
	20	1U	5-20P	1.9	8
	20	1U	L5-20P	1.9	8
	20	1U	L6-20P	3.3	8
	30	2U	L5-30P	2.9	16
	15	0U HALF	5-15P	1.4	12
	20	0U HALF	5-20P	1.9	12
	20	0U HALF	L5-20P	1.9	12
	20	0U HALF	L6-20P	3.3	16
	30	0U MID	L5-30P	2.9	18
200-240VAC, 1-Phase	30	2U	L6-30P	5.0	16
	30	0U FULL	L6-30P	5.0	24
	30	0U FULL	L6-30P	5.0	36
100-120/ 200-240VAC, 3-Phase	30	0U FULL	L21-30P	8.6	36
208VAC, 3-Phase	30	0U FULL	L15-30P	8.6	24
	30	0U FULL	L15-30P	8.6	36
	50	0U FULL	CS8365C	10.0	36
	60	0U FULL	IEC 60309 3P+E 9h (IP44)	17.3	24

Outlet Type	Length (inches)	Width (inches)	Depth (inches) at Outlet position	Panduit Part No.
⊙ (8)5-20R	1.7	17.5	10.6	P08E14M
⊙ (8)5-20R	1.7	17.5	10.6	P08E15M
⊙ (8)5-20R	1.7	17.5	10.6	P08E16M
⊙ (8)C13	1.7	17.5	10.6	P08E18M
⊙ (16)5-20R	3.4	17.5	10.6	P16E17M
⊙ (12)5-20R	36.1	2.0	2.1	P12E20M
⊙ (12)5-20R	36.1	2.0	2.1	P12E21M
⊙ (12)5-20R	36.1	2.0	2.1	P12E22M
⊙ (12)C13, ⊙ (4)C19	36.1	2.0	2.1	P16E24M
⊙ (18)5-20R	58.7	2.0	2.1	P18E23M
⊙ (12)C13, ⊙ (4)C19	3.4	17.5	10.6	P16E19M
⊙ (20)C13, ⊙ (4)C19	68.9	2.0	2.1	P24E28M
⊙ (30)C13, ⊙ (6)C19	68.9	2.0	2.1	P36E33M
⊙ (30)C13, ⊙ (6)C19	68.9	2.0	2.1	P36E35M
⊙ (18)C13, ⊙ (6)C19	68.9	2.0	2.1	P24E29M
⊙ (30)C13, ⊙ (6)C19	68.9	2.0	2.1	P36E34M
⊙ (30)C13, ⊙ (6)C19	68.9	2.0	2.1	P36E12M
⊙ (12)C13, ⊙ (12)C19	68.9	2.0	2.1	P24E32M

Monitored Switched (MS Series)










	Input Current per phase	Form Factor	Input Plug Type	Apparent Power (kVA)	Outlet Count
415VAC, 3-Phase	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	24
	30	0U FULL	NEMA L22-30P	17.3	24
	30	0U FULL	NEMA L22-30P	17.3	24
	30	0U FULL	NEMA L22-30P	17.3	24
	30	0U FULL - Wide	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	36
	30	0U FULL - Wide	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	36
	30	0U FULL - Wide	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	36
	30	0U FULL - Wide	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	36
	30	0U FULL - Wide	NEMA L22-30P	17.3	36
	30	0U FULL - Wide	NEMA L22-30P	17.3	36

Outlet Type	Length (inches)	Width (inches)	Depth (inches) at Outlet position	Panduit Part No.
 (12)C13,  (12)C19	68.9	2.0	2.1	P24E05M
 (18)C13,  (6)C19	68.9	2.0	2.1	P24E07M
 (24)C13	68.9	2.0	2.1	P24E08M
 (12)C13,  (12)C19	68.9	2.0	2.1	P24E09M
 (18)C13,  (6)C19	68.9	2.0	2.1	P24E10M
 (24)C13	68.9	2.0	2.1	P24E11M
 (12)C13,  (12)C19	68.9	2.0	2.1	P24E06M
 (18)C13,  (6)C19	68.9	2.0	2.1	P24E12M
 (24)C13	68.9	2.0	2.1	P24E13M
 (24)C13,  (12)C19	68.9	3.3	2.1	P36E01M
 (30)C13,  (6)C19	68.9	3.3	2.1	P36E03M
 (24)C13,  (12)C19	68.9	3.3	2.1	P36E04M
 (30)C13,  (6)C19	68.9	3.3	2.1	P36E05M
 (24)C13,  (12)C19	68.9	3.3	2.1	P36E02M
 (30)C13,  (6)C19	68.9	3.3	2.1	P36E06M

(table continues on next page)

Monitored Switched (MS Series)

	Input Current per phase	Form Factor	Input Plug Type	Apparent Power (kVA)	Outlet Count
415VAC, 3-Phase	30	0U FULL - Wide +	NEMA L22-30P	17.3	48
	30	0U FULL - Wide +	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	48
	30	0U FULL - Wide +	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	48
	30	0U FULL - Wide +	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	48
	30	0U FULL - Wide +	NEMA L22-30P	17.3	48
	30	0U FULL - Wide +	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	48

Outlet Type	Length (inches)	Width (inches)	Depth (inches) at Outlet position	Panduit Part No.
 (48)C13	74.0	3.3	2.1	P48E04M
 (48)C13	74.0	3.3	2.1	P48E03M
 (48)C13	74.0	3.3	2.1	P48E11M
 (42)C13,  (6)C19	74.0	3.3	2.1	P48E05M
 (42)C13,  (6)C19	74.0	3.3	2.1	P48E06M
 (42)C13,  (6)C19	74.0	3.3	2.1	P48E12M

Monitored Per Outlet (MPO Series)






















	Input Current per phase	Form Factor	Input Plug Type	Apparent Power (kVA)	Outlet Count
200-240VAC, 1-Phase	30	0U FULL	L6-30P	5.0	24
	30	0U FULL	L6-30P	5.0	36
208VAC, 3-Phase	30	0U FULL	L15-30P	8.6	24
	30	0U FULL	L21-30P	8.6	24
	50	0U FULL	CS8365C	10.0	36
	60	0U FULL	IEC 60309 3P+E 9h (IP44)	17.3	24
415VAC, 3-Phase	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	24
	30	0U FULL	NEMA L22-30P	17.3	24
	30	0U FULL	NEMA L22-30P	17.3	24
	30	0U FULL	NEMA L22-30P	17.3	24

Outlet Type	Length (inches)	Width (inches)	Depth (inches) at Outlet position	Panduit Part No.
☐ (20)C13, ☐ (4)C19	68.9	2.0	2.1	P24F01M
☐ (30)C13, ☐ (6)C19	68.9	2.0	2.1	P36F15M
☐ (18)C13, ☐ (6)C19	68.9	2.0	2.1	P24F02M
☐ (18)C13, ☐ (6)C19	68.9	2.0	2.1	P24F03M
☐ (30)C13, ☐ (6)C19	68.9	2.0	2.1	P36F18M
☐ (12)C13, ☐ (12)C19	68.9	2.0	2.1	P24F05M
☐ (12)C13, ☐ (12)C19	68.9	2.0	2.1	P24F09M
☐ (18)C13, ☐ (6)C19	68.9	2.0	2.1	P24F11M
☐ (24)C13	68.9	2.0	2.1	P24F12M
☐ (12)C13, ☐ (12)C19	68.9	2.0	2.1	P24F13M
☐ (18)C13, ☐ (6)C19	68.9	2.0	2.1	P24F14M
☐ (24)C13	68.9	2.0	2.1	P24F15M
☐ (12)C13, ☐ (12)C19	68.9	2.0	2.1	P24F10M
☐ (18)C13, ☐ (6)C19	68.9	2.0	2.1	P24F16M
☐ (24)C13	68.9	2.0	2.1	P24F17M

(table continues on next page)

Monitored Per Outlet (MPO Series)

	Input Current per phase	Form Factor	Input Plug Type	Apparent Power (kVA)	Outlet Count
415VAC, 3-Phase	30	0U FULL - Wide	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	48
	30	0U FULL - Wide	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	48
	30	0U FULL - Wide	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	48
	30	0U FULL - Wide	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	48
	30	0U FULL - Wide	NEMA L22-30P	17.3	48
	30	0U FULL - Wide	NEMA L22-30P	17.3	48
	30	0U FULL - Wide +	NEMA L22-30P	17.3	48
	30	0U FULL - Wide +	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	48
	30	0U FULL - Wide +	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	48
	30	0U FULL - Wide +	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	48
	30	0U FULL - Wide +	NEMA L22-30P	17.3	48
	30	0U FULL - Wide +	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	48

Outlet Type	Length (inches)	Width (inches)	Depth (inches) at Outlet position	Panduit Part No.
 (24)C13,  (12)C19	68.9	3.3	2.1	P36F01M
 (30)C13,  (6)C19	68.9	3.3	2.1	P36F03M
 (24)C13,  (12)C19	68.9	3.3	2.1	P36F04M
 (30)C13,  (6)C19	68.9	3.3	2.1	P36F05M
 (24)C13,  (12)C19	68.9	3.3	2.1	P36F02M
 (30)C13,  (6)C19	68.9	3.3	2.1	P36F06M
 (48)C13	74.0	3.3	2.1	P48F04M
 (48)C13	74.0	3.3	2.1	P48F03M
 (48)C13	74.0	3.3	2.1	P48F11M
 (42)C13,  (6)C19	74.0	3.3	2.1	P48F05M
 (42)C13,  (6)C19	74.0	3.3	2.1	P48F06M
 (42)C13,  (6)C19	74.0	3.3	2.1	P48F12M

Monitored & Switched Per Outlet (MSPO Series)






















	Input Current per phase	Form Factor	Input Plug Type	Apparent Power (kVA)	Outlet Count
100-240VAC, 1-Phase	30	0U FULL	L6-30P	5.0	24
	30	0U FULL	L6-30P	5.0	36
100-120/ 200-240VAC, 3-Phase	30	0U FULL	L21-30P	8.6	24
	30	0U FULL	L21-30P	8.6	36
208VAC, 3-Phase	30	0U FULL	L15-30P	8.6	24
	30	0U FULL	L15-30P	8.6	36
	50	0U FULL	CS8365C	14.4	24
	50	0U FULL	CS8365C	10.0	36
	60	0U FULL	IEC 60309 3P+E 9h (IP44)	17.3	24
415VAC, 3-Phase	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	24
	30	0U FULL	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	24
	30	0U FULL	NEMA L22-30P	17.3	24
	30	0U FULL	NEMA L22-30P	17.3	24
	30	0U FULL	NEMA L22-30P	17.3	24

Outlet Type	Length (inches)	Width (inches)	Depth (inches) at Outlet position	Panduit Part No.
☐ (20)C13, ☐ (4)C19	68.9	2.0	2.1	P24G01M
☐ (30)C13, ☐ (6)C19	68.9	2.0	2.1	P36G18M
☐ (18)C13, ☐ (6)C19	68.9	2.0	2.1	P24G03M
☐ (30)C13, ☐ (6)C19	68.9	2.0	2.1	P36G19M
☐ (18)C13, ☐ (6)C19	68.9	2.0	2.1	P24G02M
☐ (30)C13, ☐ (6)C19	68.9	2.0	2.1	P36G22M
☐ (12)C13, ☐ (12)C19	68.9	2.0	2.1	P24G04M
☐ (30)C13, ☐ (6)C19	68.9	2.0	2.1	P36G20M
☐ (12)C13, ☐ (12)C19	68.9	2.0	2.1	P24G05M
☐ (12)C13, ☐ (12)C19	68.9	2.0	2.1	P24G09M
☐ (18)C13, ☐ (6)C19	68.9	2.0	2.1	P24G13M
☐ (24)C13	68.9	2.0	2.1	P24G14M
☐ (12)C13, ☐ (12)C19	68.9	2.0	2.1	P24G15M
☐ (18)C13, ☐ (6)C19	68.9	2.0	2.1	P24G16M
☐ (24)C13	68.9	2.0	2.1	P24G17M
☐ (12)C13, ☐ (12)C19	68.9	2.0	2.1	P24G10M
☐ (18)C13, ☐ (6)C19	68.9	2.0	2.1	P24G18M
☐ (24)C13	68.9	2.0	2.1	P24G19M

(table continues on next page)

Monitored & Switched Per Outlet (MSPO Series)

	Input Current per phase	Form Factor	Input Plug Type	Apparent Power (kVA)	Outlet Count
415VAC, 3-Phase	30	0U FULL - Wide	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	36
	30	0U FULL - Wide	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	36
	30	0U FULL - Wide	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	36
	30	0U FULL - Wide	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	36
	30	0U FULL - Wide	NEMA L22-30P	17.3	36
	30	0U FULL - Wide	NEMA L22-30P	17.3	36
	30	0U FULL - Wide +	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	48
	30	0U FULL - Wide +	NEMA L22-30P	17.3	48
	30	0U FULL - Wide +	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	48
	30	0U FULL - Wide +	IEC 60309 3P+N+E 6h 30A (IP67)	17.3	48
	30	0U FULL - Wide +	NEMA L22-30P	17.3	48
	30	0U FULL - Wide +	IEC 60309 3P+N+E 6h 30A (IP44)	17.3	48

Outlet Type	Length (inches)	Width (inches)	Depth (inches) at Outlet position	Panduit Part No.
 (24)C13,  (12)C19	68.9	3.3	2.1	P36G01M
 (30)C13,  (6)C19	68.9	3.3	2.1	P36G03M
 (24)C13,  (12)C19	68.9	3.3	2.1	P36G04M
 (30)C13,  (6)C19	68.9	3.3	2.1	P36G05M
 (24)C13,  (12)C19	68.9	3.3	2.1	P36G02M
 (30)C13,  (6)C19	68.9	3.3	2.1	P36G06M
 (48)C13	74.0	3.3	2.1	P48G03M
 (48)C13	74.0	3.3	2.1	P48G04M
 (48)C13	74.0	3.3	2.1	P48G12M
 (42)C13,  (6)C19	74.0	3.3	2.1	P48G05M
 (42)C13,  (6)C19	74.0	3.3	2.1	P48G06M
 (42)C13,  (6)C19	74.0	3.3	2.1	P48G13M

Basic PDU

	Input Current per phase	Form Factor	Input Plug Type	Apparent Power (kVA)	Outlet Count
100-240VAC, 1-Phase	15	1U	NEMA 5-15P	1.4	12
	20	1U	NEMA 5-20P	1.9	12
	20	1U	NEMA L5-20P	1.9	12
	20	1U	NEMA L6-20P	3.3	12
	30	1U	NEMA L6-30P	5.0	12
	50	1U	CS8265C	8.3	6
	30	2U	NEMA L5-30P	2.9	16
	15	0U HALF	NEMA 5-15P	1.4	16
	20	0U HALF	NEMA 5-20P	1.9	16
	20	0U HALF	NEMA L5-20P	1.9	16
	20	0U HALF	NEMA L5-20P	1.9	22
	20	0U HALF	NEMA L6-20P	3.3	22
	30	0U HALF	NEMA L5-30P	2.9	22
	30	0U HALF	NEMA L6-30P	5.0	20
	30	0U MID	NEMA L6-30P	5.0	24
	30	0U MID	NEMA L6-30P	5.0	42
	50	0U MID	CS8265C	8.3	36
	50	0U MID	50A Hardwire	8.3	36
208VAC, 3-Phase	30	1U	NEMA L15-30P	8.6	6
	30	1U	NEMA L21-30P	8.6	6
	50	1U	CS8365C	14.4	6
	30	1U	IEC 60309 3P+E 9h 60A (IP44)	17.3	6
	50	0U HALF	NEMA L15-30P	8.6	18
	60	0U HALF	NEMA L21-30P	8.6	18
	30	0U MID	NEMA L15-30P	8.6	36
	30	0U MID	NEMA L21-30P	8.6	30
	30	0U MID	NEMA L21-30P	8.6	36
	30	0U FULL	NEMA L15-30P	8.6	42
	30	0U FULL	NEMA L21-30P	8.6	42
	50	0U FULL	CS8365C	10.0	42
	60	0U FULL	IEC 60309 3P+E 9h 60A (IP44)	17.3	24

Outlet Type	Length (inches)	Width (inches)	Depth (inches) at Outlet position	Panduit Part No.
Ⓜ (12)5-20R	1.6	17.5	2.0	P12B01M
Ⓜ (12)5-20R	1.6	17.5	2.0	P12B19M
Ⓜ (12)5-20R	1.6	17.5	2.0	P12B30M
Ⓜ (12)C13	1.6	17.5	2.0	P12B46M
Ⓜ (12)C13	1.7	17.5	7.8	P12B47M
Ⓜ (6)C19	1.7	17.5	7.8	P06B48M
Ⓜ (16)5-20R	3.4	17.5	7.8	P16B41M
Ⓜ (16)5-20R	32.2	2.0	2.1	P16B04M
Ⓜ (16)5-20R	32.2	2.0	2.1	P16B07M
Ⓜ (16)5-20R	32.2	2.0	2.1	P16B08M
Ⓜ (20)C13, Ⓜ (2)C19	32.2	2.0	2.1	P22B05M
Ⓜ (20)C13, Ⓜ (2)C19	32.2	2.0	2.1	P22B10M
Ⓜ (22)5-20R	32.2	2.0	2.1	P22B09M
Ⓜ (20)C13	32.2	2.0	2.1	P20B16M
Ⓜ (20)C13, Ⓜ (4)C19	58.7	2.0	2.1	P24B15M
Ⓜ (36)C13, Ⓜ (6)C19	58.7	2.0	2.1	P42B17M
Ⓜ (30)C13, Ⓜ (6)C19	58.7	2.0	2.1	P36B18M
Ⓜ (30)C13, Ⓜ (6)C19	58.7	2.0	2.1	P36B20M
Ⓜ (6)C19	1.7	17.5	7.8	P06B49M
Ⓜ (6)C19	1.7	17.5	7.8	P06B50M
Ⓜ (6)C19	1.7	17.5	7.8	P06B02M
Ⓜ (6)C19	1.7	17.5	7.8	P06B03M
Ⓜ (18)C13	32.2	2.0	2.1	P18B21M
Ⓜ (18)C13	32.2	2.0	2.1	P18B24M
Ⓜ (30)C13, Ⓜ (6)C19	58.7	2.0	2.1	P36B22M
Ⓜ (24)C13, Ⓜ (3)C19, (3)5-20R	58.7	2.0	2.1	P30B25M
Ⓜ (30)C13, Ⓜ (6)C19	58.7	2.0	2.1	P36B26M
Ⓜ (36)C13, Ⓜ (6)C19	68.9	2.0	2.1	P42B23M
Ⓜ (36)C13, Ⓜ (6)C19	68.9	2.0	2.1	P42B27M
Ⓜ (36)C13, Ⓜ (6)C19	68.9	2.0	2.1	P42B28M
Ⓜ (12)C13, Ⓜ (12)C19	68.9	2.0	2.1	P24B14M

Basic PDU

	Input Current per phase	Form Factor	Input Plug Type	Apparent Power (kVA)	Outlet Count
230VAC, 1-Phase	16	1U	IEC 60309 2P+E 6h 16A (IP44)	3.7	12
	32	1U	IEC 60309 2P+E 6h 32A (IP44)	7.4	6
	32	1U	IEC 60309 2P+E 6h 32A (IP44)	7.4	12
	16	0U HALF	IEC 60309 2P+E 6h 16A (IP44)	3.7	22
	32	0U HALF	IEC 60309 2P+E 6h 32A (IP44)	7.4	20
	32	0U MID	IEC 60309 2P+E 6h 32A (IP44)	7.4	30
	32	0U MID	IEC 60309 2P+E 6h 32A (IP44)	7.4	42
	48	0U MID	IEC 60309 2P+E 6h 63A (IP44)	11.0	36
230/400VAC, 3-Phase	16	1U	IEC 60309 3P+N+E 6h 16A (IP44)	11.0	6
	32	1U	IEC 60309 3P+N+E 6h 32A (IP44)	22.0	6
	16	0U MID	IEC 60309 3P+N+E 6h 16A (IP44)	11.0	42
	16	0U MID	IEC 60309 3P+N+E 6h 16A (IP44)	11.0	30
	32	0U FULL	IEC 60309 3P+N+E 6h 32A (IP44)	22.0	24
	32	0U FULL	IEC 60309 3P+N+E 6h 32A (IP44)	22.0	42

Outlet Type	Length (mm)	Width (mm)	Depth (mm) at Outlet position	Panduit Part No.
☺ (12)C13	41.5	443.5	49.9	P12B34M
☺ (6)C19	43.5	443.5	197.4	P06B35M
☺ (12)C13	43.5	443.5	197.4	P12B36M
☺ (20)C13, ☹ (2)C19	817.0	52.0	53.0	P22B39M
☺ (20)C13	817.0	52.0	53.0	P20B40M
☺ (24)C13, ☹ (6)C19	1490.0	52.0	53.0	P30B06M
☺ (36)C13, ☹ (6)C19	1490.0	52.0	53.0	P42B42M
☺ (30)C13, ☹ (6)C19	1490.0	52.0	53.0	P36B43M
☺ (6)C19	41.5	443.5	49.9	P06B37M
☺ (6)C19	43.5	443.5	197.4	P06B38M
☺ (36)C13, ☹ (6)C19	1490.0	52.0	53.0	P42B44M
☺ (24)13, ☹ (6)C19	1490.0	52.0	53.0	P30B13M
☺ (12)C13, ☹ (12)C19	1750.0	52.0	53.0	P24B12M
☺ (30)C13, ☹ (12)C19	1750.0	55.0	53.0	P42B11M

Accessories

Security & Environmental Accessories that connect directly to the G5 iPDU.

Note: A maximum of 8 sensors can be managed by the Panduit® SmartZone™ G5 PDU controller. See User Manual for Complete Details.

Description	Dimensions L x W x H (in.)	Length (ft.)	Panduit Part No.
Temperature Sensor	1.73 x 0.83 x 0.43	6.56	EA001
Temperature + Humidity Sensor	1.73 x 0.83 x 0.43	6.56	EB001
3 Temperature + Humidity Sensor	1.73 x 0.83 x 0.43	6.56	EC001
Water - Rope	2.36 x 2.36 x 0.87	6.56	ED001
Water - Spot	2.36 x 2.36 x 0.87	16.40	EE001
3 Sensor Hub	3.35 x 1.26 x 1.06	n/a	EF001
Water - Rope extension	n/a	6.56	EG001
Door Switch (magnetic 2 piece)	1.73 x 0.83 x 0.43 (1.14 x 0.67 x 0.28 for magnet)	3.28	ACA01
Dry Contact Input	1.73 x 0.83 x 0.43	9.84	ACC01
USB Light Strip	15 x 1 x 0.5	5.0	ACD01



EA001



EB001



EC001



ED001



EE001



EF001



EG001



ACA01



ACC01



ACD01

SmartZone™ Security Handle & Accessories that attach to the handle.

Description	Dimensions L x W x H (in.)	Length (ft.)	Panduit Part No.
SmartZone™ Security Handle with Humidity Sensor and Card Reader	n/a	n/a	ACF05
SmartZone™ Security Handle with Humidity Sensor and Card Reader + Keypad	n/a	n/a	ACF06
SmartZone™ Handle T + Door Sensor	n/a	7.64	ACF10
SmartZone™ Handle 3T + Door Sensor	n/a	9.84	ACF11
SmartZone™ Handle to iPDU Harness	n/a	9.12	ACF20



ACF05



ACF06



ACF10



ACF11



ACF20










Accessories

Dual Locking Power Cords

(UL, CE, VDE, TUV Approved)

Color	Description	Ratings	Gauge/Cross Section
Red	Locking Power Cord, IEC C14 to IEC C13	10A/250V	17 AWG/1.0mm ²
Red	Locking Power Cord, IEC C14 to IEC C13	10A/250V	17 AWG/1.0mm ²
Red	Locking Power Cord, IEC C14 to IEC C13	10A/250V	17 AWG/1.0mm ²
Red	Locking Power Cord, IEC C14 to IEC C13	10A/250V	17 AWG/1.0mm ²
Blue	Locking Power Cord, IEC C14 to IEC C13	10A/250V	17 AWG/1.0mm ²
Blue	Locking Power Cord, IEC C14 to IEC C13	10A/250V	17 AWG/1.0mm ²
Blue	Locking Power Cord, IEC C14 to IEC C13	10A/250V	17 AWG/1.0mm ²
Blue	Locking Power Cord, IEC C14 to IEC C13	10A/250V	17 AWG/1.0mm ²
Black	Locking Power Cord, IEC C14 to IEC C13	10A/250V	17 AWG/1.0mm ²
Black	Locking Power Cord, IEC C14 to IEC C13	10A/250V	17 AWG/1.0mm ²
Black	Locking Power Cord, IEC C14 to IEC C13	10A/250V	17 AWG/1.0mm ²
Black	Locking Power Cord, IEC C14 to IEC C13	10A/250V	17 AWG/1.0mm ²



Length (ft.)	Part Number (10 pk)			
2	LPCA01-X			
4	LPCA02-X			
6	LPCA03-X			
8	LPCA04-X			
2	LPCA06-X			
4	LPCA07-X			
6	LPCA08-X			
8	LPCA09-X			
2	LPCA11-X			
4	LPCA12-X			
6	LPCA13-X			
8	LPCA14-X			










Accessories

Dual Locking Power Cords

(UL, CE, VDE, TUV Approved)

Color	Description	Ratings	Gauge/Cross Section Area
Red	Locking Power Cord, IEC C20 to IEC C19	16A/250V	15 AWG/1.5mm ²
Red	Locking Power Cord, IEC C20 to IEC C19	16A/250V	15 AWG/1.5mm ²
Red	Locking Power Cord, IEC C20 to IEC C19	16A/250V	15 AWG/1.5mm ²
Red	Locking Power Cord, IEC C20 to IEC C19	16A/250V	15 AWG/1.5mm ²
Blue	Locking Power Cord, IEC C20 to IEC C19	16A/250V	15 AWG/1.5mm ²
Blue	Locking Power Cord, IEC C20 to IEC C19	16A/250V	15 AWG/1.5mm ²
Blue	Locking Power Cord, IEC C20 to IEC C19	16A/250V	15 AWG/1.5mm ²
Blue	Locking Power Cord, IEC C20 to IEC C19	16A/250V	15 AWG/1.5mm ²
Black	Locking Power Cord, IEC C20 to IEC C19	16A/250V	15 AWG/1.5mm ²
Black	Locking Power Cord, IEC C20 to IEC C19	16A/250V	15 AWG/1.5mm ²
Black	Locking Power Cord, IEC C20 to IEC C19	16A/250V	15 AWG/1.5mm ²
Black	Locking Power Cord, IEC C20 to IEC C19	16A/250V	15 AWG/1.5mm ²



Length (ft.)	Part Number (10 pk)			
2	LPCB01-X			
4	LPCB02-X			
6	LPCB03-X			
8	LPCB04-X			
2	LPCB06-X			
4	LPCB07-X			
6	LPCB08-X			
8	LPCB09-X			
2	LPCB11-X			
4	LPCB12-X			
6	LPCB13-X			
8	LPCB14-X			

Complete Warranty & Compliance information can be found at www.panduit.com
Customer Service: cs@panduit.com or 800.777.3300
Technical Support: techsupport@panduit.com or 866.405.6654

PANDUIT[®]

©2021 Panduit Corp. ALL RIGHTS RESERVED.
Replaces PUCB20 **PUCB23--SA-ENG** 5/2021