

Hanging Scales PCE-CS 10000N



PCE-CS 10000N are a digital battery-powered heavy-duty industrial crane, lifter, suspended or hanging scales, dynamometer, electronic balance or weighing hook that displays measurement values in kilograms (kg) or pounds (lbs). The scales are delivered factory calibrated and include a hook, shackle and remote control. For an additional fee, the scales can be calibrated according to ISO standards.

- ▶ Maximum weighing capacity: 10000 kg / 22046 lbs \approx 10 Tons
- ▶ Resolution: 5 kg
- ▶ Tare range: 100% full scale
- ▶ Displays measurement values in kilograms (kg) or pounds (lbs)
- ▶ Comes factory calibrated (see accessories for optional ISO calibration)
- ▶ Includes hook, shackle and remote control
- ▶ Features zero, tare, hold, sum / accumulation, battery voltage indication and adjustable brightness functions

Specifications

Maximum capacity	10000 kg / 22046 lbs ≈ 10 Tons
Minimum weight	100 kg / 220.5 lbs
Resolution	5 kg
Standard	OIML class III
Zero range	4 % full scale (FS)
Tare range	100 % FS
Settling time	≤ 10 seconds
Overload indication	100 % FS + 9e
Max. safety load	125 % FS
Ultimate load	400 % FS
Display	5-digit LCD/LED, 30 mm / 1.18" character height
Battery	6 V / 7 Ah fully-sealed lead-acid battery
Battery life	≥ 50 hours
Battery charger	9 V DC / 1000 mA
Remote control range	15 m / 49.2'
Remote control battery	2 x 1.5 V AAA batteries
Operating temperature	-10 ... +40 °C / +14 ... +104 °F
Operating humidity	≤ 85 % RH under +20 °C / +68 °F
Dimensions	264 x 206 x 745 mm / 10.4 x 8.1 x 29.4"
Weight	30 kg / 66.2 lbs

Subject to change