

SOUND LEVEL METER

PCE-NSP 10



- » **measurement functions: HOLD, MAX, LEQ**
- » **time weighting: F, S and I**
- » **octave band measurement**
- » **frequency range: 20 ... 8000 Hz**
- » **frequency weighting: A, C and Z**
- » **battery and mains operation**

Thanks to its wide measurement range and versatile functions, our sound level meter is suitable for noise measurements in industry, the environment, occupational health and safety, at events and in research. Our sound level meter records and visualises sound levels within a range from 20 to 130 dB in three manual measurement ranges and offers various measurement functions such as Hold, Max and Leq value. The sound level meter supports time weighting F, S and I as well as frequency weighting A, C and Z and can record sound within a frequency range from 25 to 130 dB.

With operation modes for Leq, 1/1 and 1/3 octave filter measurements, it covers a wide range of measurement requirements. The internal memory function enables automatic storage of up to 12 data groups for octave band measurements. In addition, up to 800 individual measurements and regular measurements can be saved over a period of up to 6 days. These functions make sound level meters indispensable tools in acoustics to ensure both the protection of people and the quality of rooms and products. An RS232 interface can transfer the data via the optional software. An AC output is also available.

The sound level meter fulfils several standards, including IEC 61672-1, GB/T3785.2-2010 and IEC 1260-2014, all in class II, making it the ideal choice for standard-compliant measurements. The sound level meter is supplied with a windscreen in a practical carrying case.

Specification

Sound level	
Measurement range up to	20 ... 90 dB
Resolution	0,1 dB
Accuracy	±1.5 dB

Sound level	
Measurement range up to	40 ... 110 dB
Resolution	0,1 dB
Accuracy	±1.5 dB

Sound level	
Measurement range up to	60 ... 130 dB
Resolution	0,1 dB
Accuracy	±1.5 dB

General technical data	
Outputs	AC signal (3.5 mm jack)
Measuring functions	HOLD, MAX, Leq
Measuring functions (additional information)	Working mode selection between: - Leq - 1/1-octave filter measurement - 1/3-octave filter measurement
Connections	1/2 inch microphone
Time weighting	fast (125 ms), slow (1 s), Pulse (35ms)
Frequency	20 ... 8000 Hz
Frequency weighting	A, C, Z
Display type	LCD with backlight
Display size	2,2 Inch
Storage medium	Internal memory
Storage capacity	800 Data records
Memory information	- Frequency octave band measurement: automatic storage of up to 12 data groups - Integration and statistics function: storage of up to 800 individual measurements
Microphone type	Condenser microphone
Interface	RS232
Standard(s)	IEC 61672-1 (Class II), GB/T3785.2-2010, JIG 188-2017, GB/T 3241-2014 (class II), IEC 1260-2014 (class II)
Menu language	English, English (GB)
Protection class (device)	IP20
Power supply	6 V DC
(Rechargeable) battery	4 x 1,5 V AAA battery , Alkali-manganese
Capacity	1200 mAh
Operating conditions	-10 ... 50 °C, 0 ... 90 % RH
Storage conditions	-10 ... 50 °C, 0 ... 90 % RH
Dimensions (L x W x H)	230 x 65 x 25 mm
Weight	186 g