

# Benchtop Scale PCE-PB 200N



**Benchtop scale with external display / Max. weighing range up to 200 kg / LC display /  
Large and flat weighing surface of 350 x 390 x 40 mm / Battery and mains operation**

The benchtop scale with a maximum weighing range of up to 200 kg and a weighing surface of 350 x 390 mm is the ideal measuring device for determining the weight of parcels or the contents of propane gas bottles. With an accuracy of  $\pm 0.3$  kg, the platform scale is a precise measuring device. Furthermore, the platform scale can be used for the dosing of paints. This makes the platform scale a universally applicable test device in production, warehouse and logistics.

In addition to the normal measuring mode, the benchtop scale has a counting function. With the counting function, the platform scale determines, for example, the number of batteries in a package. Another function is the automatic zeroing, with which the platform scale sets the zero point again after switching on. This function can also be deactivated in order to resume a measurement with the platform scale. The tare key can be used to manually reset the measured value to zero at any time, for example to hide the weight of trays, boxes or other packaging materials.

The benchtop scale can be used stationary because of the power supply unit and the wall bracket included in the scope of delivery to attach the display. With the additional option of battery operation, the platform scale can also be used on the move. The platform scale has an automatic switch-off function to save the batteries used. This will automatically turn off the platform scale after five minutes of inactivity.

- ▶ Optionally with ISO calibration
- ▶ Counting function
- ▶ Weighing units kg, lb, oz/lb
- ▶ Weighing surface of 350 x 390 mm / 13.7 x 15.3"
- ▶ Wall mounting bracket for the display
- ▶ Automatic shutdown when inactive

Subject to change

# Specifications

Weighing range	<b>200 kg / 440 lb</b>
Resolution	<b>0.1 kg / 3.5 oz</b>
Accuracy	±0.3 kg / 10.5 oz
Minimum load	0.3 kg / 10.5 oz

## Further specifications

Units	kg, lb, oz/lb
Display when the measuring range is exceeded	"0_Ld"
Display when voltage is too low	"LO"
Operating conditions	5 ... 35 °C / 41 ... 95 °F, <85% RH, non-condensing
Power supply battery	4 x 1.5 V AA batteries
Mains power supply	primary: 100 ... 240 VAC, 50/60 Hz, 0.3 A secondary: 6 VDC, 1 A
Dimensions platform	350 x 390 x 40 mm / 13.7 x 15.3 x 1.5"
Dimensions display	180 x 88 x 33 mm / 7.0 x 3.4 x 1.3"
Weight	ca. 3 kg / 6.6 lb

Subject to change