

Camera cable specifications

Model	Cable length	Cable type	Cable Ø	Boost function*	Lighting	Articulation camera head
PCE-VE 320N	1000 mm	Semi-flexible	5.5 mm	No	4 LEDs	Front view only
PCE-VE 320HR	1000 mm	Semi-flexible	5.5 mm	Yes	4 LEDs on the front 2 LEDs on the side	Front view only
PCE-VE 330N	2000 mm	Semi-flexible	5.5 mm	No	4 LEDs	Front view only
PCE-VE 333HR	3000 mm	Semi-flexible	5.5 mm	Yes	4 LEDs on the front 2 LEDs on the side	Front view only
PCE-VE 340N	10000 mm	Flexible	5.5 mm	No	3 LEDs	4-way articulation
PCE-VE 350N	1000 mm	Flexible	6.0 mm	No	4 LEDs	2-way articulation
PCE-VE 350N3**	3000 mm	Flexible	6.0 mm	No	4 LEDs	2-way articulation
PCE-VE 350HR	1000 mm	Flexible	6.0 mm	Yes	4 LEDs on the front 2 LEDs on the side	2-way articulation
PCE-VE 350HR3	3000 mm	Flexible	6.0 mm	Yes	4 LEDs on the front 2 LEDs on the side	2-way articulation
PCE-VE 355N	1500 mm	Flexible	4.5 mm	No	5 LEDs	2-way articulation
PCE-VE 355N3	3000 mm	Flexible	4.5 mm	No	5 LEDs	2-way articulation
PCE-VE 360N	1000 mm	Semi-flexible	3.9 mm	No	3 LEDs	Front view only
PCE-VE 370HR	1000 mm	Semi-flexible	6.0 mm	Yes	3 LEDs	4-way articulation
PCE-VE 370HR3	3000 mm	Flexible	6.0 mm	Yes	3 LEDs	4-way articulation
PCE-VE 380N	30000 mm	Semi-flexible	28 mm	No	8 LEDs	Front view only
PCE-VE 390N	10000 mm	Semi-flexible	28 mm	No	8 LEDs	Front view only

*The boost function improves the quality of pictures and videos in dark environments.

**This model is no longer available.