Uncontrolled document as of February 25, 2011. Refer to website for up to date specifications.

CASES 1450 Case



1450 Case

- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handle
- Stainless steel hardware and padlock protectors
- Pick N Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Lifetime Guarantee of Excellence

1450 Case Configurations

Cat. #	Description
1450	1450 Case
1450NF	1450 Case (No foam)
1454	1450 Case with Padded Dividers

Black Silver Orange Yellow OD Green* Desert Tan

*OD Green available upon request (minimum quantities apply)

1450 Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
16.00" x 13.00" x 6.87" (40.6 x 33 x 17.4 cm)	14.62" x 10.18" x 6.00" (37.1 x 25.8 x 15.2 cm)	
Lid Depth	**Bottom Depth**	**Total Depth**
1.75" (4.4 cm)	4.25" (10.8 cm)	6.00" (15.2 cm)
Weight with foam	**Weight without foam**	**Buoyancy Max.**
6.39 lbs. (2.9 kg)	5.51 lbs. (2.5 kg)	30 lbs. (13.61 kg)

Range Temperature
-40 / 210° F (-40 / 99° C)

Personalized Nameplate Available

1450 Case Certificates

• IP67 (1 meter submersion for 30 minutes)
• MIL C-4150J • Def Stan 81-41/STANAG 4280

1450 Case Accessories

Cat. #	Description
1450PF	Special Application Panel Frame
1451	3 pc. Replacement Foam Set
1453	Replacement O-ring
1455	Padded Divider Set Only

Pelican Products, Inc.
23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail:sales@pelican.com • www.pelican.com

PDFmyURL.com