



iM2306

Storm

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Guaranteed for life
- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



CONFIGURATIONS



iM2306
Standard



iM2306-X0000
No Foam



iM2306-X0002
With Padded Dividers



iM2306-X0001
With Foam

DIMENSIONS

Interior (L x W x D)	17.00 x 6.30" x 6.20 (43.2 x 16 x 15.7 cm)
Exterior (L x W x D)	18.20 x 8.40" x 6.70 (46.2 x 21.3 x 17 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	4.20" (10.7 cm)
Total Depth	6.2" (15.7 cm)
Int Volume	0.38 ft ³ (0.011 m ³)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com

COLORS

Document created on 04-11-19 Black OD Green

WEIGHT

Weight With Foam	4.70 lbs (2.1 kg)
Weight Empty	4.30 lbs (2 kg)
Buoyancy	24.25 lbs (11 kg)
Master Pack Weight	29.00 lbs (13.2 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

CERTIFICATIONS

MIL-STD-810F
ATA 300
FED-STD-101C

FOAM PROPERTIES

Layer 1 (Lid)	2.00" Convolute
Layer 2 (Base)	0.63" Pad
Layer 3 (Base)	1.81" Pick N Pluck
Layer 4 (Base)	1.81" Pick N Pluck

OTHER

Master Pack	4
Military	yes

ACCESSORIES
