

ITW Permatex
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924 (ChemTel)
 International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: ULTRA GREY RIGID HIGH TORQUE RTV 13 OZ
Item No: 82195
Product Type: Silicone

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Component | Weight% | ACGIH; TLV-TWA | OSHA PEL |
|--|---------|----------------------|------------|
| POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8 | 40-70 | Not listed | Not listed |
| CALCIUM CARBONATE 471-34-1 | 20-40 | 10 mg/m ³ | Not listed |
| GARNET MINERAL 1302-62-1 | 10-30 | Not listed | Not listed |
| VINYL OXIMINOSILANE 2224-33-1 | <7 | Not listed | Not listed |
| STEARIC ACID 57-11-4 | <2 | Not listed | Not listed |
| 2-BUTANONE OXIME 96-29-7 | 0.5-2.0 | Not listed | Not listed |

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. When this product is exposed to moisture, butanone oxime may be formed. May be harmful if swallowed. May irritate lips, gums, tongue, mouth, nose and throat. Note: This product does not contain microcrystalline silica.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Butanone oxime produced during curing is toxic and irritates eyes, nose and throat. Overexposure to the silane may cause coma and respiratory failure.

Aggravated Medical Condition: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: Rinse mouth. If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.

Skin Contact: Wipe off material with paper towel or cloth. Wash off with soap and water. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >200°F TCC

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures: Cool closed containers exposed to fire with water spray.

Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime, Silica fume, Formaldehyde

Unusual Fire/Explosion Hazards: None.

Lower Explosive Limit: n/d

Upper Explosive Limit: n/d

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Wipe up with absorbent material (e.g. cloth, fleece). Slippery, can cause falls if walked on.

Product Name: ULTRA GREY RIGID HIGH TORQUE RTV 13
OZ

Item No. 82195

7. HANDLING AND STORAGE

Storage: Keep container tightly closed. Store at temperatures not exceeding 32°C/ 90°F.
Handling: Avoid contact with skin and eyes. Do not inhale vapors. Do not wear contact lenses. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

Comments: When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Grey paste
Odor: Mild
Boiling Point: Not applicable, polymeric material
pH: N/AP
Solubility in Water: Polymerized
Specific Gravity: 1.47
VOC(Wt.%): <2%
Vapor Pressure: <5 mm Hg @ 70°F
Vapor Density (Air=1): >1
Evaporation Rate: n/d

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: Will not occur
Incompatibilities: Polymerized by contact with moisture., Strong oxidizers, Acids, Iron
Conditions to Avoid: Exposure to moisture.
Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime, Silica fume, Formaldehyde

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

U.S. Department of Transportation - DOT - 49 CFR (Ground)

DOT Shipping Name: Not regulated
Hazard Class: None
UN/ID Number: None

IATA (Air)

Proper Shipping Name: Not regulated
Class or Division: None
UN/ID Number: None

IMDG (Vessel)

Product Name: ULTRA GREY RIGID HIGH TORQUE RTV 13
OZ

Item No. 82195

Proper Shipping Name: Not regulated
Hazard Class: None
UN Number: None

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

California Proposition 65: No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

HMIS is a registered trademark of the National Paint and Coatings Association

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106
Telephone No.: 1-87-Permatex (877) 376-2839

Revision Date: June 28, 2012
Revision Number: 4