

Safety Data Sheet

acc. to OSHA HCS

Printing Date 12/01/2023

Revision Number 3

Revision Date 12/01/2023

1 Identification

- Product identifier
- Trade name: HP-800 Aerosol Can
- Article number: 13247-A5.56
- Relevant identified uses of the substance or mixture. Industrial Use Only.
- Application of the substance / the mixture Adhesive
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
Royal Adhesives And Sealants, LLC
2001 W. Washington Street South
Bend IN 46628-2023 Information
Phone Number: 574-246-5000
- Information department: Global Regulatory Department.

2 Hazard(s) identification

- Classification of the substance or



mixture GHS02 Flame

Flammable Aerosols 1

H222 Extremely flammable aerosol.



GHS07

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



GHS02 GHS07

- Signal word Danger
- Hazard statements Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.
- Precautionary statements
Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.

Safety Data Sheet

acc. to OSHA HCS

Printing Date 12/01/2023

Revision Number 3

Revision Date 12/01/2023

Trade name: HP-800 Aerosol Can

(Contd. of page 1)


Use only outdoors or in a well-ventilated area.
 Wear eye protection / face protection.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 If eye irritation persists: Get medical advice/attention.
 Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 - 4)



Health = 2
 Fire = 4
 Reactivity = 0

- HMIS-ratings (scale 0 - 4)



Health = 2
 Fire = 4
 Physical Hazard = 3

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Mixture

- Hazardous components:

74-98-6	propane	25-50%
67-64-1	acetone	≥10-<20%
110-54-3	n-hexane	5-20%
106-97-8	butane (containing 0,1 % butadiene (203-450-8))	2.5-10%
79-20-9	methyl acetate	≥2.5-<10%

4 First-aid measures

- Description of first aid measures
- After inhalation:
 Supply fresh air or oxygen; call for doctor.
 In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
 Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 12/01/2023

Revision Number 3

Revision Date 12/01/2023

Trade name: HP-800 Aerosol Can

(Contd. of page 2)

- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:
CO₂, extinguishing powder or water spray. Fight larger fires with water spray. Use fire fighting measures that suit the environment.
- For safety reasons unsuitable extinguishing agents: Do not use direct water stream.
- Special hazards arising from the substance or mixture Extremely flammable aerosol.
Contents under pressure. Pressurized container may explode when exposed to heat or flame. During a fire hazardous gases may be formed.
- Advice for firefighters
Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
- Protective equipment: Protective clothing and respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- Handling:
Precautions for safe handling
Open and handle receptacle with care.
Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material.
- Conditions for safe storage, including any incompatibilities
- Storage:
Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.
Empty containers may contain hazardous residuals. Keep away from heat, sparks and open flame.
DO NOT cut, drill, puncture, weld or grind on or near full, partially full or empty product containers.

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 12/01/2023

Revision Number 3

Revision Date 12/01/2023

Trade name: HP-800 Aerosol Can

(Contd. of page 3)

- Information about storage in one common storage facility: Store away from oxidizing agents. Store away from foodstuffs.
- Further information about storage conditions: Keep away from heat, spark and flame.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- Control parameters
- Components with limit values that require monitoring at the workplace:
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known

exposure limits. 74-98-6 propane

PEL Long-term value: 1800 mg/m³, 1000 ppmREL Long-term value: 1800 mg/m³, 1000 ppm

TLV see Appendix F Minimal oxygen content (D, EX)

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppmREL Long-term value: 590 mg/m³, 250 ppmTLV Short-term value: 500
ppm Long-term value:
250 ppm A4, BEI

110-54-3 n-hexane

PEL Long-term value: 1800 mg/m³, 500 ppmREL Long-term value: 180 mg/m³, 50 ppmTLV Long-term value: 50
ppm Skin; BEI

106-97-8 butane (containing 0,1 % butadiene (203-

450-8)) REL Long-term value: 1900 mg/m³, 800 ppmTLV Short-term value: 1000
ppm (EX)

79-20-9 methyl acetate

PEL Long-term value: 610 mg/m³, 200 ppmREL Short-term value: 760 mg/m³, 250 ppm
Long-term value: 610 mg/m³, 200 ppmTLV Short-term value: 250 ppm
Long-term value: 200 ppm

- Ingredients with biological limit

values: 67-64-1 acetone

BEI 25 mg/L Medium:
urine Time: end
of shift

Parameter: Acetone (nonspecific)

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 12/01/2023

Revision Number 3

Revision Date 12/01/2023

Trade name: HP-800 Aerosol Can

(Contd. of page 4)

110-54-3 n-hexane

BEI 0.5 mg/L

Medium: urine

Time: end of shift

Parameter: 2.5-Hexanedione without hydrolysis

- Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment (see listings below)
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.
Store protective clothing separately. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.
- Breathing equipment:
Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- Material of gloves
Nitrile rubber, NBR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection:
Safety glasses with side shields.



Tightly sealed goggles

- Body protection: Protective work clothing

9 Physical and chemical properties

- Information on basic physical and chemical properties
- General Information
- Appearance:

Form:	Compressed gas
Color:	Not determined.
- Odor: Characteristic
- Odor threshold: Not determined.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 12/01/2023

Revision Number 3

Revision Date 12/01/2023

Trade name: HP-800 Aerosol Can

(Contd. of page 5)

· pH-value:	Not applicable.
· Change in condition	
Melting point:	Undetermined.
Boiling point:	Not applicable, as aerosol.
· Flash point:	-104.4 °C (-155.9 °F)
· Auto igniting:	240 °C (464 °F)
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Flammable limits:	
Lower:	1.2 Vol %
Upper:	13 Vol %
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)
· Specific gravity at 20 °C (68 °F):	0.7112 g/cm ³ (5.93496 lbs/gal)
· Relative density	Not Available.
· Vapor density	Not Available.
· Evaporation rate	Not Available.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Viscosity:	
Dynamic:	Not Available
Kinematic:	Not Available
· Solvent content:	
Organic solvents:	53.1%
Solids content:	Not Available.
· Other information	No further relevant information available.

*

10 Stability and reactivity

- Reactivity Not reactive as supplied
- Chemical stability Stable under recommended storage conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No further information is available.
- Conditions to avoid Heat, flames, sparks.
- Incompatible materials: Strong oxidizers, acids, and bases.
- Hazardous decomposition products: Carbon monoxide and carbon dioxide

USA

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 12/01/2023

Revision Number 3

Revision Date 12/01/2023

Trade name: HP-800 Aerosol Can

(Contd. of page 6)

11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

- LD/LC50 values that are relevant for classification:

106-97-8 butane (containing 0,1 % butadiene (203-

450-8)) Inhalative LC50/4 h 658 mg/l (rat)

- Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.

- on the eye:

Irritating effect.

Vapors may be irritating to the eyes.

- Sensitization: No sensitizing effects known.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- Carcinogenic categories

- IARC (International Agency for Research on

Cancer) None of the ingredients is listed.

- NTP (National Toxicology Program)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health

Administration) None of the ingredients is listed.

12 Ecological information

- Toxicity

- Aquatic toxicity: No further relevant information available.

- Persistence and degradability No further relevant information available.

- Behavior in environmental systems:

- Bioaccumulative potential No further relevant information available.

- Mobility in soil No further relevant information available.

- Additional ecological information:

- General notes: At present there are no ecotoxicological assessments.

- Results of PBT and vPvB assessment

- PBT: Not applicable.

- vPvB: Not applicable.

- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods

- Recommendation: Comply with current regulations.

- Uncleaned packagings:

- Recommendation: Comply with current regulations.

USA

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 12/01/2023

Revision Number 3

Revision Date 12/01/2023

Trade name: HP-800 Aerosol Can

(Contd. of page 7)

14 Transport information

- UN-Number - DOT, IMDG, IATA	UN1950
- UN proper shipping name - DOT - IMDG - IATA	Aerosols, flammable AEROSOLS AEROSOLS, flammable
- Transport hazard class(es) - DOT 	
- Class - Label	2.1 Gases 2.1
IMDG, IATA 	
- Class - Label	2.1 Gases 2.1
- Packing group - DOT, IMDG, IATA	not regulated
Environmental hazards:	Not applicable.
- Special precautions for user - Hazard identification number (Kemler code): - - EMS Number: - Stowage Code	Warning: Gases F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Segregation Code	
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

USA

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 12/01/2023

Revision Number 3

Revision Date 12/01/2023

Trade name: HP-800 Aerosol Can

(Contd. of page 8)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

110-54-3 n-hexane

- TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- Hazardous Air Pollutants

110-54-3 n-hexane

- Proposition 65

Please contact H.B. Fuller for more information regarding Proposition 65 on this product: reg.request@hbfuller.com.

- (DSL) Canada Domestic Substance List

All components of this product are on the DSL (Canada Domestic Substance list) or are exempt from DSL requirements.

- Cancerogenity categories

- EPA (Environmental Protection Agency)

67-64-1 acetone

I

110-54-3 n-hexane

II

- TLV (Threshold Limit Value)

67-64-1 acetone

A4

- MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

- NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- National regulations:

- Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- Department issuing SDS:

Global Regulatory Department.
reg.request@hbfuller.com

- Creation Date: 12/21/2021

- Contact:

- Date of preparation / last revision 12/01/2023

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 12/01/2023

Revision Number 3

Revision Date 12/01/2023

Trade name: HP-800 Aerosol Can

(Contd. of page 9)

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flammable Aerosols 1: Aerosols – Category 1
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

USA