

R&S® FPL1000 Spectrum Analyzer Specifications



3
year
warranty

CONTENTS

Definitions	3
Specifications.....	4
Frequency	4
Sweep time.....	5
Resolution bandwidths.....	5
Level.....	6
Measurement speed	8
Trigger functions.....	8
I/Q data	8
Inputs and outputs	9
General data.....	10
Options	11
R&S®FPL1-B5 additional interfaces	11
R&S®FPL1-B30 DC power input 12/24 V	12
R&S®FPL1-B31 internal lithium-ion battery	12
R&S®FSV-B34 charger (only needed for charging spare batteries).....	12
Ordering information	13
Options.....	13
Recommended extras.....	13
Power sensors supported by the R&S®FPL1-K9 option	14
Service options	15

Definitions


General

Product data applies under the following conditions:

- Three hours storage at ambient temperature followed by 30 minutes warm-up operation
- Specified environmental conditions met
- Recommended calibration interval adhered to
- All internal automatic adjustments performed, if applicable

Specifications with limits

Represent warranted product performance by means of a range of values for the specified parameter. These specifications are marked with limiting symbols such as $<$, \leq , $>$, \geq , \pm , or descriptions such as maximum, limit of, minimum. Compliance is ensured by testing or is derived from the design. Test limits are narrowed by guard bands to take into account measurement uncertainties, drift and aging, if applicable.



Specifications without limits

Represent warranted product performance for the specified parameter. These specifications are not specially marked and represent values with no or negligible deviations from the given value (e.g. dimensions or resolution of a setting parameter). Compliance is ensured by design.

Typical data (typ.)

Characterizes product performance by means of representative information for the given parameter. When marked with $<$, $>$ or as a range, it represents the performance met by approximately 80 % of the instruments at production time. Otherwise, it represents the mean value.

Nominal values (nom.)

Characterize product performance by means of a representative value for the given parameter (e.g. nominal impedance). In contrast to typical data, a statistical evaluation does not take place and the parameter is not tested during production.

Measured values (meas.)

Characterize expected product performance by means of measurement results gained from individual samples.

Uncertainties

Represent limits of measurement uncertainty for a given measurand. Uncertainty is defined with a coverage factor of 2 and has been calculated in line with the rules of the Guide to the Expression of Uncertainty in Measurement (GUM), taking into account environmental conditions, aging, wear and tear.

Device settings and GUI parameters are indicated as follows: "parameter: value".

Typical data as well as nominal and measured values are not warranted by Rohde & Schwarz.

In line with the 3GPP/3GPP2 standard, chip rates are specified in Mcps (million chips per second), whereas bit rates and symbol rates are specified in Mbps (million bits per second), kbps (thousand bits per second) or ksps (thousand symbols per second), and sample rates are specified in Msample/s (million samples per second). Mcps, Mbps, kbps, ksps and Msample/s are not SI units.

Specifications


Frequency

Frequency range		5 kHz to 3 GHz
Frequency resolution		0.01 Hz

Reference frequency, internal, nominal		
Accuracy		(time since last adjustment × aging rate) + temperature drift + calibration accuracy
Aging per year	standard	1×10^{-6}
	with R&S®FPL1-B4 OCXO reference frequency option	1×10^{-7}
Temperature drift (0 °C to +50 °C)	standard	1×10^{-6}
	with R&S®FPL1-B4 OCXO reference frequency option	1×10^{-7}
Achievable initial calibration accuracy	standard	5×10^{-7}
	with R&S®FPL1-B4 OCXO reference frequency option	5×10^{-8}

Frequency readout		
Marker resolution		0.01 Hz
Uncertainty		$\pm(\text{marker frequency} \times \text{reference uncertainty} + 10 \% \times \text{resolution bandwidth} + \frac{1}{2} (\text{span}/(\text{sweep points} - 1)) + 1 \text{ Hz})$
Number of sweep (trace) points	default value	1001
	range	101 to 100001
Marker tuning frequency step size	marker step size = sweep points	$\text{span}/(\text{sweep points} - 1)$
	marker step size = standard	$\text{span}/(\text{default sweep points} - 1)$
Frequency counter resolution		1 Hz
Count accuracy		$\pm(\text{frequency} \times \text{reference uncertainty} + \frac{1}{2} (\text{last digit}))$
Display range for frequency axis		0 Hz, 10 Hz to max. frequency
Resolution		0.1 Hz
Max. span deviation		0.1 %

Spectral purity		
SSB phase noise	frequency = 1000 MHz, carrier offset	
	100 Hz	-88 dBc (1 Hz) (nom.)
	1 kHz	-107 dBc (1 Hz) (nom.)
	10 kHz	< -105 dBc (1 Hz), -108 dBc (1 Hz) (typ.)
	100 kHz	< -113 dBc (1 Hz), -116 dBc (1 Hz) (typ.)
	1 MHz	< -133 dBc (1 Hz), -136 dBc (1 Hz) (typ.)
	10 MHz	-153 dBc (1 Hz) (nom.)



Typical phase noise at different center frequencies.

Sweep time

Range	span = 0 Hz	1 μ s to 8000 s
	span \geq 10 Hz, RBW \geq 100 kHz	1 ms to 8000 s ¹
	span \geq 10 Hz, RBW < 100 kHz	75 μ s to 8000 s ²
Sweep time accuracy	span = 0 Hz	0.1 % (nom.)
	span \geq 10 Hz, RBW \geq 100 kHz	3 % (nom.)

Resolution bandwidths

Sweep filters and FFT filters		
Resolution bandwidths (-3 dB)	sweep filters	100 kHz to 10 MHz in 1/2/3/5 sequence
	FFT filters	1 Hz to 50 kHz in 1/2/3/5 sequence
Bandwidth uncertainty		< 3 % (nom.)
Shape factor 60 dB:3 dB		< 5 (nom.)

¹ Net sweep time without additional hardware settling time.

² Time for data acquisition for FFT calculation.

Channel filters		
Bandwidths (-3 dB)		100/200/300/500 Hz 1/1.5/2/2.4/2.7/3/3.4/4/4.5/5/6/7.5/8.5/9/ 10/12.5/14/15/16/20/21/25/30/50/100/150/ 192/200/300/500 kHz 1/1.228/1.5/2/3/3.75/5/10 MHz
Bandwidth uncertainty		< 2 % (nom.)
Shape factor 60 dB:3 dB		< 2 (nom.)
Video bandwidths		
	standard	1 Hz to 10 MHz in 1/2/3/5 sequence
Signal analysis bandwidth (equalized)		
	standard	10 MHz (nom.)
	with R&S®FPL1-B40 option	40 MHz (nom.)

Level

Display range		displayed noise floor up to +30 dBm
---------------	--	-------------------------------------

Max. input level		
DC voltage		50 V
CW RF power	RF attenuation 0 dB	
	RF preamplifier = off	20 dBm (= 0.1 W)
	with R&S®FPL1-B22 option, RF preamplifier = on	13 dBm (= 0.02 W)
	RF attenuation ≥ 10 dB	
	RF preamplifier = off	30 dBm (= 1 W)
	with R&S®FPL1-B22 option, RF preamplifier = on	23 dBm (= 0.2 W)
Pulse spectral density	RF attenuation 0 dB, RF preamplifier = off	97 dB μV/MHz
Max. pulse voltage	RF attenuation ≥ 10 dB	150 V
Max. pulse energy	RF attenuation ≥ 10 dB, 10 μs	1 mWs

Intermodulation		
1 dB compression of input mixer (two-tone)	RF attenuation 0 dB, RF preamplifier = off	+7 dBm (nom.)
Third-order intercept point (TOI)	RF attenuation 0 dB, level 2 × -20 dBm, Δf > 5 × RBW or 10 kHz, whichever is larger, RF preamplifier = off	
	10 MHz ≤ f _{in} < 300 MHz	> 13 dBm, 16 dBm (typ.)
	300 MHz ≤ f _{in} < 3 GHz	> 17 dBm, 20 dBm (typ.)
Second harmonic intercept (SHI)	RF attenuation 0 dB, level -13 dBm, RF preamplifier = off	
	1 MHz < f _{in} ≤ 900 MHz	45 dBm (nom.)
	900 MHz < f _{in} ≤ 1.5 GHz	70 dBm (nom.)

Displayed average noise level (DANL)		
	0 dB RF attenuation, termination 50 Ω, log. scaling, normalized to 1 Hz RBW, RBW = 1 kHz, VBW = 1 Hz, sample detector, +20 °C to +30 °C	
RF preamplifier off	5 kHz ≤ f < 100 kHz	-146 dBm (typ.)
	100 kHz ≤ f < 5 MHz	< -145 dBm, -150 dBm (typ.)
	5 MHz ≤ f < 2 GHz	< -149 dBm, -152 dBm (typ.)
	2 GHz ≤ f < 3 GHz	< -148 dBm, -151 dBm (typ.)
RF preamplifier on (gain 20 dB (nom.))	3 MHz ≤ f < 10 MHz	< -155 dBm, -160 dBm (typ.)
	10 MHz ≤ f < 2 GHz	< -163 dBm, -167 dBm (typ.)
	2 GHz ≤ f < 3 GHz	< -162 dBm, -165 dBm (typ.)

Spurious responses		
	mixer level ≤ -13 dBm, sweep optimization: auto or dynamic	
Image response	10 MHz ≤ f ≤ 3 GHz	
	f _{in} - 2 × 4020.4 MHz (1st IF)	< -90 dBc (typ.)
	f _{in} - 2 × 820.4 MHz (2nd IF)	< -90 dBc
	f _{in} - 2 × 20.4 MHz (3rd IF), RBW ≤ 5 MHz	< -80 dBc
Intermediate frequency response	2 MHz ≤ f ≤ 3 GHz	
	1st IF (4020.4 MHz)	< -90 dBc (typ.)
	2nd IF (820.4 MHz)	< -80 dBc
	3rd IF (20.4 MHz)	< -80 dBc
Residual spurious response	0 dB RF attenuation	
	f ≤ 1 MHz	< -90 dBm (nom.)
	f > 1 MHz	< -90 dBm

Local oscillator related spurious	f < 3 GHz	
	1 kHz ≤ carrier offset ≤ 10 MHz	< -70 dBc
	carrier offset > 10 MHz	< -80 dBc
Other interfering signals		
Subharmonic of 1st LO	20 MHz ≤ f < 3 GHz, spurious at 4020.4 MHz - 2 × f _{in}	< -80 dBc (nom.)
Harmonic of 1st LO	mixer level < -25 dBm, spurious at f _{in} - 2010.2 MHz	< -80 dBc (nom.)

Level display		
Logarithmic level axis		1 dB to 200 dB, in 1 dB steps
Linear level axis		10 % of reference level per level division, 10 divisions or logarithmic scaling
Number of traces		6
Trace detector		max. peak, min. peak, auto peak (normal), sample, RMS, average
Trace functions		clear/write, max. hold, min. hold, average, view
Setting range of reference level		-130 dBm to (-13 dBm + RF attenuation - RF preamplifier gain), in steps of 0.01 dB
Units of level axis		dBm, dBμV, dBmV, dBμA, dBpW, V, A, W

Level measurement uncertainty		
Absolute level uncertainty at 50 MHz	RBW = 10 kHz, level -10 dBm, reference level -10 dBm, RF attenuation 10 dB	
	+20 °C to +30 °C	< 0.3 dB (σ = 0.1 dB)
	0 °C to +50 °C	< 0.5 dB (σ = 0.17 dB)
Frequency response referenced to 50 MHz	RF attenuation 10/20/30/40 dB, RF preamplifier = off, +20 °C to +30 °C	
	5 kHz ≤ f < 3 MHz	< 1 dB (nom.)
	3 MHz ≤ f < 3 GHz	< 0.3 dB (σ = 0.1 dB)
	any setting of RF attenuation, RF preamplifier = off, 0 °C to +50 °C	
	5 kHz ≤ f < 3 GHz	< 1 dB (nom.)
Attenuator switching uncertainty	RF attenuation ≤ 20 dB, RF preamplifier = on, +20 °C to +30 °C	
	3 MHz ≤ f < 3 GHz	< 0.6 dB (nom.)
Attenuator switching uncertainty	f = 50 MHz, 0 dB to 45 dB, referenced to 10 dB attenuation	< 0.2 dB (σ = 0.07 dB)
Uncertainty of reference level setting		0 dB ³
Bandwidth switching uncertainty	referenced to RBW = 10 kHz and sweep type FFT	
	sweep type = FFT (RBW < 100 kHz)	< 0.1 dB (nom.)
	sweep type = sweep (RBW ≥ 100 kHz)	< 0.2 dB (nom.)

Nonlinearity of displayed level		
Logarithmic level display	S/N > 16 dB, 0 dB to -50 dB	< 0.2 dB (σ = 0.07 dB)
Linear level display	S/N > 16 dB, 0 dB to -70 dB	5 % of reference level (nom.)

Total measurement uncertainty	signal level 0 dB to -50 dB below reference level, S/N > 20 dB, sweep time auto, sweep type = FFT, RF attenuation 10 dB, 20 dB, 30 dB, 40 dB, RF preamplifier = off, span/RBW < 100, confidence level 95 %, +20 °C to +30 °C	
	3 MHz ≤ f < 3 GHz	0.5 dB

³ The setting of the reference level affects only the graphical representation of the measurement result on the display, not the measurement itself. Therefore, the reference level setting causes no additional uncertainty in measurement results.

Measurement speed

Local measurement and display update rate	1001 sweep points, sweep optimization set to "speed"	1 ms (1000/s) (nom.)
Max. sweep rate, remote operation ^{4,5}	trace average = on	0.9 ms (1100/s) (nom.)
Remote measurement and LAN transfer ⁴		2.8 ms (357/s) (nom.)
Marker peak search ⁴		1.3 ms (nom.)
Center frequency tune + sweep + sweep data transfer ⁴		15 ms (nom.)

Trigger functions

Trigger		
Trigger source		free run, video, external, IF power
Trigger offset	span \geq 10 Hz	50 ns to 40 s, min. resolution 50 ns (or 0.5 % of offset)
	span = 0 Hz	(-sweep time) to 40 s, min. resolution 50 ns (or 0.5 % of offset)
Max. deviation of trigger offset		$\pm(7.8125 \text{ ns} + (0.1 \% \times \text{trigger offset}))$
IF power trigger		
Sensitivity	min. signal power	-60 dBm + RF attenuation – RF preamplifier gain
	max. signal power	-15 dBm + RF attenuation – RF preamplifier gain
IF power trigger bandwidth	RBW > 5 MHz	40 MHz (nom.)
	RBW \leq 5 MHz	6 MHz (nom.)

I/Q data

Interface		GPIB or LAN interface
Memory length		max. 25 Msample I and Q
Word length of I/Q samples		14 bit
Sampling rate	standard	100 Hz to 12.5 MHz
	with R&S®FPL-B40 option	100 Hz to 100 MHz
Max. signal analysis bandwidth (equalized)	Standard	10 MHz
	with R&S®FPL-B40 option	40 MHz
Signal analysis bandwidth \leq 10 MHz		
Amplitude flatness	$f_{\text{center}} \geq 12 \text{ MHz}$ and (1.25 \times signal analysis bandwidth)	$\pm 0.3 \text{ dB}$ (nom.)
Deviation from linear phase	$f_{\text{center}} \geq 12 \text{ MHz}$ and (1.25 \times signal analysis bandwidth)	$\pm 1^\circ$ (nom.)
Signal analysis bandwidth \leq 40 MHz		
Amplitude flatness	$f_{\text{center}} \geq 12 \text{ MHz}$ and (1.25 \times signal analysis bandwidth)	$\pm 0.5 \text{ dB}$ (nom.)
Deviation from linear phase	$f_{\text{center}} \geq 12 \text{ MHz}$ and (1.25 \times signal analysis bandwidth)	$\pm 1.5^\circ$ (nom.)

⁴ Measured with a PC equipped with Intel® Core™ i7 2.8 GHz and Gbit LAN interface.

⁵ Measurement is performed with a sweep count of 1000. The indicated speed is the average speed of 1 sweep.

Inputs and outputs

RF input		
Impedance		50 Ω
Connector		N female
VSWR	RF attenuation ≥ 10 dB	
	10 MHz $\leq f < 3$ GHz	< 1.5 (nom.)
Setting range of attenuator	standard	0 dB to 45 dB, in 5 dB steps
	with R&S®FPL1-B25 option	0 dB to 45 dB, in 1 dB steps
RF preamplifier gain	with R&S®FPL1-B22 option	20 dB (nom.)
Noise source drive		
Connector		BNC female
Output voltage		0 V/28 V, switchable, max. 100 mA (nom.)
Power sensor		
Connector		6-pin LEMOSA female for supported R&S®NRP-Zxx power sensors
USB interface		
		4 ports, type A plug, version 2.0
Reference output		
Connector		BNC female
Impedance		50 Ω
Output frequency	internal reference	10 MHz
	external reference	same as reference input signal
Level		> 0 dBm (nom.)
Reference input		
Connector		BNC female
Impedance		50 Ω
Input frequency range		10 MHz \pm 5 ppm
Required level		> 0 dBm into 50 Ω
External trigger/gate input		
Connector		BNC female
Trigger voltage		0.5 V to 3.5 V
Input impedance		10 k Ω
IEC/IEEE bus control		
		interface in line with IEC 625-2 (IEEE 488.2)
Command set		SCPI 1997.0
Connector		24-pin Amphenol female
Interface functions		SH1, AH1, T6, L4, SR1, RL1, PP1, DC1, DT1, C0
LAN interface		
Connector		10/100/1000BASE-T RJ-45
External monitor		
Connector		DVI-D

General data

Display		21 cm LC TFT color display (10.1")
Resolution		1280 x 800 pixel (WXGA resolution)
Pixel failure rate		$< 1 \times 10^{-5}$

Data storage		
Internal	standard	solid-state drive (SSD) 32 Gbyte
External		supports USB-2.0-compatible memory devices

Environmental conditions		
Temperature	operating temperature range	+0 °C to +50 °C
	storage temperature range	-20 °C to +70 °C
Climatic loading	without condensation	+40 °C at 85 % rel. humidity, in line with EN 60068-2-30,

Mechanical resistance		
Vibration	sinusoidal	5 Hz to 55 Hz 0.15 mm constant amplitude (1.8 g at 55 Hz); 55 Hz to 150 Hz acceleration: 0.5 g constant; in line with EN 60068-2-6
	random	10 Hz to 300 Hz, acceleration 1.2 g (RMS), in line with EN 60068-2-64
Shock		40 g shock spectrum, in line with MIL-STD-810E method no. 516.4 procedure I, MIL-PRF-28800F

EMC		in line with EMC Directive 2014/30/EU including IEC/EN 61326-1 ^{6,7} , IEC/EN 61326-2-1, CISPR 11/EN 55011 ⁶ , IEC/EN 61000-3-2, IEC/EN 61000-3-3
------------	--	---

Recommended calibration interval		2 years
---	--	---------

Power supply		
AC supply	without battery option	100 V to 240 V \pm 10%, 50 Hz to 60 Hz \pm 5%, 400 Hz \pm 5% class of protection I in line with VDE 411
	with battery option	100 V to 240 V \pm 10%, 50 Hz to 60 Hz \pm 5%
Current consumption	without options	1.7 A to 0.8 A (nom.)
	with internal battery (option R&S®FPL1-B31) in charge mode	3 A to 1.5 A (nom.)
Safety		in line with EN 61010-1, IEC 61010-1, UL 61010-1, CAN/CSA-C22.2 No. 61010-1
Test mark		CSA, CSA-NRTL

Dimensions and weight		
Dimensions	W x H x D	408 mm x 186 mm x 235 mm (16.06 in x 7.32 in x 9.25 in)
Net weight, nominal	without options	6 kg (13.22 lb)
	with internal battery	7.3 kg (16 lb)

⁶ Emission limits for class A equipment.

⁷ Immunity test requirement for industrial environment (EN 61326 table 2).

Options

R&S®FPL1-B5 additional interfaces

User port		
Connector		25-pin D-Sub female
Output		TTL-compatible, 0 V/5 V, max. 15 mA
Input		TTL-compatible, max. 5 V
Noise source control		
Connector		BNC female
Output		0 V/28 V, max. 100 mA, switchable, supply for noise source
Power sensor		
Connector		6-pin LEMOSA female for supported R&S®NRP-Zxx power sensors
IF/video/demod out		
Connector		BNC female, 50 Ω
IF out		
Bandwidth		equal to RBW setting
IF frequency		25 MHz
Output level	center frequency > 10 MHz, span = 0 Hz, signal at reference level and center frequency	0 dBm (nom.)
Video out		
Bandwidth		equal to VBW setting
Output scaling	log. display scale lin. display scale	logarithmic linear
Output level	center frequency > 10 MHz, span = 0 Hz, signal at reference level and center frequency	1 V (nom.), open circuit
Audio output		
Loudspeaker		built-in, adjustable
AF out		
Connector		3.5 mm mini jack
Output impedance		10 Ω
Open-circuit voltage		up to 1.5 V, adjustable

R&S®FPL1-B30 DC power input 12/24 V

Input voltage range		12 V to 24 V (nom.) 10.4 V to 28 V, switch-on voltage > 11 V (meas.)
Input current	$V_{in} = 12/24\text{ V}$	13 A/6.5 A (nom.)
	$V_{in} = 12/24\text{ V}$, operating mode, without internal batteries (R&S®FPL1-B31)	5.5 A/2.7 A (meas.)
	$V_{in} = 12/24\text{ V}$, operating mode, internal batteries in charge mode	11 A/5 A (meas.)
	$V_{in} = 12/24\text{ V}$, instrument standby mode, internal batteries in charge mode	6.5 A/3 A (meas.)
Temperature	operating temperature range	0 °C to +40 °C
	storage temperature range	-20 °C to +70 °C

R&S®FPL1-B31 internal lithium-ion battery

Operating time		3.5 h (nom.)
Charge time	standby mode, AC supply	< 2 h (nom.)
	standby mode, external DC supply (R&S®FPL1-B30)	< 2 h (nom.)
	operating mode	< 4 h (nom.)
Temperature	operating temperature range, discharge	0 °C to +50 °C
	operating temperature range, charge	0 °C to + 45 °C
	storage temperature range	-20 °C to +60 °C ⁸

R&S®FSV-B34 charger (only needed for charging spare batteries)

AC input voltage range		100 V to 240 V, $\pm 10\%$ (nom.)
AC supply frequency		50 Hz to 60 Hz (nom.)
Power consumption		max. 300 W (nom.)
Number of charger bays		4
Dimensions	W x H x D	400 mm x 127 mm x 203 mm (15.75 in x 5 in x 8 in)
Net weight		3.1 kg (6.9 lb)

⁸ The battery packs should be stored in an environment with low humidity, free from corrosive gas at a recommended temperature range < +21 °C. Extended exposure to temperatures above +45°C could degrade battery performance and life.

Ordering information

Designation	Type	Order No.
Spectrum Analyzer	R&S®FPL1003	1304.0004.03
Accessories supplied		
Power cable and quick start guide		

Options

Designation	Type	Order No.	Retrofittable	Remarks
OCXO Reference Frequency	R&S®FPL1-B4	1323.1902.02	yes	retrofit in service center
Additional Interfaces	R&S®FPL1-B5	1323.1883.02	yes	user-retrofittable IF/video/demod out, user port, noise source control, power sensor, AF output, loudspeaker
GPIB Interface	R&S®FPL1-B10	1323.1890.02	yes	user-retrofittable
Second Hard Disk (SSD)	R&S®FPL1-B19	1304.0427.02	yes	user-retrofittable mounted on PC board, including analyzer firmware
RF Preamplifier	R&S®FPL1-B22	1323.1719.02	yes	user-retrofittable
1 dB Steps for electronic attenuator	R&S®FPL1-B25	1323.1990.02	yes	user-retrofittable
DC Power Supply 12/24 V	R&S®FPL1-B30	1323.1877.02	yes	user-retrofittable
Internal Lithium-Ion Battery	R&S®FPL1-B31	1323.1725.02	yes	retrofit in service center; including 2 battery packs and internal charging unit
40 MHz Analysis Bandwidth	R&S®FPL1-B40	1323.1931.02	yes	user-retrofittable
Firmware/software				
AM/FM/φM Measurement Demodulator	R&S®FPL1-K7	1323.1731.02		
Power Sensor Measurement with R&S®NRP Power Sensors	R&S®FPL1-K9	1323.1754.02		supports R&S®NRPxx power sensors
Noise Figure and Gain Measurements	R&S®FPL1-K30	1323.1760.02		requires R&S®FPL1-B5

Recommended extras

Designation	Type	Order No.
Protective Hard Cover	R&S®FPL1-Z1	1323.1960.02
Soft Carrying Bag for transport and outdoor operation	R&S®FPL1-Z2	1323.1977.02
H-style Shoulder Harness (requires R&S®FPL1-Z2 option)	R&S®FPL1-Z3	1323.1683.02
Spare Lithium-Ion Battery Pack	R&S®FPL1-Z4	1323.1677.02
Anti-glare Display Film for outdoor operation	R&S®FPL1-Z5	1323.1690.02
Lithium-Ion Battery Charger for charging spare batteries	R&S®FSV-B34	1321.3950.02
19" Rackmount Kit	R&S®FPL1-Z6	1323.1954.02
Headphones		0708.9010.00
Matching pads, 50/75 Ω		
L Section, matching at both ends	R&S®RAM	0358.5414.02
Series Resistor, 25 Ω, matching at one end (taken into account in instrument function RF INPUT 75 Ω)	R&S®RAZ	0358.5714.02
High-power attenuators		
Attenuator 100 W, 3/6/10/20/30 dB, 1 GHz	R&S®RBU100	1073.8495.xx (xx = 03/06/10/20/30)
Attenuator 50 W, 3/6/10/20/30 dB, 2 GHz	R&S®RBU50	1073.8695.xx (xx = 03/06/10/20/30)
Attenuator 50 W, 20 dB, 6 GHz	R&S®RDL50	1035.1700.52
Connectors and cables		
IEC/IEEE Bus Cable, length: 1 m	R&S®PCK	0292.2013.10
IEC/IEEE Bus Cable, length: 2 m	R&S®PCK	0292.2013.20
DC block		
DC Block, 10 kHz to 18 GHz (type N)	R&S®FSE-Z4	1084.7443.02

Power sensors supported by the R&S®FPL1-K9 option ⁹

Designation	Type	Order No.
Universal power sensors		
10 MHz to 8 GHz, 100 mW, two-path	R&S®NRP-Z211	1417.0409.02
10 MHz to 8 GHz, 200 mW ¹⁰	R&S®NRP-Z11	1138.3004.02
10 MHz to 18 GHz, 100 mW, two-path	R&S®NRP-Z221	1417.0309.02
10 MHz to 18 GHz, 200 mW ¹⁰	R&S®NRP-Z21	1137.6000.02
10 MHz to 18 GHz, 2 W ¹⁰	R&S®NRP-Z22	1137.7506.02
10 MHz to 18 GHz, 15 W ¹⁰	R&S®NRP-Z23	1137.8002.02
10 MHz to 18 GHz, 30 W ¹⁰	R&S®NRP-Z24	1137.8502.02
Power sensor modules with power splitter		
DC to 18 GHz, 500 mW	R&S®NRP-Z27	1169.4102.02
DC to 26.5 GHz, 500 mW	R&S®NRP-Z37	1169.3206.02
Thermal power sensors		
0 Hz to 18 GHz, 100 mW	R&S®NRP18T	1424.6115.02
0 Hz to 18 GHz, 100 mW	R&S®NRP18TN	1424.6121.02
0 Hz to 33 GHz, 100 mW	R&S®NRP33T	1424.6138.02
0 Hz to 33 GHz, 100 mW	R&S®NRP33TN	1424.6144.02
0 Hz to 40 GHz, 100 mW	R&S®NRP40T	1424.6150.02
0 Hz to 40 GHz, 100 mW	R&S®NRP40TN	1424.6167.02
0 Hz to 50 GHz, 100 mW	R&S®NRP50T	1424.6173.02
0 Hz to 50 GHz, 100 mW	R&S®NRP50TN	1424.6180.02
0 Hz to 67 GHz, 100 mW	R&S®NRP67T	1424.6196.02
0 Hz to 67 GHz, 100 mW	R&S®NRP67TN	1424.6209.02
0 Hz to 110 GHz, 100 mW	R&S®NRP110T	1424.6215.02
Average power sensors		
8 kHz to 6 GHz, 200 mW	R&S®NRP6A	1424.6796.02
8 kHz to 6 GHz, 200 mW	R&S®NRP6AN	1424.6809.02
9 kHz to 6 GHz, 200 mW ¹⁰	R&S®NRP-Z91	1168.8004.02
8 kHz to 18 GHz, 200 mW	R&S®NRP18A	1424.6815.02
8 kHz to 18 GHz, 200 mW	R&S®NRP18AN	1424.6821.02
Three-path diode power sensors		
100 pW to 200 mW, 10 MHz to 8 GHz	R&S®NRP8S	1419.0006.02
100 pW to 200 mW, 10 MHz to 8 GHz, LAN version	R&S®NRP8SN	1419.0012.02
100 pW to 200 mW, 10 MHz to 18 GHz	R&S®NRP18S	1419.0029.02
100 pW to 200 mW, 10 MHz to 18 GHz, LAN version	R&S®NRP18SN	1419.0035.02
1 nW to 2 W, 10 MHz to 18 GHz	R&S®NRP18S-10	1424.6721.02
10 nW to 15 W, 10 MHz to 18 GHz	R&S®NRP18S-20	1424.6738.02
30 nW to 30 W, 10 MHz to 18 GHz	R&S®NRP18S-25	1424.6744.02
100 pW to 200 mW, 10 MHz to 33 GHz	R&S®NRP33S	1419.0064.02
100 pW to 200 mW, 10 MHz to 33 GHz, LAN version	R&S®NRP33SN	1419.0070.02
100 pW to 200 mW, 10 MHz to 33 GHz, LAN version, TVAC-compliant	R&S®NRP33SN-V	1419.0129.02
100 pW to 100 mW, 50 MHz to 40 GHz	R&S®NRP40S	1419.0041.02
100 pW to 100 mW, 50 MHz to 40 GHz, LAN version	R&S®NRP40SN	1419.0058.02
100 pW to 100 mW, 50 MHz to 50 GHz	R&S®NRP50S	1419.0087.02
100 pW to 100 mW, 50 MHz to 50 GHz, LAN version	R&S®NRP50SN	1419.0093.02
Wideband power sensors		
50 MHz to 18 GHz, 100 mW	R&S®NRP-Z81	1137.9009.02
50 MHz to 40 GHz, 100 mW (2.92 mm)	R&S®NRP-Z85	1411.7501.02
50 MHz to 40 GHz, 100 mW (2.40 mm)	R&S®NRP-Z86	1417.0109.40
50 MHz to 44 GHz, 100 mW (2.40 mm)	R&S®NRP-Z86	1417.0109.44

⁹ For average power measurement only.

¹⁰ Product discontinued.

Warranty		
Base unit		3 years
All other items ¹²		1 year
Options		
Extended Warranty, one year	R&S®WE1	Please contact your local Rohde & Schwarz sales office.
Extended Warranty, two years	R&S®WE2	
Extended Warranty with Calibration Coverage, one year	R&S®CW1	
Extended Warranty with Calibration Coverage, two years	R&S®CW2	
Extended Warranty with Accredited Calibration Coverage, one year	R&S®AW1	
Extended Warranty with Accredited Calibration Coverage, two years	R&S®AW2	

Extended warranty with a term of one to two years (WE1 to WE2)

Repairs carried out during the contract term are free of charge ¹³. Necessary calibration and adjustments carried out during repairs are also covered. Simply contact the forwarding agent we name; your product will be picked up free of charge and returned to you in top condition a couple of days later.

Extended warranty with calibration (CW1 to CW2)

Enhance your extended warranty by adding calibration coverage at a package price. This package ensures that your Rohde & Schwarz product is regularly calibrated, inspected and maintained during the term of the contract. It includes all repairs ¹³ and calibration at the recommended intervals as well as any calibration carried out during repairs or option upgrades.

¹² For options that are installed, the remaining base unit warranty applies if longer than 1 year. Exception: all batteries have a 1 year warranty.

¹³ Excluding defects caused by incorrect operation or handling and force majeure. Wear-and-tear parts are not included.

Service that adds value

- | Worldwide
- | Local and personalized
- | Customized and flexible
- | Uncompromising quality
- | Long-term dependability

Rohde & Schwarz

The Rohde & Schwarz electronics group offers innovative solutions in the following business fields: test and measurement, broadcast and media, secure communications, cybersecurity, monitoring and network testing. Founded more than 80 years ago, the independent company which is headquartered in Munich, Germany, has an extensive sales and service network with locations in more than 70 countries.

Sustainable product design

- | Environmental compatibility and eco-footprint
- | Energy efficiency and low emissions
- | Longevity and optimized total cost of ownership

Certified Quality Management

ISO 9001

Certified Environmental Management

ISO 14001

Rohde & Schwarz GmbH & Co. KG

www.rohde-schwarz.com

Rohde & Schwarz training

www.training.rohde-schwarz.com

Regional contact

- | Europe, Africa, Middle East | +49 89 4129 12345
customersupport@rohde-schwarz.com
- | North America | 1 888 TEST RSA (1 888 837 87 72)
customer.support@rsa.rohde-schwarz.com
- | Latin America | +1 410 910 79 88
customersupport.la@rohde-schwarz.com
- | Asia Pacific | +65 65 13 04 88
customersupport.asia@rohde-schwarz.com
- | China | +86 800 810 82 28 | +86 400 650 58 96
customersupport.china@rohde-schwarz.com

R&S® is a registered trademark of Rohde & Schwarz GmbH & Co. KG

Trade names are trademarks of the owners

PD 5214.6974.22 | Version 02.00 | September 2017 (as)

R&S®FPL1000 Spectrum Analyzer

Data without tolerance limits is not binding | Subject to change

© 2017 Rohde & Schwarz GmbH & Co. KG | 81671 Munich, Germany



5214697422