

**M1800 SYSTEM WATER-BASED
PRECISION LINE® INVERTED MARKING PAINT****DESCRIPTION AND USES**

Industrial Choice M1800 System Water-Based Precision Line® is a general purpose inverted marking paint. Use for marking concrete, pavement, gravel, grass, and more. M1800 Precision Line is suitable for marking the location of underground utilities at construction and excavation sites where identification is desired.

PRODUCTS

SKU	DESCRIPTION
1801838	Clear
1834838	Safety Green
1861838	Fluorescent Pink
1862838	Fluorescent Red
1868838	Safety Purple
1869838	Fluorescent Purple
1875838	Black
203031	Caution Blue
203032	Fluorescent Green
203033	Caution Yellow
203034	High Visibility Yellow
203035	Alert Orange
203036	Fluorescent Orange
203037	Fluorescent Red-Orange
203038	Safety Red
203039	White
205176	Fluorescent Blue

PACKAGING

Inverted 20 fl. oz. aerosol container, (17 oz. fill weight; except 1801838 Clear: 16 oz. fill weight), 12 aerosols/carton.

PRODUCT APPLICATION**SURFACE PREPARATION**

ALL SURFACES: Remove loose contaminants by sweeping the surface before application of the coating.

APPLICATION

Use when temperature is 40-90°F (10-32°C) and humidity is below 85% to ensure proper drying. This product can be used down to 25°F (-4°C) which may result in a slight reduction of delivery rate. Protect surrounding surfaces from overspray. Overspray can carry a significant distance. Shake can vigorously for one minute after mixing ball is heard. Invert can and point at ground or floor. Hold can 4 to 10 inches above surface to be marked. Press in sideways to spray or use Rust-Oleum Marking Wand (#2393000) or Rust-Oleum Marking Pistol (#210188). Follow directions for proper use of this equipment. Keep can moving to prevent build-up.

CLEAN-UP

Clean valve by spraying upright for 2-3 seconds after each use. Properly discard empty container. Do not burn or place in trash compactor. Empty container can be recycled

CLOGGING

If valve clogs, carefully remove spray tip and clean in thinner. **DO NOT** insert any object into can valve opening.

AEROSOLS	TECHNICAL DATA	IC-51
• TRUSTED QUALITY SINCE 1921 • RUST-OLEUM® INDUSTRIAL CHOICE®	M1800 SYSTEM WATER-BASED PRECISION LINE® INVERTED MARKING PAINT	

PHYSICAL PROPERTIES

	WATER-BASED PRECISION LINE INVERTED MARKING PAINT
Resin Type	Hydrocarbon
Pigment Type	Varies with color
MIR	Maximum value of 0.85
Fill Weight	17 oz.; except 1801838 Clear: 16 oz. fill weight
Practical Coverage	Approximately 600-700 linear feet at 1 inch wide
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Less than 2 hours
Shelf Life	5 years
Safety Information	For additional information, see SDS

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.