

QUALIFICATION REPORT – ANSI/ESD S20.20

SCS HGC1M-N72-BLU CUP STYLE HEEL GRINDER

ANSI/ESD S20.20	SCS Test Results	Test Methods
-----------------	------------------	--------------

Point-to-Groundable-Point Resistance (ohms), 48-72 hours, 10V/100V, N=6 specimens

@12%RH, 23°C	< 1.0 x 10 ⁹	See Table 1	ANSI/ESD SP9.2
@ 50%RH, 23°C	< 1.0 x 10 ⁹	See Table 1	ANSI/ESD SP9.2

Test Equipment (Calibration records and test results are located at our corporate lab (Sanford, NC)):

For Test Method ANSI/ESD SP9.2:


- ETS Controlled Environment Chamber (Model 5532)
- SCS Surface Resistance Meter (Model 770761)

Test Data:

Table 1 – Resistance (ohms)

Specimen	Point-to-Groundable-Point Resistance (ohms)	
	@ 23°C, 12%RH, 48-72 hours	@ 23°C, 50%RH, 48-72 hours
1	1.04 x 10 ⁶	1.03 x 10 ⁶
2	1.04 x 10 ⁶	1.04 x 10 ⁶
3	1.04 x 10 ⁶	1.04 x 10 ⁶
4	1.06 x 10 ⁶	1.04 x 10 ⁶
5	1.06 x 10 ⁶	1.05 x 10 ⁶
6	1.03 x 10 ⁶	1.05 x 10 ⁶
Min =	1.03 x 10 ⁶	1.03 x 10 ⁶
Max =	1.06 x 10 ⁶	1.05 x 10 ⁶
Mean =	1.05 x 10 ⁶	1.04 x 10 ⁶

References:



ANSI/ESD SP9.2 – Figure 1: Foot Grinder Resistance Test