

Process calibrators // UC RTD.2

for resistance thermometers



UC RTD.2



Highlights

- Precise simulation and measurement of RTD signals
- Simple to use and robust housing
- For mobile on-site calibration

Technical data

Resistance thermometers (RTD)

Generation and measurement of RTD signals	Pt50, Pt100, Pt200, Pt500, Pt1000, Cu10, Cu50, Ni100, Ni120, Ni1000
Ω -generator function	0...3500 Ω
Ω -measurement function	0...3600 Ω
Accuracy (of reading + const.)	$\pm 0.012\%$
Selectable temperature unit	$^{\circ}\text{C}$ / $^{\circ}\text{F}$
Measurement of multi-wire connections	2 / 3 / 4

Technical data

Functions	
Generation	
High-speed call values	10 points (flexible)
Linear steps and ramps	✓
User-defined synthesiser values	10
User-defined signal output characteristic	10 points
Editable units	✓
Measurement	
Data memory	10 000 values
Value tables and graphics function	✓
Offset programming for sensor characteristic	✓
Calibration data files and linearisation points	5 x 4 values
User-defined measuring input characteristic	10 points
Editable units	✓
Measured value min. / max.	✓
Measured value hold function	✓
Averaging function	✓

General data	
Features	
Sensor connection	4 safety sockets (1 channel) incl. 2 sets with safety instrument leads (4 mm) and alligator clips (optional)
Power supply	4 x 1.5 V AA-battery, Operating time approx. 40 h or rechargeable battery including power adapter 230 VAC / 12 VDC (optional)
PC Interface	mini-USB Type B
Operator guidance	Menu with pull-down windows, programming and control via PC
Display	Multifunction display, LCD, 6 digit
Housing	
Version	ABS plastic with protective cover
Dimensions	160 x 85 x 45 mm (H x W x D)
Weight	Approx. 300 g

Article numbers

Order code		
Type	Version	Order number
UC RTD.2	Accuracy ± 0.012 % of reading + const.	EME8AOUCRTD020

Order code	
Accessories	Order number
DAkKS certificate	EKSIMMONO0000D
SIKA works calibration certificate	EKSIMMONO0000W
Transport case	EME8GKK3100000
Plug connector 4 mm, red	EME8AOSKLS40RT
Plug connector 4 mm, black	EME8AOSKLS40SW
Software Datacal for UC RTD.2	EME8AOMCSDWCKA
Battery and charger for UC series	EME8AOAN601100