


The simalube lubricator is available in 15, 30, 60, 125 and 250 ml sizes. The compact design of all of the simalube lubricators makes it possible to apply in tight spaces, as well as with numerous lubricants.

<b>Product</b>	Automatic grease and oil lubricator			
<b>Power generation</b>	Hydrogen gas producing dry cells			
<b>Working pressure</b>	Max. 5 bar			
<b>Adjustment</b>	Stepless 1–12 months			
<b>Dispensing quantity</b>	0.04–8.3 ml/day			
<b>Operating temperature</b>	–20 °C to +55 °C			
<b>Usage</b>	The lubricator can be installed in any position, even underwater. Attention: do not expose to direct heat			
<b>Certifications / Approvals</b>	 KEMA 09ATEX0098X IECEx DEK 20.0032X			
	<b>Marking typ 30, 60, 125 ml:</b> II 1 G Ex ia IIC T6 Ga II 1 D Ex ia IIIC T200 80 °C Da I M1 Ex ia I Ma			
	<b>Marking typ 250 ml:</b> II 1 G Ex ia IIC T4 Ga II 1 D Ex ia IIIC T200 135 °C Da I M1 Ex ia I Ma			
<b>Ingress protection</b>	IP68 (dustproof and waterproof)			
<b>Usage period</b>	Activation within 2 years of production date			
<b>Stock temperature</b>	Recommended at 20 °C ± 5 °C			
<b>Sizes</b>	<b>15 ml</b>	<b>30 ml</b>	<b>60 ml</b>	<b>125 ml</b>
<b>Weight full</b>	~36 g	~82 g	~115 g	~190 g
<b>Weight empty</b>	~22.5 g	~55 g	~60 g	~75 g
<b>Refill</b>	The 15–250 ml simalubes are refillable.			

