

LHMF 300 and LHDF 900

Mounting and dismounting fluids

For bearing mounting

Mounting fluid LHMF 300

SKF Mounting Fluid is suitable for use with SKF hydraulic equipment, including hydraulic pumps, HMV ..E nuts and oil injection tools. SKF LHMF 300 contains anti-corrosives which are non-aggressive to seal materials such as nitrile rubber, perbunan, leather and chrome leather, PTFE, and so on.



LHMF 300

For bearing dismounting

Dismounting fluid LHDF 900

SKF Dismounting Fluid is suitable for use with SKF hydraulic equipment, including hydraulic pumps and oil injection tools. SKF LHDF 900 contains anti-corrosives which are non-aggressive to seal materials such as nitrile rubber, perbunan, leather and chrome leather, PTFE, and so on.



LHDF 900

Technical data

Designation	LHMF 300/pack size	LHDF 900/pack size
Specific gravity	0.882	0.885
Flash point	200 °C (390 °F)	202 °C (395 °F)
Pour point	-30 °C (-22 °F)	-28 °C (-18 °F)
Viscosity at 20 °C (68 °F)	307 mm ² /s	910 mm ² /s
Viscosity at 40 °C (104 °F)	116 mm ² /s	330 mm ² /s
Viscosity at 100 °C (212 °F)	17.5 mm ² /s	43 mm ² /s
Viscosity index	167	187
Colour	Amber	Amber
Rust test ASTM D665 A/B	Pass	Pass
Cleanliness	ISO 4406:2021 18/17/13	ISO 4406:2021 18/17/13
Available pack size	1, 5, 205 litre	5 and 205 litre

These characteristics represent typical values.



skf.com | skf.com/mapro | skf.com/lubrication

® SKF is a registered trademark of AB SKF (publ).

© SKF Group 2023. All rights reserved. Please note that this publication may not be copied or distributed, in whole or in part, unless prior written permission is granted.

Every care has been taken to ensure the accuracy of the information contained in this publication, but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB MP/P8 17380/1 EN · July 2023