

## SKF Shaft Alignment Tool TKSA 11

New technology makes shaft alignment easier and more affordable



The SKF TKSA 11 is an innovative shaft alignment tool that uses smartphones and tablets and intuitively guides the user through the shaft alignment process. With a focus on the core alignment tasks, the TKSA 11 is designed to be a very easy-to-use instrument that is especially suitable for alignment learners and compact applications. The SKF TKSA 11 is the first instrument on the market that uses inductive proximity sensors, enabling accurate and reliable shaft alignment to be affordable for every budget.

- Live view of the instrument and motor position makes the measurement and horizontal alignment intuitive and easy.
- The TKSA 11 app offers a fully functional demonstration mode allowing the complete alignment process to be experienced without the need to purchase the TKSA 11.
- The TKSA 11 is designed to give a fast return on its investment and is also affordable for almost every budget.
- By using inductive proximity sensors, the measurement is no longer affected by bright sunlight, the influence of backlash is reduced and the instrument becomes more robust. All enabling the TKSA 11 to deliver accurate and reliable shaft alignments.
- Automatic alignment reports give a complete overview of the alignment process and results. Reports can easily be shared via email or cloud services.



Technical data			
Designation	TKSA 11		
Sensors and communication	2× Inductive proximity sensors Inclinometer ±0.5°, Bluetooth 4.0 LE	Fixture	2×V-brackets with chains, width 15 mm (0.6 in.)
		Shaft diameters	20 to 160 mm (0.8 to 6.3 in.)
System measuring distance	0 to 185 mm (0 to 7.3 in.) between brackets 3 × reference bars included up to 200 mm (7.9 in.)	Max. coupling height 1)	55 mm (2.2 in.) with standard 80 mm rods (Unit should be mounted on the coupling when possible)
Measuring errors	<2%	Power adapter	Charging via micro USB port (5V) Micro USB to USB charging cable supplied Compatible with 5V USB chargers (not included)
Housing material	PC/ABS plastic		
Operating time	Up to 18 hours, rechargeable LiPo battery		
Dimensions	$105 \times 55 \times 55$ mm (4.1 × 2.2 × 2.2 in.)	Operating temperature	0 to 45 °C (32 to 113 °F)
Weight	155 g (0.34 lb)	IP rating	IP 54
Operating device	Samsung Galaxy Tab Active 2 and iPad Mini recommended iPad, iPod Touch iPhone SE, Galaxy S6 or above (all not included)	Carrying case dimensions	355 × 250 × 110 mm (14 × 9.8 × 4.3 in.)
		Total weight (incl. case)	2,1 kg (4.6 <i>lb</i> )
		Calibration certificate	Supplied with 2 years validity
Software/App update	Apple AppStore or on Google Play Store	with chains 480 mm (18.9 in.) and rods 80 mm (3.1 in.); micro USB to USB charging cable;	Measuring unit; 3 reference bars; 2 shaft brackets
Operating system requirements	Apple iOS 9 or Android OS 9 (and above)		
Alignment method	Alignment of horizontal shafts 3 position measurement 9–12–3		measuring tape 2 m (6.6 ft.); printed certificate of
Live correction values	Only for horizontal		guide (EN); SKF carrying case
Extra features	Automatic .pdf report		

1) Depending on the coupling, the brackets can be mounted on the coupling, reducing the coupling heigt limitation.



Shaft alignment is recommended for almost every industry, as it enables machine uptime to be significantly improved and maintenance costs to be reduced.

The TKSA 11 focuses on industries where these shaft alignment benefits have not yet been realised and helps customers profit from correctly aligned shafts.

## skf.com | skf.com/mapro | skf.com/lubrication

- SKF is a registered trademark of AB SKF (publ).
   App Store is a service mark of Apple Inc. registered in the US and other countries.
   Android and Google Play are trademarks of Google Inc.
- © SKF Group 2023. All rights reserved. Please note that this publication may not be copied ordistributed, in whole or in part, unless prior written permission is granted.

Every care has been taken to ensure the accuracy of the information contained in this publication, but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.