



Image may differ from product. See technical specification for details.



TMMP 2X65

Standard jaw puller, 2 armed

One of the most common ways to dismount small to medium size bearings is to use a mechanical puller. The SKF TMMP 2X65 is a small two arm puller for small bearings and short dismounting distances. Provided with a handle bar to generate the pulling force. The SKF Standard Jaw Pullers TMMP series allow for easy and fast dismounting jobs and safe puller operation.

- Cone system for automatic centring and secure positioning of arms
- Strong springs keep arms apart for easy operation
- Hardened, high quality carbon steel

Overview

Dimensions

Width of grip external	0.5906 – 2.5591 in
Effective arm length	2.3622 in
Claw height	0.315 in
Claw length	0.2756 in
Claw width	0.3937 in
Total spindle length	5.4 in

Properties

Recommended applications	For the dismantling of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft
Suitable for workpiece dismantling from a Cylindrical seating (straight shaft)	Yes
Suitable for bearing dismantling from a Tapered seating (conical shaft)	Yes
Suitable for bearing dismantling from a Sleeve (adapter or withdrawal sleeve)	Yes
Suitable for workpiece dismantling from a Blind arrangement (housing with shaft)	No
Suitable for workpiece dismantling from a Housing	No
Suitable for bearing type(s)	All
Dismounting force generation	Spindle
Special features	Cone-system for automatic centring and locking of the arms
Number of arms	2
Pulling force (max)	0.61 tf
Spindle torque (max)	7.38 lbf-ft
Spindle nose piece	No
Colour	Black
Material	Alloy engineering steels, hardened and tempered
Coating	Chemical blackened
Content	1x Puller TMMP 2x65 1x Printed instructions for use

Logistics

Product net weight	1.04 lb
eClass code	23-05-19-01
UNSPSC code	27111712

Compatible products

Accessory

Puller protection blanket	TMMX 210
---------------------------	--------------------------

Recommended product

Standard jaw puller, 2 armed	TMMP 2X170
Standard jaw puller, 3 armed	TMMP 3X185
Standard jaw puller, 3 armed	TMMP 3X230

Standard jaw puller, 3 armed

[TMMP 3X300](#)



Terms of use