Image may differ from product. See technical specification for details.

TMMR 60F

Reversible jaw puller

The multi-purpose SKF Reversible Jaw Puller TMMR 60F is designed for internal and external pulling jobs of bearings and other components such as gears and pulleys. The two arms of the puller can be mounted with the claws facing inside or facing outside, making it a versatile and essential tool for mechanical workshops.

- Easy adjustment of the width of grip with self-locking arms
- Essential and versatile tools for every workshop for internal and external pulling appliactions
- Enhanced corrosion resistance and easy cleaning with zinc passivated arms and beam
- No permanent deformation of puller arms when used up to maximum withdrawl force
- Optional accessories further increase the versatility of the puller

Overview

Logistics

Product net weight	0.99 lb
eClass code	23-05-19-01
UNSPSC code	27111712

Properties

Recommended applications	For the dismounting of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Yes
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Yes
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Yes
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	No
Suitable for workpiece dismounting from a Housing	Yes, with spindle support (not included)
Suitable for bearing type(s)	All
Dismounting force generation	Spindle
Special features	Reversible arms Selflocking arms
Number of arms	2
Width of grip external	0.9055 – 2.6772 in
Width of grip internal	2.4409 – 3.4252 in
Effective arm length	3.2283 in
Total Arm length	4.6 in
Claw height	0.1575 in
Claw length	0.2362 in
Claw width	0.5118 in
Spindle torque (max)	16.2 lbf·ft
Spindle head, hexagon size	13
Puller or Adapter hexagon size	0.5512 in
Spindle nose piece	No
Material	Alloy engineering steels, hardened and tempered
Coating	Zinc coated
Content	1x Puller TMMR 60F 1x Tube of spindle grease LGEV2/0.035 1x Printed instructions for use

Dimensions

Total spindle length	6.0 in

Compatible products

Parent product

Reversible jaw puller set	TMMR 4F/SET
Reversible jaw puller set	TMMR 8F/SET
Reversible jaw puller set	TMMR 8XL/SET

Refill

Extremely high viscosity bearing grease with solid lubricants	LGEV 2/0.035

Spare part

Spare spindle for Reversible jaw puller	TMMR 60F-3

Recommended product

Reversible jaw puller	TMMR 40F
Reversible jaw puller	TMMR 80F
Reversible jaw puller	TMMR 120F
Reversible jaw puller	TMMR 160F
Reversible jaw puller	TMMR 200F
Reversible jaw puller	TMMR 250F
Reversible jaw puller	TMMR 350F
Reversible jaw puller, long arms	TMMR 160XL
Reversible jaw puller, long arms	TMMR 200XL
Reversible jaw puller, long arms	TMMR 250XL
Reversible jaw puller, long arms	TMMR 350XL

SKF

Terms of use