



## Measuring leads

### MAL S WS 2-4 100/1



Product	MAL S WS 2-4 100/1
description	<p>Safety measuring lead according to IEC 61010, one end with 2mm safety plug and other end with 4mm safety plug, as well as 2 mm and 4 mm socket for onward connection capability.</p> <p>Gold-plated / nickel-plated copper-beryllium contact spring.</p> <p>Highly flexible, double insulated stranded lead, with good firm grip sleeves.</p> <p>Built in color indicator to detect damage to the cable insulation.</p>
operating instruction	BA252
article-no. / *colour	9751631xx <div>  <div> 00 black 01 red 02 blue 03 yellow 04 green 05 brown 06 gray 07 white 09 violet 88 yellow green </div> </div>
drawing	
	
technical data	
rated voltage	AC/DC 1000 V
measurement cat. acc. to IEC 61010	CAT II
rated current (consider derating curve)	10 A
material socket	contact pin: brass contact spring: copper - beryllium
housing material	PA
temperature range acc. To IEC61010 <sup>(1)</sup>	-15 °C to +70 °C
flammability class acc. to UL 94 (only valid for basic material of housing)	V-2
cable length	100 cm
conductor size	1 mm <sup>2</sup>
cable material	PVC

2 mm safety system

<sup>(1)</sup> contact the manufacturer for applications at deviating temperature ranges  
stand: 21.06.2022

stand: 21.06.2022