







## Sockets

### PKI 100



Product	PKI 100
description	Pole terminal with captive insulated head, which is held under constant pressure against the insulated rings by a spring. 4 mm diameter nickel-plated, brass threaded bolt with 2 mm diameter transverse hole. For non-rotating installation in switchpanels and equipment chassis with wall thickness up to 3.5 mm.
operating instruction	BA402
article-no. / *colour	9307571xx <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">               00 black           </div> <div style="text-align: center;">               01 red           </div> <div style="text-align: center;">               02 blue           </div> <div style="text-align: center;">               03 yellow           </div> <div style="text-align: center;">               04 green           </div> <div style="text-align: center;">               88 yellow green           </div> </div> <div style="text-align: right; border: 1px solid black; padding: 2px; width: fit-content;">Ni</div>
drawing	
	<p style="text-align: center;">Einbauöffnung installation hole</p>
technical data	
connection	M4 thread
rated voltage	30 VAC / 60 VDC
measurement cat. acc. to IEC 61010	O <sup>(2)</sup>
rated current (consider derating curve)	35 A
material socket	brass, nickel plated
housing material	PA
temperature range acc. To IEC61010 <sup>(1)</sup>	-25 °C to +100 °C
inflammability class acc. to UL 94 (only valid for basic material of housing)	V-2

4 mm system

<sup>(1)</sup> contact the manufacturer for applications at deviating temperature ranges

<sup>(2)</sup> without rated measurement category, for other circuits that are not directly connected to mains  
stand: 21.06.2022

stand: 21.06.2022