

Start International
PRODUCT IDENTITY: PC101 THINNER
NEW MSDS DATE: 01/01/2012

DATE: 01/01/2012

PAGE 1 OF 7

MATERIAL SAFETY DATA SHEET

This Material Safety Data Sheet conforms to the requirements of ANSI Z400.1.
THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)
IMPORTANT: Read this MSDS before handling & disposing of this product.
Pass this information on to employees, customers, & users of this product.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

PRODUCT IDENTITY: PC101 THINNER
COMPANY IDENTITY: Start International
COMPANY ADDRESS: 4270 Airborn Drive
COMPANY CITY: Addison, TX 75001
COMPANY PHONE: 1-972-248-1999
CHEMTREC PHONE: 1-800-424-9300

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

CONTAINS: 50-60% XYLENES (1330-20-7) [215-535-7],
25-35% TOLUENE (108-88-3) [203-625-9],
10-15% ETHYLBENZENE (100-41-4) [202-849-4]

Number in parentheses is CAS #, number in brackets is European EC #.

XYTOB3

SECTION 3. HAZARDS IDENTIFICATION

RISK STATEMENTS:

R11 Highly Flammable.
R36/37/38 Irritating to eyes, respiratory system and skin.
R20/65 Harmful by inhalation, may cause lung damage if swallowed.

SAFETY STATEMENTS:

S16 Keep away from sources of ignition. No smoking.
S29 Do not empty into drains.
S24/25 Avoid contact with skin and eyes.

SECTION 4. FIRST AID MEASURES

EYE CONTACT:

For eyes, flush with plenty of water for 15 minutes & get medical attention.

SKIN CONTACT:

In case of contact with skin immediately remove contaminated clothing.
Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

INHALATION:

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped give artificial respiration.

SWALLOWING:

If swallowed, CALL A PHYSICIAN IMMEDIATELY! Do NOT induce vomiting. Have patient lie down & keep warm. Vomiting may lead to pneumonitis, which may be fatal.

XYTOB3

XYTOB3

SECTION 5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

NFPA Class B extinguishers(Carbon Dioxide or foam)for Class I B liquid fires.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used.
Do not enter confined fire-space without full bunker gear.
(Helmet with face shield,bunker coats, gloves & rubber boots).
Use NIOSH approved positive-pressure self-contained breathing apparatus.

UNUSUAL EXPLOSION AND FIRE PROCEDURES

HIGHLY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE

Keep container tightly closed.
Isolate from oxidizers, heat, sparks, electric equipment & open flame.
Closed containers may explode if exposed to extreme heat.
Applying to hot surfaces requires special precautions.
Empty container very hazardous! Continue all label precautions!

SECTION 6. ACCIDENTAL RELEASE MEASURES

CONTAINMENT TECHNIQUES

Stop spill at source. Dike area & contain.

CLEAN-UP PROCEDURES:

Clean up remainder with absorbent materials. Mop up & dispose of. Persons without proper protection should be kept from area until cleaned up.

Start International
PRODUCT IDENTITY: PC101 THINNER
NEW MSDS DATE: 01/01/2012

DATE: 01/01/2012
PAGE 3 OF 7

SECTION 7. HANDLING AND STORAGE

HANDLING

Isolate from oxidizers, heat, sparks, electric equipment & open flame.
Use only with adequate ventilation. Avoid breathing of vapor or spray mist.
Avoid prolonged or repeated contact with skin.
Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier.
Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.
Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld. Empty container very hazardous! Continue all label precautions!

STORAGE

Do not store above 49 C/120 F. Store large amounts in structures made for OSHA Class I B liquids
Keep container tightly closed
& upright when not in use to prevent leakage.

XYTOB3

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION:

EXPOSURE CONTROLS

Ventilate to keep vapors of this material below 30 ppm.
If over TLV, in accordance with 29 CFR 1910.134,
use NIOSH approved positive-pressure self-contained breathing apparatus.
Consult Safety Equipment Supplier. Use explosion-proof equipment.

VENTILATION

LOCAL EXHAUST	: Necessary
MECHANICAL (GENERAL)	: Acceptable
SPECIAL	: None
OTHER	: None

PERSONAL PROTECTIONS:

Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier.
Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.

WORK & HYGIENIC PRACTICES:

Provide readily accessible eye wash stations & safety showers.
Wash at end of each workshift & before eating, smoking or using the toilet.
Promptly remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

Start International
PRODUCT IDENTITY: PC101 THINNER
NEW MSDS DATE: 01/01/2012

DATE: 01/01/2012
PAGE 4 OF 7

SECTION 9. PHYSICAL DATA

APPEARANCE : Liquid, Water-White
ODOR : Aromatic
BOILING RANGE : 115 132 142 C / 239 271 288 F
AUTO IGNITION TEMPERATURE : 510 C / 950 F (Lowest Component)
LOWER FLAMMABLE LIMIT IN AIR (% by vol): 1.2
FLASH POINT (TEST METHOD): 11 C / 52 F (TCC)
FLAMMABILITY CLASSIFICATION: Class I B
GRAVITY @ 60 F :
API : 31.1
SPECIFIC GRAVITY (Water=1) : .870
POUNDS/GALLON : 7.247
VOC'S (>0.44 Lbs/Sq In) : 100.1 Vol. % / 871.0 g/L / 7.255 Lbs/Gal
TOTAL VOC'S (TVOC) : 100.0 Vol. % / 870.0 g/L / 7.247 Lbs/Gal
NONEXEMPT VOC'S (CVOC) : 100.0 Vol. % / 870.0 g/L / 7.247 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS) : 100.0 Wt. % / 870.0 g/L / 7.247 Lbs/Gal
VAPOR PRESSURE (mm of Hg) @ 20 C 11.9
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C) 11.9
VAPOR DENSITY (air=1) : 3.5
WATER ABSORPTION : Negligible
REFRACTIVE INDEX : 1.496

SECTION 10. STABILITY & REACTIVITY

STABILITY

Stable

CONDITIONS TO AVOID

Isolate from oxidizers, heat, sparks, electric equipment & open flame.

MATERIALS TO AVOID

Isolate from strong oxidizers such as permanganates, chromates & peroxides.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon Monoxide, Carbon Dioxide from burning.

HAZARDOUS POLYMERIZATION

Will not occur.

XYTOB3

SECTION 11. TOXICOLOGICAL INFORMATION

MATERIAL	CAS #	TWA (OSHA)	TLV (ACGIH)	HAP
Xylenes	1330-20-7	100 ppm	100 ppm A4	Yes
Toluene	108-88-3	200 ppm	50 ppm A4	Yes
Ethylbenzene	100-41-4	100 ppm	100 ppm A3	Yes

In addition to EPA Hazardous Air Pollutants showing 'Yes' under "HAP" above, using manufacturers' data, based on EPA Method 311, the following EPA

Hazardous Air Pollutants may be present in trace amounts (less than 0.1%):

Benzene, Cumene

PRODUCT IDENTITY: PC101 THINNER

PAGE 5 OF 7

NEW MSDS DATE: 01/01/2012

XYTOB3

SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)

MATERIAL	CAS #	CEILING	STEL (OSHA/ACGIH)
Xylenes	1330-20-7	None Known	150 ppm
Ethylbenzene	100-41-4	None Known	125 ppm

ACUTE HAZARDS

EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis.

Absorption thru skin increases exposure.

Primary irritation to eyes, redness, tearing, blurred vision.

Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure

can cause serious nervous system depression. Vapor harmful.

Acute overexposure can cause damage to kidneys, blood, nerves, liver & lungs.

SWALLOWING:

Harmful or fatal if swallowed.

Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED

CONDITIONS AGGRAVATED

Chronic overexposure can cause damage to kidneys, blood, nerves, liver & lungs.

Persons with severe skin, liver or kidney problems should avoid use.

CHRONIC HAZARDS

CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:

Potential Cancer Hazard based on tests with laboratory animals using Ethylbenzene.

Overexposure may create cancer risk.

Leukemia been reported in humans from Benzene.

This product contains less than 160 ppm of Benzene.

Not considered hazardous in such low concentrations.

Absorption thru skin may be harmful. Studies with laboratory animals indicate this product can cause damage to fetus.

Start International
PRODUCT IDENTITY: PC101 THINNER
NEW MSDS DATE: 01/01/2012

DATE: 01/01/2012
PAGE 6 OF 7

SECTION 12. ECOLOGICAL INFORMATION

MAMMALIAN INFORMATION:

MATERIAL	CAS #	LOWEST KNOWN LETHAL DOSE DATA
		LOWEST KNOWN LD50 (ORAL)
Toluene	108-88-3	3000.0 mg/kg(Rats)
		LOWEST KNOWN LC50 (VAPORS)
Xylene	1330-20-7	5000 ppm (Mice)

AQUATIC ANIMAL INFORMATION:

The most sensitive known aquatic group to any component of this product is:
Fish are adversely affected by
components of this product.

MOBILITY

This material is a mobile liquid.

DEGRADABILITY

This product is nonbiodegradable.

ACCUMULATION

This product does not accumulate or biomagnify in the environment.

SECTION 13. DISPOSAL CONSIDERATIONS

Recycle / dispose of observing national, regional, state, provincial and local
health, safety & pollution laws.

If questions exist, contact the appropriate agencies.

SECTION 14. TRANSPORT INFORMATION

DOT SHIPPING NAME: RQ,Flammable Liquids,n.o.s.

(Xylene,Toluene),3,UN1993,PG-II

IF > 178 POUNDS OF THIS PRODUCT IS IN ONE CONTAINER THE "RQ" OF
XYLENE IS EXCEEDED.

DRUM LABEL: (FLAMMABLE LIQUID)

IATA / ICAO: RQ,Flammable Liquids,n.o.s.

(Xylene,Toluene),3,UN1993,PG-II

IMO / IMDG: RQ,Flammable Liquids,n.o.s.

(Xylene,Toluene),3,UN1993,PG-II

EMERGENCY RESPONSE GUIDEBOOK NUMBER: 128

XYTOB3

SECTION 15. REGULATORY INFORMATION

EPA REGULATION:

SARA SECTION 311/312 HAZARDS: Acute Health, Fire

All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notification

This product contains the indicated <*> toxic chemicals subject to the
reporting requirements of Section 313 of the Emergency Planning & Community
Right-To-Know Act of 1986 & of 40 CFR 372. This information must be
included in all MSDSs that are copied and distributed for this material.

Start International
PRODUCT IDENTITY: PC101 THINNER
NEW MSDS DATE: 01/01/2012

DATE: 01/01/2012
PAGE 7 OF 7

XYTOB3 SECTION 15. REGULATORY INFORMATION (CONTINUED)

SARA TITLE III INGREDIENTS	CAS#	WT. % (REG. SECTION)	RQ(LBS)
*Xylenes	1330-20-7	<60 (311,312,313,RCRA)	100
*Toluene	108-88-3	<40 (311,312,313,RCRA)	1000
*Ethylbenzene	100-41-4	<20 (311,312,313,RCRA)	None

IF > 178 POUNDS OF THIS PRODUCT IS IN ONE CONTAINER THE "RQ" OF
XYLENE IS EXCEEDED.

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65: This product contains the following chemicals
known to the State of California to cause cancer & reproductive toxicity:
Ethylbenzene, Toluene

INTERNATIONAL REGULATIONS

The components of this product are listed on the chemical
inventories of the following countries:

Australia, Canada, Europe (EINECS), Japan, Korea, United Kingdom.

SECTION 16. OTHER INFORMATION

HAZARD RATINGS:
HEALTH (NFPA): 2
HEALTH (HMIS): 2
FLAMMABILITY: 3
REACTIVITY: 0

This information is intended solely for the use of individuals
trained in the NFPA & HMIS hazard rating systems.

EMPLOYEE TRAINING

Employees should be made aware of all hazards of this material (as stated
in this MSDS) before handling it.

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability
or fitness for a specific use, with respect to the product or the information
provided herein, except for conformation to contracted specifications.

All information appearing herein is based upon data obtained from manufacturers
and/or recognized technical sources. While the information is believed to be
accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible
for verifying the data under their own operating conditions to determine
whether the product is suitable for their particular purposes and they assume
all risks of their use, handling, and disposal of the product. Users also
assume all risks in regards to the publication or use of, or reliance upon,
information contained herein.

This information relates only to the product designated herein, and does not
relate to its use in combination with any other material or process.