

# 8400 Series - ESD Vinyl Floor Tile Maintenance

Carefully read and follow all product literature including all safety, health and environmental information found in the material safety data sheet and/or product label of chemicals prior to handling or use.

## Daily Floor Maintenance

### Prevent Dirt and Wear

Install [Tacky Mats](#) at all Entry Doors

### Remove Dust and Debris

Sweep or vacuum daily

## Clean

Damp mop as needed

### Normal Cleaning

For Dirt, Grime and Scuff Marks

Use **Low-Speed Swing Buffer**  
or **Automatic Scrubber**

#### Recommended Cleaning Pad:

- Red Buffer Pad

### Heavy Cleaning

For Tough Marks

Use **Low-Speed Swing Buffer**  
or **Automatic Scrubber**

#### Use Recommended Cleaning Pad:

- Blue Cleaner Pad
- Green Scrub Pad
- Brown Stripper Pad\*

*\*Liberally apply Statguard® Floor Stripper when using the Brown Stripper Pad to avoid damaging floor.*

### Low-Speed Swing Buffer

1. Apply Statguard® ESD Floor Cleaner ([46032/46033](#)) with mop
2. Scrub with appropriate cleaning pad
3. Damp mop to wipe up soiled solution
4. Damp mop with clean solution
5. Allow to dry completely
6. If tough marks remain, repeat "Normal Cleaning" process using the same pad or switch to a recommended "Heavy Cleaning" pad

### Automatic Scrubber

1. Fill solution tank with Statguard® Stripper ([46020/46021](#))
2. Install proper pads on machine
3. Scrub floor and pick up dirty solution (automatic)
4. If tough marks remain, repeat "Heavy Cleaning" process using the same pad, or the other pads listed
5. Use the Statguard® Floor Neutralizer ([46022](#)) to rinse and bring the pH level down to level 7.0 (neutral).

## Buff and Shine Floor

### Once Floor is Cleaned and Completely Dry

- Buff to shine with low speed "swing" buffer and a clean, dry red buffer pad