

STATICO

Product Information for S0102 Adjustable Wrist Grounding Strap



Description

Adjustable wrist grounding strap through Velcro® & D-Ring with inner layer skin contact, an alligator clip, and a 6ft or 12ft coil cord. Meets ANSI/ESD S1.1-2013 & ANSI/ESD S20.20-2014.

Specifications

A. Adjustable Wrist Band	
Inner Surface	Blue Ribbon with Conductive White Treads, Sewn-On Velcro®
Outer Surface	Black Color Velcro®
Inner Surface	Polycarbonate
Metal Base	No. 304 Stainless Steel
Stud	1/8" (4mm) Brass
B. Coil Cord	
Conductor	7-Strand Single Tinsel Wire
Jacket Insulation	90 Shore A Polyurethane
Wire Diameter	0.09"
Coil Diameter	0.04"+0.02"
Cable Break Load	< 28 lbs.
Pull Force (Molded Plug End)	< 25 lbs.
Bending Test	>36,000 Cycles
2,000 Bending Cycle/Hour	
500g Load Weight	>120°

Part Numbers

S0102-06	Adjustable wrist strap with 6ft Coiled cord, and an Alligator Clip, 1/8"(4mm) Snap.
S0102-12	Adjustable wrist strap with 6ft Coiled cord, and an Alligator Clip, 1/8"(4mm) Snap.
S0101B	Adjustable Band. 1/8"(4mm) Stud.
S0102-06C	6ft Coil cord. 1/8"(4mm) Snap.
S0102-12C	12ft-coil cord. 1/8"(4mm) Snap.