

STATICO

Product Specifications for S2020A Surface Resistivity/Resistance Test Kit



Description

S2020A is a pocket size, light weight, auto ranging (10V to 100V) surface resistivity/resistance indicator. The instrument features a dual application, as follows:

- It can be used as a handheld tester, with two-parallel bars on the back performing the test.
- It can be used with the two external 5lbs Probes.

Test results are indicated by LEDs:

Green	<10 ⁵ (Conductive)
Yellow	10 ⁶ To 10 ¹¹ (Dissipative)
Red	>10 ¹² (Insulative)

10E3= 1 Kilohm	Green LED
10E4= 10 Kilohm	Green LED
10E5= 100 Kilohm	Green LED
10E6= 1megohm	Yellow LED
10E7= 10 megohm	Yellow LED
10E8= 100 megohm	Yellow LED
10E9= 1,000 megohm	Yellow LED
10E10= 10,000 megohm	Yellow LED
10E11= 100,000 megohm	Yellow LED
10E12= 1,000,000 megohm	RED LED
>10E13= Insulative	RED LED

The Kit Consists of:

- 1 Each The Tester (S2020A)
- 1 Each Leather-like Carrying Case
- 1 Each a 9V Battery
- 2 Each Connecting Cords (Tester-To-Probes)
- 2 Each 5 lbs Probes

All are housed in a heavy duty hinged plastic case with foam inserts.

Technical Data:

Size	:	131X65X30mm (LXWXH)
Weight	:	240g
Test Range	:	10 ³ to 10 ¹²
Test Voltage	:	10V/100V (Auto Range)
Accuracy*	:	+/-10%
Power Supply	:	9 V Alkaline Battery
Test Voltage	:	Nominal 9 V
Temperature Range:	:	Operating: 40° to 120°F (5°-to-49°C)
Storage	:	-15° to +60°C
Relative Humidity	:	0% to 90% (non-condensing)

*the S2020A is calibrated to ensure that the proper LEDs illuminate when their corresponding load resistances are applied. All load resistances have a $\pm 10\%$ accuracy. No claims are made for the actual resistance values that trigger the change in LEDs.