

# 1 GHz and 500 MHz High Voltage Differential Probes

TDP1000 • TDP0500 • P6251 Datasheet



## Features & Benefits

### Outstanding Electrical Performance

- 1 GHz and 500 MHz Probe Bandwidth
- <1 pF Differential Input Capacitance
- 1 M $\Omega$  Differential Input Resistance
- $\pm 42$  V (DC + pk AC) Differential Input Voltage
- >18 dB CMRR (at 250 MHz 50X attenuation)
- Selectable Bandwidth-limiting Filters
- DC Reject

### Versatile DUT Connectivity

- Small Compact Probe Head for Probing Small Geometry Circuit Elements
- Straight Pin, Square Pin, Solder Down, Variable Pitch Standard Accessories
- Robust Design for Reliability

### Easy to Use

- Provides Automatic Units Scaling and Readout on the Oscilloscope Display
- TDP1000, TDP0500
  - Connect Directly to Oscilloscopes with the TekVPI™ Probe Interface
  - Easy Access to Scope-displayed Probe Menu for Probe Setup Control and Operating Status Information
  - Remote GPIB/USB Probe Control through the Oscilloscope
  - AutoZero – Zeros Out Output Offset
- P6251
  - Connect Directly to the TekProbe™ Interface Oscilloscopes, or to TekConnect® Oscilloscopes using TCA-BNC Adapter

## Applications

- High-speed Switch Mode Power Supply Design
- CAN/LIN Bus Design
- High-speed Digital Design
- Digital Design and Characterization
- Manufacturing Engineering Test
- Research and Development

The TDP1000, TDP0500, and P6251 High-voltage Differential Probes provide excellent high-speed electrical and mechanical performance required for today's Switch Mode Power Supply (SMPS), CAN/LIN Bus, and high-speed digital system designs.

Specifically designed for use with and direct connection to Tektronix oscilloscopes with either the TekVPI™ probe interface, or TekProbe BNC Interface. The TDP1000, TDP0500, and P6251 High-voltage Differential Probes achieve high-speed signal acquisition and measurement fidelity by solving three traditional measurement challenges:

- Outstanding Electrical Performance
- Versatile Device-Under-Test Connectivity
- Ease of Use

## Characteristics

Characteristic	Description
Bandwidth (Probe only)	1 GHz (TDP1000, P6251) 500 MHz (TDP0500)
Attenuation	5X, 50X
Rise Time (Probe only)	≤350 ps (TDP1000, P6251) <700 ps (TDP0500)
Differential Input Capacitance	<1 pF
Differential Input Resistance	1 MΩ
CMRR	>55 dB at 30 kHz >50 dB at 1 MHz >18 dB at 250 MHz (warranted at 50X attenuation)
Sensitivity/Noise Level	2 mV <sub>RMS</sub> (5X attenuation) 1 mV <sub>RMS</sub> (50X attenuation) referred to the probe output 10 mV <sub>RMS</sub> (5X attenuation) 50 mV <sub>RMS</sub> (50X attenuation) referred to the probe input
Differential Mode Input Voltage	±42 V (DC + pk AC); 30 V <sub>RMS</sub>
Common Mode Input Voltage	±35 V (DC + pk AC); 25 V <sub>RMS</sub>
Input Offset Range	
TDP1000, TDP0500	±42 V (5X or 50X attenuation)
P6251	±4.25 V (5X attenuation) ±42 V (50X attenuation)
Max Input Voltage (Nondestruct)	±100 V (DC + pk AC)
Selectable Bandwidth Filter Limits	
TDP1000, TDP0500	100 Hz, 10 kHz, 1 MHz, Full
P6251	5 MHz, Full
DC Reject	0.4 Hz (5X) 4 Hz (50X)
Gain Accuracy at DC	±2%
Propagation Delay	6.5 ns
Scope Interface	
TDP1000, TDP0500	TekVPI™ Probe Interface
P6251	TekProbe BNC Level II Interface

## Physical Characteristics

Dimensions	TDP1000, TDP0500		P6251	
	lb./in.	kg/cm	lb./in.	kg/cm
Weight	0.320 lb.	0.146 kg	0.360 lb.	0.163 kg
Compensation Box Dimensions				
Height	1.6 inches	4.1 cm	1.0 inches	2.6 cm
Width	1.2 inches	3.05 cm	1.6 inches	4.1 cm
Length	4.2 inches	10.7 cm	3.2 inches	8.13 cm
Cable Length	47.2 inches, 1.2 meters			

## Power Requirements

Device	Description
TDP1000, TDP0500	Powered directly by oscilloscopes with the TekVPI interface.
P6251	Powered directly by the TekProbe-BNC interface, eliminating the need for additional power supplies and cables when used with TekProbe-BNC oscilloscopes. May also be powered through the 1103 TEKPROBE Power Supply for use with non-TekProbe interface instrumentation.

Standard Warranty – 1-year parts and labor.

## Recommended Oscilloscopes

Probes	Interface	Adapter Required
TDP1000, TDP0500	TekVPI probe	—
P6251	TekProbe BNC-Level2	—
	TekConnect®	TCA-BNC

Note: For best probe support, download and install the latest version of the oscilloscope software from [www.tektronix.com](http://www.tektronix.com)

## Ordering Information

### TDP1000

1 GHz High-voltage Differential Probe with TekVPI Interface.

### TDP0500

500 MHz High-voltage Differential Probe with TekVPI Interface.

### P6251

1 GHz High-voltage Differential Probe with TekProbe-BNC Level II Interface.

### Standard Accessories

Certificate of Traceable Calibration included standard on all models.

Description	Qty Included With Product	Reorder Part Number (Qty in Reorder)
Y-Lead Set	2 each	196-3434-xx (1)
Solder-down Lead Set, 1 inch	1 each	196-3504-xx (1)
Solder-down Lead Set, 3 inch	1 each	196-3505-xx (1)
Micro CKT Test Tip	3 each	206-0569-xx (1)
Tip Savers	2 each	016-1781-xx (2)
Longhorn Adapters	2 each	016-1780-xx (5)
Straight-pin Probe Tips	8 each	016-1891-xx (8)
3-inch Ground Leads	2 each	196-3437-xx (2)
Color-coding Bands	2 each of 5 colors	016-1315-xx (2 each of 5 colors)
Nylon Carrying Case	1 each	016-1952-xx (1)
CD with Technical Reference Manual and Quick Start Users Guides	1 each	063-4110-xx (1)
<b>TDP0500 and TDP1000 only</b>		
Quick Start Users Guide	1 each	
English		071-1974-xx (1)
Japanese (with Opt. L5)		071-1975-xx (1)
Simplified Chinese (with Opt. L7)		071-1976-xx (1)
Documentation Kit CD, Includes: Quick Start Users Guide (English, Japanese, and Simplified Chinese versions); Technical Reference Manual	1 each	063-3941-xx (1)
<b>P6251 only</b>		
Documentation Kit CD, Includes: Quick Start Users Guide (English, Japanese, and Simplified Chinese versions); Technical Reference Manual	1 each	063-4110-xx (1)

### Manual Options (TDP1000, TDP0500 only)

Option	Description
Opt. L5	Japanese
Opt. L7	Simplified Chinese

## Recommended Accessories

Description	Part Number	Quantity
BNC to Probe Tip Adapter	067-1734-xx	1 each
Spring Loaded Grounds	016-1782-xx	1 pkg of 6
Twin Foot Adapter	016-1785-xx	1 pkg of 4
Twin Tip Adapter	016-1786-xx	1 pkg of 4
IC Micro Grabber	SMK4	1 pkg of 4
TEKPROBE Probe Power Supply	1103	1 each

## Service Options

Option	Description
Opt. C3	Calibration Service 3 Years
Opt. C5	Calibration Service 5 Years
Opt. R3	Repair Service 3 Years
Opt. R5	Repair Service 5 Years
Opt. SILV600	Standard Warranty Extended to 5 Years (TDP0500)
Opt. SILV900	Standard Warranty Extended to 5 Years (TDP1000 and P6251)

### Additional Service Products Available During Warranty (DW)

#### or Post Warranty (PW)

#### TDP0500 and TDP1000

TDP0500-CA1/ TDP1000-CA1	A single calibration event or coverage for the designated calibration interval, whichever comes first
TDP0500-R1PW/ TDP1000-R1PW	Repair service coverage, 1-year post warranty
TDP0500-R2PW/ TDP1000-R2PW	Repair service coverage, 2-year post warranty
TDP0500-R3DW/ TDP1000-R3DW	Repair service coverage 3 years (includes product warranty period) 3-year period starts at time of customer instrument purchase
TDP0500-R5DW/ TDP1000-R5DW	Repair service coverage 5 years (includes product warranty period) 5-year period starts at time of customer instrument purchase

#### P6251

P6251-CA1	A single calibration event or coverage for the designated calibration interval, whichever comes first
P6251-R1PW	Repair service coverage, 1-year post warranty
R6251-R2PW	Repair service coverage, 2-year post warranty
P6251-R3DW	Repair service coverage 3 years (includes product warranty period) 3-year period starts at time of customer instrument purchase
P6251-R5DW	Repair service coverage 5 years (includes product warranty period) 5-year period starts at time of customer instrument purchase



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.



Product(s) complies with IEEE Standard 488.1-1987, RS-232-C, and with Tektronix Standard Codes and Formats.

**Contact Tektronix:**

- ASEAN / Australasia** (65) 6356 3900
- Austria** 00800 2255 4835\*
- Balkans, Israel, South Africa and other ISE Countries** +41 52 675 3777
- Belgium** 00800 2255 4835\*
- Brazil** +55 (11) 3759 7627
- Canada** 1 800 833 9200
- Central East Europe and the Baltics** +41 52 675 3777
- Central Europe & Greece** +41 52 675 3777
- Denmark** +45 80 88 1401
- Finland** +41 52 675 3777
- France** 00800 2255 4835\*
- Germany** 00800 2255 4835\*
- Hong Kong** 400 820 5835
- India** 000 800 650 1835
- Italy** 00800 2255 4835\*
- Japan** 81 (3) 6714 3010
- Luxembourg** +41 52 675 3777
- Mexico, Central/South America & Caribbean** 52 (55) 56 04 50 90
- Middle East, Asia, and North Africa** +41 52 675 3777
- The Netherlands** 00800 2255 4835\*
- Norway** 800 16098
- People's Republic of China** 400 820 5835
- Poland** +41 52 675 3777
- Portugal** 80 08 12370
- Republic of Korea** 001 800 8255 2835
- Russia & CIS** +7 (495) 7484900
- South Africa** +41 52 675 3777
- Spain** 00800 2255 4835\*
- Sweden** 00800 2255 4835\*
- Switzerland** 00800 2255 4835\*
- Taiwan** 886 (2) 2722 9622
- United Kingdom & Ireland** 00800 2255 4835\*
- USA** 1 800 833 9200

\* European toll-free number. If not accessible, call: +41 52 675 3777

Updated 10 February 2011

**For Further Information.** Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit [www.tektronix.com](http://www.tektronix.com)



Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

26 Jul 2012

51W-19997-7

