# **TECHNI-PRO**

### **Product Data Sheet**

## Techni-Pro Black Metal Wrist Strap with 6-Foot Grouding Cord

TNP 758ST1064



### **Product Information**

Techni-Pro **758ST1064** wrist straps are flexible, non-allergenic, easy to clean and adjustable to any size wrist. The expansion band has a stainless steel conductive interior and a coated, insulative exterior for stray charge protection.

General Specifications							
General Specific	ations						
Brand	Techni-Pro						
Color	Black						
Cord Length	6 ft.						
Material	Metal						
Туре	Wrist strap with grounding cord						
Wearable Size	Adjustable						
Resistor	Yes						
Cord and Snap Included	Yes						
Wrist Strap Included	Yes						
Snap Size	1/4"						
Cord Style	Single						
Plug Style	Banana						
Snap Style	1/4" (7mm)						

**Table 1. Product Qualification** 

ELECTRICAL	REQUIRED LIMIT	TEST SECTION	UOM	A	В	С	D	E	F	RESULT
Wrist Strap Continuity and Resistance $(M\Omega)$	1 megohm ± 20% or user defined value	6.1	ΜΩ	0.97	0.9B8	0.97	0.98	0.97	0.97	PASS
Wristband (Cuff) Resistance Interior ( $k\Omega$ )	≤ 100 kilohms or user defined value	6.2	kΩ	< 1	< 1	< 1	< 1	< 1	< 1	PASS
Wristband Resistance Exterior (M $\Omega$ )	≥ 10 megohms	6.2	ΜΩ	> 2000	> 2000	> 10000	> 10000	> 10000	> 1000	PASS
MECHANICAL										
Wristband Size (inches)	Defined (min/max circumference)	6.3	IN	7/12	7/12	7/12	7/12	7/12	7/12	PASS
Breakaway Force (lbs)	>0.45 kg (1lb), < 2.3 kg (5lb)	6.4	LBS	2.0	1.8	1.6	1.4	1.8	2.2	PASS
CONNECTOR & CORD INTEGRITY										
Breaking point of ground cord (lbs)	< 2.3 kg (5lbs)	6.5	LBS	40.2	41.4	37.8	45.5	42.1	37.0	PASS
Breaking point of ground connector to ground cord (lbs)	> 66% of cord strength	6.5	%	99%	93%	97%	85%	94%	87%	PASS
Breaking point of wristband connector to cord (lbs)	> 66% of cord strength	6.5	%	100%	97%	100%	83%	98%	94%	PASS
Ground cord extendibility (MΩ)	Extension to mfr's specified length with no continuity loss	6.6	МΩ	0.98	0.97	0.97	0.98	0.97	0.97	PASS
Bending Life	≥ 16,000 cycles	6.7	Cycles	29,121	30,761	30,903	27,155	21,620	35,477	PASS
MARKING										
Manufacturer's Identification	Logo and/or name	6.8	Cord	TT	TT	TT	TT	TT	TT	PASS
			Band	None	None	None	None	None	None	PASS
ID of Non-Standard Resistance Value	Red feature. Value marked	6.9		NA	NA	NA	NA	NA	NA	PASS

Rev. JAN24





### Techni-Pro Black Metal Wrist Strap with 6-Foot Grouding Cord

TNP 758ST1064

#### **Table 2. Acceptance Testing**

ELECTRICAL	REQUIRED LIMIT	TEST SECTION	иом	А	В	С	D	E	F	RESULT
Wrist Strap Resistance (MΩ)	1 megohm ±20% or user defined value	6.10	ΜΩ	0.97	0.96	0.96	0.97	0.97	0.97	PASS

### Table 3. System Test

ELECTRICAL	REQUIRED LIMIT	TEST SECTION	иом	А	В	С	D	E	F	RESULT
Wrist Strap System Resistance (M $\Omega$ )	"Pass" or <35 megohms or user defined value	6.11	ΜΩ	1.00	1.03	1.06	1.05	1.05	1.07	PASS

Conclusion: TNP 758ST1064 has met the required limits for ANSI/ESD S1.1

### >>> Techni-Pro

### Wider selection | Higher quality | Stronger value

We've engineered a new private-label brand for world-class production supplies. You probably already know Techni-Pro products as Techni-Tool, Tec-Cut, Techni-Stat, Tec-Tuff, and other brands. Our goal was the same as it has always been: To give you more. More equipment. More supplies. More value.

Rev. JAN24

