

TECHNI-PRO

Product Data Sheet

Techni-Pro Black Conductive Foam



Product Information

Techni-Pro's conductive foam is used to protect static-sensitive devices and components in a variety of manufacturing applications. Comes in both high and low-density and can be used for packaging, lead insertion and protection.

Order Information

Part Numbers	Product Description
758ST5120	Low-Density 1/8" Conductive Foam
758ST2209	High-Density 1/4" Conductive Foam
758ST2206	Low-Density 3/8" Conductive Foam
758ST2210	High-Density 3/8" Conductive Foam
758ST2211	High-Density 1/2" Conductive Foam
758ST2208	Low-Density 1" Conductive Foam

General Specifications

Corrosion Resistance	Very Good
Density	High Density: 2.8 to 3.1 lb/ft ³ Low Density: 1.7 to 1.9 lb/ft ³
Tensile Strength	20 psi min
Construction	Polyurethane open cell
Thickness	1/8" 1/4" 3/8" 1/2" 3/4" 1"
Colors	Black
Elongation	150%
Sheet Size	24" x 36"
Heat Resistance	Stable 2500F
Electrical's Surface Resistivity	10 ² -10 ⁵
Volume Resistivity	10 ² -10 ⁵
Charge Decay	<0.05 seconds
Standards	Meet ANSI/ESD S20.20 Mil-Std 883-B and Mil-B-82646

»» Techni-Pro

Wider selection | Higher quality | Stronger value

We've engineered a new private-label brand for world-class production supplies. You probably already know Techni-Pro products as Techni-Tool, Tec-Cut, Techni-Stat, Tec-Tuff, and other brands. Our goal was the same as it has always been: To give you more. More equipment. More supplies. More value.

Rev. JAN24

TECHNI-PRO

Production supplies that **WORK** as hard as you do

Techni-Pro is a TestEquity private label brand featured on:

www.testequity.com/brand/techni-pro
www.techni-tool.com/brand/techni-pro
www.jensentools.com/brand/techni-pro