

Product Data Sheet

Masking Tape

182-312



Product Information

A medium tensile strength, pressure sensitive, kraft flatback, paper packaging and identification tape. Specially formulated adhesive provides for easier unwind while exhibiting an excellent balance of face-to-face adhesion and quick stick characteristics. Printable with standard flexographic ink.

Technical Details

Typical Values

Backing	Kraft Flatback
Adhesive	Synthetic Rubber
Adhesion to Steel (oz/in of width) PSTC-101	50 (13.7 N/25mm)
Quick Stick (oz/in of width)	To Kraft: 8 (2.2 N/25mm) To Steel: 23 (6.3 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	31 (136 N/25mm)
Elongation (% at break) PSTC-131	3
Total Thickness (mils) PSTC-133	6.3 (0.16mm)

Packaging

182-312	1/2" x 60 Yds, 3" Core, 6.3 mil, Tan
---------	--------------------------------------

Compliance

A-A-883, Type II. ASTM D6123, D6123M, Type II.
General Motors 9885278

»» Techni-Pro

Wider selection | Higher quality | Stronger value

We've engineered a new private-label brand for world-class production supplies. You probably already know Techni-Pro products as Techni-Tool, Tec-Cut, Techni-Stat, Tec-Tuff, and other brands. Our goal was the same as it has always been: To give you more. More equipment. More supplies. More value.

Rev. AUG23