TECHNI-PRO

Product Data Sheet

Brushes, ESD







Product Information

Non-sparking, non-magnetic, corrosion-resistant.

- RTT Resistance: 1 x 10³ to 1 x 10⁵ ohms tested per modified ANSI/ESD S4.1
- IEC 60079-32-2/Ed1: Explosive atmospheres Part 32-2: Electrostatics hazards Test
- Products are marked with the ESD symbol.
- This conductive product was tested and proved to meet the following standards: ESH TR53-01-06, ASTMD-257-78 and CENELEC/TR 50404-2006.

Warning: These are made of conductive material. To avoid the risk of electric shock, do not use item close to live currency/wire.

Part Number	Description	Size	Bristle Length	Bristle Thickness	Handle Material	Bristle Material
TNP100334EA	Round 1/8"	Ø3mm x 127mm	14mm	0.4mm	Polypropylene	Stiff Conductive Nylon
TNP100335EA	Round 1/4"	Ø6.3mm x 127mm	12mm	0.4mm	Polypropylene	Stiff Conductive Nylon
TNP100336EA	Flat 1/2"	13mm x 127mm	17mm	0.4mm	Polypropylene	Stiff Conductive Nylon
TNP100337EA	Flat 3/4"	19mm x 150mm	19mm	0.4mm	Polypropylene	Stiff Conductive Nylon
TNP100338EA	Flat 1"	26mm x 150mm	19mm	0.4mm	Polypropylene	Stiff Conductive Nylon
TNP100339EA	Flat 1.5"	38mm x 150mm	21mm	0.4mm	Polypropylene	Stiff Conductive Nylon
TNP100341EA	Flat 2"	50mm x 150mm	21mm	0.4mm	Polypropylene	Stiff Conductive Nylon

Rev. MAR23