TECHNI-PRO

Product Data Sheet

Fish Scale Fabric Wiper, Cleanroom

TNP100110PK



Description

A fish scale fabric wiper that is certified for a cleanroom environment. The unique structure of fish scale lattice texture improves the surface contact, and provides effective cleaning.

Features and Benefits

- · High water and oil absorption.
- Individually lot coded for ease of trace-ability and quality control.
- Good absorption with water and solvents.
- · Holds more dirt and residues than average wipe.
- · Remove residues from the surface more effectively.
- · Ultrasonic perfect edge sealing
- · Easy to wash without detergent.
- · Soft, no scratch to sensitive surfaces.

Technical Data

Wipe material

75% Polyester 25% Nylon

Attribute; (units)	Value **	Test Method	
Basis weight; nominal (g/m²)	268	MSD-QI-QS-007 A0	
Absorbency in water		IEST-RP-CC004.3	
Intrinsic; (mL/g)	2.6		
Extrinsic; (mL/m²)	696.8		
Sorptive rate; (seconds)	1	IEST-RP-CC004.3	
Non-volatile residue, NVR		IEST-RP-CC004.3	
In deionized water; (g/m²)	0.11		
In isopropanol; (g/m²)	0.38		
Particles, readily releasable			
APC: ≥0.3µm(Ea/ft³)	265	IEST-RP-CC003.3	

Cleanroom Environment

- ISO Class 5 8
- Class 100 100,000

Shelf Life

- Non-Sterile (Dry) 3 years from date of manufacture
- Non-Sterile (Pre-Wetted) 2 years from the date of manufacture
- Sterile 2 years from the date of manufacture

Rev. DEC22

TECHNI-PRO

Product Data Sheet

Fish Scale Fabric Wiper, Cleanroom

TNP100110PK

_		-		
0	ro	М	 ~1	-
_			 	-

Part Number	Description	Sterile Packaging		Case				
Dry wipes								
TNP100110PK	12" x 12" dry		6 wipes/bag	50 bags				

Notes:

- 1) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions
- 2) The information presented here is applicable to the part numbers shown above, as well as to any product containing the same materials and produced under the same conditions.
- 3) Size can be customized according to customer requirements.
- 4) Stacked, Bulk and Folded method can be customized according to customer requirements.

Rev. DEC22