

TECHNI-PRO

Product Data Sheet

Cellulose Tape, ESD Symbols Printed

758ST049, 758ST047, 758ST048



- Fast charge decay times
- Used in binding, edging and securing

Product Information

Transparent cellulose tape printed with ESD symbols. Ideal for sealing ESD packing containers.

Technical Details

Typical Values

Total Thickness	2 mil
Adhesion to Steel	30 oz/in
Temperature	66°C
Tensile Strength	25 lb/in
Elongation	18%
Static Generation	< 250 volts @ 50% RH

Packaging

758ST049	1" x 72 Yds, 3" core, 2 mil
758ST047	1/2" x 72 Yds, 3" core, 2 mil
758ST048	3/4" x 72 Yds, 3" core, 2 mil

Compliance

RoHs/REACH Compliant: This Product complies with the European Union's "Restriction of Hazardous Substances" (RoHs) initiative and European REACH Regulation.

»» Techni-PRO

Wider selection | Higher quality | Stronger value

We've engineered a new private-label brand for world-class production supplies. You probably already know Techni-PRO products as Techni-Tool, Tec-Cut, Techni-Stat, Tec-Tuff, and other brands. Our goal was the same as it has always been: To give you more. More equipment. More supplies. More value.

Rev. JUN23

TECHNI-PRO

Production supplies that **WORK** as hard as you do

Techni-PRO is a TestEquity private label brand featured on:

www.testequity.com/brand/techni-pro
www.techni-tool.com/brand/techni-pro
www.jensentools.com/brand/techni-pro