

## Product Data Sheet

# Coolor Striped Cellulose Tape, ESD Safe

443-340, 758ST653, 758ST0033, 758ST6331, 205ST613, 205ST633, 417-361, 758ST0013, 758ST0023, 758ST0053, 758ST0623, 758ST0653, 758ST1116, 758ST623



## Product Information

ESD safe color striped cellulose tape is 2.4 mil thick with a charge decay of <.014 seconds. This clear anti static tape is perfect for sealing ESD bags and ESD packing containers. It can also be used for a wide range of workstation applications such as binding, edging and securing.

- Rubber Based Adhesive
- Generates Less Than 250 Volts
- Tensile Strength is 90 N/25mil
- Lead-free RoHS Compliant

## Technical Details

Technical Details	Typical Values
Material	Transparent Cellulose
Backing	Cellophane
Adhesive	Natural Rubber
Thickness	2 mils
Static Generation	< 250 volts @50% RH
Adhesion	66 oz/in
Tensile Strength	90N/25mil
Elongation	18%
Temperature	32° to 150°F

## Packaging

443-340	1/2" x 72 Yds, 3" core, 2.4 mil, Green Stripe
758ST653	1/2" x 72 Yds, 3" core, 2.4 mil, Red
758ST0033	3/4" x 72 Yds, 3" core, 2.4 mil, Yellow Stripe
758ST6331	3/4" x 72 Yds, 3" core, 2.4 mil, Blue Stripe
205ST613	1" x 72 Yds, 3" core, 2.4 mil, Red Stripe
205ST633	3/4" x 72 Yds, 3" core, 2.4 mil, Blue
417-361	3/4" x 72 Yds, 3" core, 2.4 mil, Red Stripe
758ST0013	1" x 72 Yds' 3" core, 2.4 mil, Yellow Stripe
758ST0023	2" x 72 Yds, 3" core, 2.4 mil, Yellow Stripe
758ST0053	1/2" x 72 Yds, 3" core, 2.4 mil, Yellow Stripe
758ST0623	2" x 72 Yds, 3" core, 2.4 mil, Blue Stripe
758ST0653	1/2" x 72 Yds, 3" core, 2.4 mil, Blue Stripe
758ST1116	1" x 72 Yds, 3" core, 2.4 mil, Blue Stripe
758ST623	2" x 72 Yds, 3" core, 2.4 mil, Red Stripe

## Compliance

RoHs/REACH Compliant: This Product complies with the European Union's "Restriction of Hazardous Substances" (RoHs) initiative and European REACH Regulation.

Rev. JUN23