

TECHNI-PRO

Product Data Sheet

Cellulose Tape, ESD Safe

758ST041, 758ST651, 758ST611



- Rubber Based Adhesive
- Generates Less Than 250 Volts
- Tensile Strength is 90 N/25mil
- Lead-free RoHS Compliant

Product Information

ESD Safe Clear Cellulose Tape is 2 mm thick with a charge decay of <.014 seconds. Ideal for sealing ESD bags and ESD packing containers. It can also be used for a wide range of workstation applications such as binding, edging and securing.

Technical Details

Technical Details	Typical Values
Backing	Cellophane
Adhesive	Natural Rubber
Thickness	2 mil
Surface Resistance	1×10^8 to $< 1 \times 10^{11}$ Ohms
Static Generation	<250 volts @50%RH
Adhesion	66 oz/in
Tensile Strength	90N/25mil
Elongation	18%
Temperature	32° - 150°F

Packaging

758ST041	3/4" x 36 Yds, 1" core, 2 mil
758ST651	1/2" x 36 Yds, 1" core, 2 mil
758ST611	1" x 36 Yds, 1" core, 2 mil

»» Techni-PRO

Wider selection | Higher quality | Stronger value

We've engineered a new private-label brand for world-class production supplies. You probably already know Techni-PRO products as Techni-Tool, Tec-Cut, Techni-Stat, Tec-Tuff, and other brands. Our goal was the same as it has always been: To give you more. More equipment. More supplies. More value.

Rev. JUN23

TECHNI-PRO

Production supplies that **WORK** as hard as you do

Techni-PRO is a TestEquity private label brand featured on:

www.testequity.com/brand/techni-pro
www.techni-tool.com/brand/techni-pro
www.jensentools.com/brand/techni-pro