# Safety Data Sheet



Revision Number: 002.1

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

0450 PS 35 LB CProduct type:Hotmelt adhesiveRestriction of Use:None identifiedCompany address:Henkel Canada CorporationMeadowpine Boulevard 2515Mississauga, Ontario L5N 6C3

TECHNOMELT 0450 0450 PS 35 LB C Hotmelt adhesive IDH number:

420381

Item number:83354Region:CanadaContact information:Telephone: +1 (905) 814-6511MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW		
WARNING:	MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS.	
	VAPORS ABOVE MOLTEN ADHESIVE MAY CAUSE EYE, SKIN AND	
	RESPIRATORY TRACT IRRITATION.	
	STATIC CHARGES GENERATED BY EMPTYING PACKAGE IN OR NEAR	
	FLAMMABLE VAPORS MAY CAUSE IGNITION.	

HAZARD CLASS	HAZARD CATEGORY
None	None

PICTOGRAM(S)

None

**Precautionary Statements** 

Prevention:	Not prescribed
Response:	Not prescribed
Storage:	Not prescribed
Disposal:	Not prescribed

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

#### See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Ethene, homopolymer	9002-88-4	1 - 5

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

	FIRST AID MEASURES
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
Skin contact:	Molten adhesive may cause severe burns. Cool melted product on skin with plenty of water. Do not remove solidified product. No attempt should be mad to remove material from skin or to remove contaminated clothing as damage skin can be easily torn. Cover affected areas with clean sheeting or gauze ar seek immediate medical attention.
Eye contact:	If eye contact occurs with molten material immediately cool with water. Do n remove adhesive. Seek medical attention.
Ingestion:	Ingestion of solid adhesive is not expected to be hazardous. If symptoms develop and persist, get medical attention.
Symptoms:	See Section 11.
5. FI	RE FIGHTING MEASURES
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide. Use extinguishing measures appropriate to local circumstances and the surrounding environment.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Oxides of carbon. Acrid smoke and fumes.
6. ACCIE	DENTAL RELEASE MEASURES
personal protection recommended in Section sonnel.	8, isolate the hazard area and deny entry to unnecessary and unprotected
Environmental precautions:	No special environmental precautions required. Do not allow material to contaminate ground water system.
Environmental precations.	

1.	HAND	LING	AND	21	ORA	GE

Handling:	Always be careful around molten material. Avoid skin contact with molten resins. Do not place wet or damp solid into melt tank. Follow suggested application temperature. Do not wear contact lenses. At elevated temperatures, irritating fumes may be emitted. Provide adequate ventilation.
Storage:	For safe storage, store between 8 °C (46.4 °F) and 28 °C (82.4 °F) Keep cool in accordance with information on label and in Technical Data Sheets.

Shelf Life Statement: Not available.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethene, homopolymer	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles.	15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Engineering controls:	Work should be done in an adequately ventilated area (i.e., ventilation sufficient to maintain concentrations below one half of the PEL and other relevant standards). Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.			
Respiratory protection:	Solid Resin: Dust safety masks are recommended when the potential for dust inhalation exists. Molten Resin: Use a NIOSH approved air-purifying respirator with an organic vapor cartridge.			
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Do not wear contact lenses.			
Skin protection:	Insulated gloves and long sleeved clothing are strongly recommended when working with molten adhesive.			

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Flammability: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content: Viscosity: Decomposition temperature:

Solid Light yellow Mild Not available. Not available. Not applicable Not available. 157 °C (314.6 °F) 0.94 Not available. > 232 °C (> 449.6 °F) Not applicable Not applicable Not applicable Not applicable Not applicable Insoluble Not available. 0 %; 0 g/l Not available. Not available.

# **10. STABILITY AND REACTIVITY**

Stability:	Stable under normal conditions of storage and use.	
Hazardous reactions:	Will not occur.	
Hazardous decomposition products:	Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.	
Incompatible materials:	Oxidizing agents.	
Reactivity:	Not available.	
Conditions to avoid:	Excessive heat.	
11. TOXICOLOGICAL INFORMATION		

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation:	Continuous breathing of vapors above molten adhesive may irritate mucous membranes. Dusts from solid adhesive may cause irritation.
Skin contact:	Molten adhesive may cause severe burns. Solid adhesive has no hazards.
Eye contact:	Molten adhesive in eyes will cause severe and permanant damage. Can cause mechanical irritation if dusts are generated. Fumes released during thermal processing may cause eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s		Immediate and Delayed Health Effect		
Ethene, homopolymer	None N			No Target Organs	
Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen		OSHA Carcinogen (Specifically Regulated)	
Ethene, homopolymer	No	N	0	No	

## **12. ECOLOGICAL INFORMATION**

**Ecological information:** 

Not available.

### **13. DISPOSAL CONSIDERATIONS**

Information provided is for unused product only.

Recommended method of disposal:

# Follow all local, state, federal and provincial regulations for disposal.

# **14. TRANSPORT INFORMATION**

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA) Proper shipping name: Hazard class or division: Identification number: Packing group:	Not regulated None None None
Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group: Exceptions:	Not regulated None None None None

### **15. REGULATORY INFORMATION**

Canada Regulatory Information

CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
United States Regulatory Information	
TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

### **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: 3

Prepared by: Regulatory Affairs

Issue date: 04/07/2017

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.