

3.5mm / SMA - Female VNA calibration kit, 6 GHz

1 Introduction

The TBVC-SF6 is a 3.5mm/SMA compatible calibration kit for Vector Network Analyzers. It contains an Open, Short, Load and a Through. It is used for OSLT calibration in the frequency range DC-6GHz.



Picture 1: TBVC-SF6

2 Specification

Load:

3.5mm-Female
 $Z = 50 \Omega$
 Return loss > 30 dB

THROUGH:

3.5mm-Female
 $Z = 50 \Omega$
 Loss = 6.24 GΩ/s
 Delay = 75.17 ps

Short:

3.5mm-Female
 $Z = 50 \Omega$
 Delay = 48.586 ps
 Loss = 7.08 GΩ/s
 $L_0 = 5.59 \text{ pH}$
 $L_1 = -8.5598\text{e-}21 \text{ H/Hz}$
 $L_2 = -3.092\text{e-}31 \text{ H/Hz}^2$
 $L_3 = -1.77\text{e-}42 \text{ H/Hz}^3$

Open:

3.5mm-Female
 $Z = 50 \Omega$
 Delay = 46.378 ps
 Loss = 6.14 GΩ/s
 $C_0 = 4.1 \text{ fF}$
 $C_1 = 6.4125\text{e-}24 \text{ F/Hz}$
 $C_2 = -2.78\text{e-}35 \text{ F/Hz}^2$
 $C_3 = -2.593\text{e-}44 \text{ F/Hz}^3$

Frequency range: DC – 6 GHz
 Box dimensions: 145 mm x 145 mm x 55 mm
 Weight: 340 g

3.5mm / SMA - Female VNA calibration kit, 6 GHz

The calibration kit file is pre-installed with our TBVNA-6000 software and can be downloaded separately from our website.

3 Ordering Information

Part Number	Description
TBVC-SF6	3.5mm / SMA - Female OSLT VNA calibration kit, 6 GHz

4 History

Version	Date	Author	Changes
V 1.0	2.5.2025	Mayerhofer	Creation
V1.1	21.7.2025	Mayerhofer	Typo correction 2,5mm->3.5mm