

PA3587 SurePunch® PRO PDT PUNCHDOWN TOOL

The Tempo Communications PA3587 SurePunch® Pro SSP Punchdown Tool with a detachable light is ideal for working in dark environments. It will terminate 28-22 AWG solid or stranded wire in a single punch. Additionally, the SurePunch® offers a spudger that can be used as a screwdriver or an IDC contact insertion tool, a wire hook to feed wires through holes, and a pick to separate twisted-pair cables or to strip insulation and cut wire.

FEATURES:

- Terminate cable in single punch including 23 AWG Cat6
- Detachable light with long-life LED specially designed to focus the light on the panel work area
- Luminous intensity of the LED is 2200 mcd
- Finger grips and non-slip rubber-embedded cushioned handle for comfort
- Multi-use spudger that can be used as a screwdriver or an IDC contact insertion tool

ADVANTAGES:

- Hook to feed wires through holes
- Pick to separate bonded twisted-pair cables or to strip insulation and cut wire
- Adjustable HI/LO spring compression for all cable types. LO= 27.5 lbs (122 N), HI= 37.5 lbs (167 N)
- Uses twist-and-lock style blades
- Blade storage area in end of handle with comfortable latch cover



Paladin® brand hand tools from Tempo® Communications carry a Limited Lifetime Warrantu.













PALADIN

SurePunch[™] *Pro*

ACCESSORIES:



PA4572

SurePunch® 110 reversible blade



PA4573

SurePunch® 66 reversible blade



PA3596

SurePunch[®] Pro PDT with 110 reversible cut & punch/ punch-only blade and light

ORDERING INFORMATION:

PART NO.	CAT. NO.	DESCRIPTION
52050824	PA3588	SurePunch® Pro PDT with 110/66 combination cut-only
52046976	PA3596	SurePunch® Pro PDT with 110 reversible cut & punch/punch-only blade and light
52050826	PA3586	SurePunch® Pro PDT with 110 & 66 reversible cut & punch/punch-only blades



Renewed Vision. **Innovation** Forward.











©2021 Tempo Communications Inc. • An ISO 9001 Company

1390 Aspen Way Vista, CA • 92081

Latin America Phone : 1.760.510.0558 | EMEA Phone: +44 (0) 1633 927 050

TC-PA3587 08/21