



OTDR II Specifications:

Display:	7 in (178 mm) outdoor-enhanced touchscreen, 800 x 480 TFT
Interfaces:	Two USB 2.0 ports RJ-45 LAN 10/100 Mbit/s
Storage:	2 GB internal memory (20 000 OTDR traces, typical)
Batteries:	Rechargeable lithium-polymer battery 12 hours of operation as per Telcordia (Bellcore) TR-NWT-001138
Power supply:	Power supply AC/DC adapter, input 100-240 VAC, 50-60 Hz, 9-16 V DCIN 15 Watts minimum
Wavelength (nm) ^b :	850/1300/1310/1550
Dynamic range (dB) ^c :	27/29/36/35
Event dead zone (m) ^d :	MM: 0.5, SM: 0.7
Attenuation dead zone (m) ^e :	MM: 2.5, SM: 3
Distance range (km):	0.1 to 260 for single-mode and 0.1 to 40 for multimode
Pulse width (ns):	MM: 3 to 1000, SM 3 to 20 000
Linearity:	(dB/dB) ±0.03
Loss threshold:	(dB) 0.01
Loss resolution:	(dB) 0.001
Sampling resolution (m):	0.04 to 5
Sampling points:	Up to 256 000
Distance uncertainty (m) ^f :	±(0.75 + 0.0025 % x distance + sampling resolution)
Measurement time:	User-defined (60 min. maximum)
Reflectance accuracy:	(dB) ±2
Typical real-time refresh (Hz):	4
Laser safety:	1M

Notes

- a. All specifications valid at 23 °C ± 2 °C with an FC/APC connector, unless otherwise specified.
- b. Typical.
- c. Typical dynamic range with longest pulse and three-minute averaging at SNR = 1.
- d. Typical, for reflectance below -55 dB, using a 3-ns pulse.
- e. Typical, for reflectance below -55 dB, using a 3-ns pulse. Attenuation dead zone at 1310 nm is 4.5 m typical with reflectance below -45 dB
- f. Does not include uncertainty due to fiber index.

General:

Size (H x W x D):	166 mm x 200 mm x 68 mm (6 9/16 in x 7 7/8 in x 2 ¾ in)
Weight (with battery):	1.5 kg (3.3 lb)
Temperature:	Operating -10 °C to 50 °C (14 °F to 122 °F) Storage -40 °C to 70 °C (-40 °F to 158 °F) ^a
Relative humidity:	0 % to 95 % noncondensing

Source (optional)

Output power (dBm) ^b :	MM: -3, SM: -6
Modulation:	CW, 1 kHz, 2 kHz

Built-In Power Meter (GeX - optional ^c)

Calibrated wavelengths (nm):	850, 1300, 1310, 1490, 1550, 1625, 1650
Power range (dBm) ^d :	27 to -50
Uncertainty (%) ^e :	±5 % ± 10 nW
Display resolution:	(dB) 0.01 = max to -40 dBm 0.1 = -40 dBm to -50 dBm
Automatic offset nulling range ^{d,f} :	Max power to -30 dBm
Tone detection (Hz):	270/330/1000/2000



Visual Fault Locator (VFL)

Laser, 650 nm: ± 10 nm
CW/Modulate: 1 Hz
Typical Pout in 62.5/125 μ m: > -1.5 dBm (0.7 mW)
Laser safety: Class 2

Laser Safety:

CAUTION: VIEWING THE LASER OUTPUT WITH CERTAIN OPTICAL INSTRUMENTS (FOR EXAMPLE: EYE LOUPES, MAGNIFIERS AND MICROSCOPES) WITHIN A DISTANCE OF 100 MM MAY POSE AN EYE HAZARD.

Notes

- a. -20 °C to 60 °C (-4 °F to 140 °F) with the battery pack.
- b. Typical output power is given at MM 1300nm, SM 1550 nm.
- c. At 23 °C ± 1 °C, 1550 nm and FC connector. With modules in idle mode. Battery operated after 20-minute warm-up.
- d. Typical.
- e. At calibration conditions.
- f. For ± 0.05 dB, from 10 °C to 30 °C.

IDEAL INDUSTRIES NETWORKS DIVISION

Unit 3, Europa Court, Europa Boulevard, Warrington, Cheshire, WA5 7TN, UK.

Tel. +44 (0)1925 444 446 | Fax. +44 (0)1925 445501

uksales@idealnwd.com

Specification subject to change without notice. E&OE

© IDEAL Networks 2016



IDEAL INDUSTRIES, INC.

**A subsidiary of
IDEAL INDUSTRIES INC.**



Call Us 1.877.571.7901