

4-Port DisplayPort KVM Switch with Audio, Cables and USB 3.0 SuperSpeed Hub

MODEL NUMBER: B004-DPUA4-K



Control 4 DisplayPort computers using one DisplayPort monitor, USB keyboard and USB mouse. Connect USB 3.0 peripherals, such as hard drives and webcams, and share them between computers.

Features

Access and Control Up to 4 Computers with One KVM Switch

- Switch among computers using keyboard hotkeys or front-panel buttons
- Monitor's EDID information sent to connected computer when selected
- Auto Scan feature cycles among computers at regular intervals for at-a-glance observation of activity
- Supports DisplayPort 1.1

Independent Audio Switching

- 3.5 mm mini-stereo speaker and microphone jacks allow sharing of audio equipment among computers
- Listen to audio files on one computer while accessing another computer
- Supports 2-channel stereo audio

Independent USB 3.0 Peripheral Sharing

- 2-port USB 3.0 SuperSpeed hub allows connection of peripherals, such as webcams, flash drives, printers and scanners
- Print documents from one computer while accessing another computer
- Supports USB 3.0 data transfer rates up to 5 Gbps
- Backward compatible with USB 2.0 and USB 1.1 devices

Compatible with All Major Operating Systems

- Easy to set up with no software or drivers to install
- Supports digital video resolutions up to 2560 x 1600, including 1080p
- Works with Windows, Mac, Linux and Sun
- All necessary cables included

Highlights

- Connect peripherals to built-in 2-port USB 3.0 hub
- Switch among computers via front buttons or keyboard hotkeys
- Supports digital video resolutions up to 2560 x 1600
- Supports Displayport 1.1
- Includes all necessary DisplayPort, USB 3.0 and audio cables

System Requirements

- DisplayPort-enabled monitor
- USB keyboard and mouse
- Speaker and microphone with 3.5 mm mini-stereo plugs (for audio)
- Computer with USB port (need USB 3.0 port for USB 3.0 speed)
- Computer with 3.5 mm mini-stereo jacks (for audio)
- Compatible with all major operating systems

Package Includes

- B004-DPUA4-K 4-Port DisplayPort KVM Switch
- (4) DisplayPort cables, 6-ft. (1.83 m)
- (4) USB 3.0 Type-A to Type-B cables, 6-ft. (1.83 m)
- (4) 3.5 mm mini-stereo cables, 6-ft. (1.83 m)
- External power supply (Input: 100/240V, 50/60 Hz, 0.8A; Output: 9V, 2A)
- Universal plug adapters (NEMA 1-15P, CEE 7/16, BS1363, and AS3112)
- Owner's manual



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Specifications

OVERVIEW	
UPC Code	037332188632
Technology	DisplayPort; Stereo Audio
VIDEO	
Max Supported Video Resolution	2560 x 1600 @60Hz
INPUT	
Voltage Compatibility (VAC)	100; 110; 120; 127; 200; 208; 220; 230; 240
POWER	
AC Adapter	Input: 100-240V, 50/60Hz, 0.8A Output: 9V, 2A
External Power Supply Input Specs (V / Hz / A)	100-240V / 50/60Hz / 0.8A
External Power Supply Output Specs (V / A)	9V/ 2A
External Power Supply Cord Length (ft.)	6
DC Barrel Plug	OD: 5.5 x 2.1 x 10mm, Positive Pin, Negative Sleeve
Power Consumption (Watts)	6.5
External Power Supply Plug(s)	NEMA 1-15P North America; CEE 7/16 Schuko; BS 1363 UK; AS/NZS 3112 Australia
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	Red (USB); White (Selected PC)
PHYSICAL	
Material of Construction	Steel
Color	Black
Cable Jacket Color	Black
Shipping Dimensions (hwd / cm)	18.80 x 15.75 x 26.92
Shipping Dimensions (hwd / in.)	7.40 x 6.20 x 10.60
Shipping Weight (kg)	2.68
Shipping Weight (lbs.)	5.90
Unit Dimensions (hwd / in.)	1.8 x 8.1 x 3.9
Unit Packaging Type	Box
Unit Weight (lbs.)	2.1



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Unit Weight (kg)	0.95
ENVIRONMENTAL	
Operating Temperature Range	32 to 104 F (0 to 40 C)
Storage Temperature Range	-4 to 140 F (-20 to 60 C)
Relative Humidity	0%-90% RH, Non-Condensing
BTUs	22.2 BTU/Hr
COMMUNICATIONS	
IP Remote Access	No
CONNECTIONS	
Number of Ports	4
PC/Server Connections	USB; DisplayPort
Side A - Connector 1	(4) DISPLAYPORT (FEMALE)
Side A - Connector 2	(4) USB 3.0 B (FEMALE)
Side A - Connector 3	(8) 3.5MM (FEMALE)
Side B - Connector 1	DISPLAYPORT (FEMALE)
Side B - Connector 2	(2) USB 3.0 A (FEMALE)
Side B - Connector 3	(2) USB A (FEMALE)
Side B - Connector 4	(2) 3.5MM (FEMALE)
Computer Keyboard and Mouse Interface	USB
Computer Monitor Interface	Displayport
Console Keyboard and Mouse Interface	USB
Console Monitor Interface	Displayport
Connector Plating	Nickel
FEATURES & SPECIFICATIONS	
Autoscan (Y,N)	Y
Autoscan Duration	10 TO 60 (DEFAULTS AT 10, USER DEFINABLE IN 10 SECOND INTERVALS)
Number of Users	1
NIAP-Certified Secure	No
Port Selection	Pushbutton; Hotkey
Displayport Specification	1.1
USB Hub Ports	Yes
Number of USB Hub Ports	2



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
Driver Required	No
Cat5 KVM Switch	No
STANDARDS & COMPLIANCE	
External Power Supply Certifications	CE; FCC; UL; cUL; TUV; GS; BS; RCM; CB
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>