

Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

2-Port Compact USB KVM Switch with Audio and Cable

MODEL NUMBER: B004-VUA2-K-R







2-port Compact USB KVM Switch with optional audio and microphone switching function allows you to access control boot and reboot two USB-enabled computers from a single keyboard monitor and mouse

Features

- · Fast, easy switching via keyboard hot keys, push buttons or software
- Plug-and-play setup no software required
- Hot-swap capability allows easy addition or removal of computers without powering down the switch or other computers
- Speaker and microphone connections allow sharing of audio components between systems (standard 3.5 mm audio connections)
- Independent audio switching allows you to listen to audio from one computer while switching to the other computer
- Supports video resolutions up to 2048 x 1536 (standard 15-pin VGA connectors)
- Supports Microsoft® IntelliMouse® and the scrolling wheel on most mice]
- · Compact design saves desk space
- Does not require an AC adapter
- · Compatible with all major operating systems
- Includes two, 6-ft. (1.83 m) Cable Kits

Highlights

- Fast, easy switching via keyboard hot keys, push buttons or software (not required)
- PC and Mac compatible
- Allows sharing of audio components between systems; listen to music from one computer while switching to the other computer
- Compact design saves desk space
- No AC adapter required
- (x2) 6-ft. (1.83 m) USB KVM
 Cable kits and (x2) 6-ft. (1.83 m)
 3.5mm Audio Cable kits included
- Compatible with all major operating systems

System Requirements

- Console: VGA, SVGA or Multisync Monitor, USB Keyboard and USB Mouse
- Computers: VGA, SVGA or Multisync Monitor Port and USB Port
- Audio (Optional): Speakers with standard 3.5 mm Connectors and a computer with 3.5mm ports
- Compatible with all major operating systems

Package Includes

- Compact 2-port USB KVM Switch with Audio
- (2) 6-ft. (1.83 m) USB KVM Cable Kits and (2) 6-ft. (1.83 m) 3.5mm Audio Cable Kits
- CD-ROM with KVM Switcher Software
- Owner's Manual with Warranty Information

Specifications

OVERVIEW	
UPC Code	037332140043
Product Type	KVM





Console	No	
Max CPU	1	
Technology	VGA/SVGA; Stereo Audio	
Host Connector	(2) USB A (FEMALE)	
VIDEO		
Video Input	HD15 (FEMALE)	
Video Output	HD15 (FEMALE)	
Number of Monitors Supported	1	
Video Ports	(3) HD15 (FEMALE)	
Max Supported Video Resolution	2048 x 1536 @60Hz	
AUDIO		
Audio Ports	(2) 3.5MM (FEMALE)	
Audio Ports Details	Connect a microphone and speaker via the dual 3.5mm audio ports	
Audio Input	3.5mm	
Audio Output	Audio	
Audio Specification	Stereo Audio	
DATA		
Data Ports	(2) USB A (FEMALE)	
Data Ports Details	(2) USB-A - USB 2.0	
INPUT		
Bus Powered	Yes	
Power Source	Bus; USB	
POWER		
Power Consumption (Watts)	0.5	
USER INTERFACE, ALERTS & CO	NTROLS	
LED Indicators	Green (Selected PC)	
PHYSICAL		
Material of Construction	ABS	
Color	Black	
Cable Jacket Color	Black	
Total Number of Ports	9	



Shipping Dimensions (hwd / cm)	7.62 x 20.07 x 19.81	
Shipping Dimensions (hwd / in.)	3.00 x 7.90 x 7.80	
Shipping Weight (kg)	0.82	
Shipping Weight (lbs.)	1.80	
Unit Dimensions (hwd / in.)	1.3 x 4 x 2.6	
Unit Packaging Type	Вох	
Unit Weight (lbs.)	0.22	
Unit Weight (kg)	0.10	
ENVIRONMENTAL		
Operating Temperature Range	32 to 104 F (0 to 40 C)	
Storage Temperature Range	-4 to 140 F (-20 to 60 C)	
Relative Humidity	0%-90% RH, Non-Condensing	
BTUs	1.7 BTU/Hr	
ESD Protection	Yes	
COMMUNICATIONS		
Hotkey	Yes	
IP Remote Access	No	
EDID Compatible	Yes	
IR Remote Extension Support	No	
CONNECTIONS		
CONNECTIONS		
Number of Ports	2	
Daisy-Chain Port	No No	
Firmware Upgrade Port	No No	
PC/Server Connections	USB; VGA	
Side A - Connector 1	(2) HD15 (FEMALE)	
Side B - Connector 1	HD15 (FEMALE)	
Side B - Connector 2	(2) USB A (FEMALE)	
Side B - Connector 3	(2) 3.5MM (FEMALE)	
Side B - Connector 4	(2) USB MINI-B 5-PIN (FEMALE)	
Included Cable (Side A) - Connector 1	Yes	
Computer Keyboard and Mouse Interface	USB	





Console Keyboard and Mouse Interface	USB
Console Monitor Interface	VGA
Connector Plating	Nickel
FEATURES & SPECIFICATIONS	
Autoscan (Y,N)	Y
Autoscan Duration	10 - 60 seconds
Number of Users	1
NIAP-Certified Secure	No
On-Screen Display (OSD)	No
Port Selection	Pushbutton; Hotkey; Software
USB Hub Ports	Yes
USB Specification	USB 2.0 (up to 480 Mbps)
Driver Required	No
Cat5 KVM Switch	No
STANDARDS & COMPLIANCE	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies