

HDMI over Cat5/6 Passive Extender, Low-Profile Remote Receiver for Video/Audio, Up to 100 ft. (30 m), TAA

MODEL NUMBER: B126-1P0-MINI



Works with Tripp Lite's B126-Series transmitters to extend an HDMI signal via one Cat5e/6 cable up to 100 ft. to a projector, monitor or television. Recommended for digital signs, classrooms and trade show presentations.

Description

The B126-1P0-MINI HDMI over Cat5/Cat6 Passive Extender, Low-Profile Remote Receiver works with Tripp Lite's B126-002 and B126-004 transmitters (sold separately) to extend an HDMI signal to multiple projectors, monitors or televisions in a chain. It's recommended for digital signs, trade shows, presentations, classrooms, churches, retail settings and other applications where the video source is located farther than conventional cables allow.

The compact, low-profile design helps hide the unit from view. The B126-1P0-MINI's built-in HDMI male connector plugs directly into the monitor. The unit can extend a 1080i (@ 60 Hz) signal up to 100-ft. (30.5 m) or a 1080p (@ 60 Hz) signal up to 50-ft. (15.24 m) with a single Cat5e/6 cable. For best results, use 24 AWG solid-wire Cat5e/6 cable (such as Tripp Lite's N202-Series) between this unit and the transmitter. In addition to crystal-clear video, the B126-1P0-MINI delivers full, rich stereo and 7.1-channel surround sound (multi-channel or PCM) audio when paired with a B126-002 or B126-004 transmitter. Supports 24-bit True Color (8 bits per channel) and HDCP compatibility. Easy to set up with no software, drivers or external power supply required.

Features

Extends High-Definition Signals

• Works in tandem with Tripp Lite's B126-002 and B126-004 transmitter units (sold separately)

- Extends a 1080i (@ 60 Hz) signal up to 100-ft. (30.5 m)
- Extends a 1080p (@ 60 Hz) signal up to 50-ft. (15.24 m)
- Connects to transmitter with one Cat5e/6 cable
- Built-in HDMI male connector plugs directly into monitor

Supports the Latest Video and Audio Resolutions

Works with all operating systems and HDMI video sources

• Supports stereo and 7.1-channel surround sound (multi-channel or PCM) when paired with B126-002 or B126-004

Highlights

- Compact, low-profile design hides unit from view
- Supports high-definition video resolutions up to 1080p (@ 60 Hz)
- Supports stereo and 7.1channel surround sound audio
- Works with all operating systems and HDMI video sources
- Plug-and-play—no software, drivers or external power supply

Package Includes

- B126-1P0-MINI HDMI over Cat5/Cat6 Passive Low-Profile Remote Receiver
- USB Micro-B cable
- Owner's manual



• Supports 24-bit True Color (8 bits per channel) and HDCP

Easy to Set Up and Use

- Plug-and-play engineering—no software or drivers necessary
- No external power required; included USB Micro-B cable provides extra power when necessary

TAA-Compliant

• Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW		
UPC Code	037332200402	
Product Type	Receiver	
Technology	HDMI; Cat5/5e; Cat6	
VIDEO		
Max Supported Video Resolution	1920x1080 (1080p @ 60Hz)	
Max 720P Range (ft)	100	
Max 1080P Range (ft)	50	
Max 1280 x 720 (720p) Range (ft)	100	
Max 1920 x 1080 (1080p) Range (ft)	50	
Receiver/Transceiver Video Output	HDMI	
Receiver - Number of Video Outputs	1	
Range Extension using other Tripp Lite product	175ft @ 1080i 125ft @ 1080p	
Recommended Cabling	N202-Series Cat6 Patch Cable	
Other Tripp Lite product used to extend range	B126-110	
Max Supported Color Depth	24-bit True Color	
HDR Support	No	
3D Video Supported	Yes	
Chroma Sub Sampling	4:4:4	
Maximum Signal Range (ft)	100	
Maximum Signal Range (m)	30	
Maximum Signal Range Details	100 ft @ 1080i50 ft @ 1080p	
AUDIO		



[
Audio Output	HDMI	
Audio Specification	Pass-through audio	
INPUT		
Bus Powered	No	
POWER		
Power Source Type	USB	
Power Source	Receiver end only (Optional)	
Power Over Cable (PoC) Support	No	
PHYSICAL		
Color	Black	
Number of Displays	1	
Form Factor/Mounting Options	Pigtail	
Shipping Dimensions (hwd / cm)	3.30 x 14.99 x 12.19	
Shipping Dimensions (hwd / in.)	1.30 x 5.90 x 4.80	
Shipping Weight (kg)	0.09	
Shipping Weight (lbs.)	0.20	
Unit Dimensions (hwd / in.)	1.52 x 0.85 x 0.81	
Unit Packaging Type	Box	
Unit Weight (Ibs.)	0.03	
Unit Weight (kg)	0.01	
Housing	Plastic	
ENVIRONMENTAL		
Operating Temperature Range	32 to 104 °F (0 to 40 °C)	
Storage Temperature Range	5 to 122 °F (-15 to 50 °C)	
Relative Humidity	0% to 85%, Non-Condensing	
COMMUNICATIONS		
Max 1024 x 768 Range (ft)	100	
Max 480P Range (ft)	100	
Max 1440 x 900 Range (ft)	100	
Max 1080i Range (ft)	100	
Max 480i Range (ft)	100	
Max 640 x 480 Range (ft)	100	



Max 800 x 600 Range (ft)	100	
Max 1600 x 1200 Range (ft)	100	
EDID Compatible	Yes	
IR Remote Extension Support	No	
RS-232 Serial Extension Support	No	
Consumer Electronics Control (CEC) Supported	Yes	
USB Extension Support	No	
CONNECTIONS		
Number of Ports	1	
Side A - Connector 1	RJ45 (FEMALE)	
Side B - Connector 1	HDMI (MALE); MICRO-USB B (FEMALE)	
Connector Plating	Nickel	
FEATURES & SPECIFICATIONS		
HDCP Specification	1.4	
Driver Required	No	
10/100 Ethernet Extension Support	No	
Built-In Equalizer	No	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY		
Product Warranty Period (Worldwide)	1-year limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies