

Standby UPS 450VA 255W - 8 5-15R Outlets, 120V, 50/60 Hz, 5-15P Plug, Desktop/Wall Mount

MODEL NUMBER: BC450



Compact desktop UPS with silent alarm provides battery backup support for your home/office network system or digital signage components.

Features

Compact Desktop 450VA/255W Battery Backup for PCs, Home Theater and Digital Signage

The standby BC450 UPS system provides reliable battery backup and AC power protection against blackouts, brownouts, overvoltages, surges and line noise that can damage valuable electronics or destroy data. The eight-outlet 120V battery backup is ideal protection for your home office, media center or professional kiosk, security and small-business applications, including computers, routers, printers, HDTVs, Blu-ray players, game consoles, ATMs, security systems, phone systems, wireless hotspots and digital signage equipment.

Allows Time to Back Up Critical Files During a Blackout

Backup support allows you to work through short power failures and gives you enough time to safely save files and shut down your system in case of a prolonged blackout. Backup time varies according to load, but the BC450 should keep an energy-efficient desktop computer with small LCD monitor powered as long as 18 minutes. During normal operation, incoming utility power keeps the replaceable internal battery fully charged, so backup power will always be available.

8 NEMA 5-15R Outlets Protect Your Computer and Other Connected Components

Four 5-15R outlets provide battery backup and surge protection for your computer, monitor and other crucial components. The other four 5-15R outlets provide surge suppression only for printers, scanners, speakers and other desktop equipment regarded as non-essential during a blackout.

316 Joules Fight Back Against Unexpected Power Surges

A 316-joule surge suppression rating protects connected components from the harmful effects of power surges.

Combats Electromagnetic Interference That Can Harm Equipment

Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems and can lead to incremental hardware damage, data corruption and audio/video transmission problems. The BC450 incorporates technology that filters out disruptive line noise so that it won't affect your equipment.

Home-Friendly Alarm and Diagnostic LED Report Real-Time Status

Highlights

- Protects equipment against blackouts, brownouts, overvoltages, surges and line noise
- Battery backup allows time to save files and safely shut down during blackouts
- Alarm remains silent in battery mode; sounds to report low battery and overloads
- High >98% efficiency reduces BTU emissions, saves power and lowers energy costs

Applications

- Protect your PC and other sensitive electronics against power surges, line noise, brownouts, overvoltages and blackouts
- Operate essential equipment during short-term power outages using battery backup power
- Shut down desktop PCs and other equipment without data loss during long-term power outages

Package Includes

- BC450 120V 450VA 255W Standby UPS with 8 Outlets
- Owner's manual



The UPS remains silent in both line and battery backup modes. The alarm sounds only to report low battery, excessive load or fault condition. An LED indicator points out operating mode and fault status at a glance.

High-Efficiency Operation Helps You Save Energy and Cut Costs

A high >98% efficiency rating reduces BTU emissions, energy consumption and, ultimately, your energy costs.

Compact Housing for Convenient Installation Almost Anywhere

The space-saving ABS housing fits on a desktop, shelf or anywhere else convenient to your workstation or home theater. Keyhole mounting tabs on the rear allow easy wall-mount installation. The five-foot power cord with NEMA 5-15P plug connects to any compatible AC outlet.

Specifications

| OVERVIEW | |
|---|-------------------------------------|
| UPC Code | 037332238283 |
| UPS Type | Standby |
| INPUT | |
| Rated input current (Maximum Load) | 6A |
| Nominal Input Voltage(s) Supported | 120V AC |
| UPS Input Connection Type | 5-15P |
| Input Circuit Breakers | 7A |
| UPS Input Cord Length (ft.) | 5 |
| UPS Input Cord Length (m) | 1.5 |
| Recommended Electrical Service | 15A 120V |
| Input Phase | Single-Phase |
| OUTPUT | |
| Output Volt Amp Capacity (VA) | 450 |
| Output Watt Capacity (Watts) | 255 |
| Nominal Voltage Details | 120v nominal output in battery mode |
| Frequency Compatibility | 50 / 60 Hz |
| Output Voltage Regulation (Line Mode) | 120V ($\pm 20\%$) |
| Output Voltage Regulation (Battery Mode) | 120V ($\pm 10\%$) |
| UPS Output Receptacles (Surge Suppression Only) | 4 UPS outlets, 4 surge-only outlets |
| Output AC Waveform (AC Mode) | Pure sine wave |
| Output AC Waveform (Battery Mode) | PWM sine wave |



| | |
|---|--|
| Nominal Output Voltage(s) Supported | 110V; 115V; 120V |
| Output Receptacles | (8) 5-15R |
| Individually Controllable Load Banks | No |
| BATTERY | |
| Battery Type | Valve Regulated Lead Acid (VRLA) |
| Full Load Runtime (min.) | 1.5 min. (255w) |
| Half Load Runtime (min.) | 6.9 min. (127.5w) |
| Expandable Runtime | No |
| DC System Voltage (VDC) | 12 |
| Battery Recharge Rate (Included Batteries) | 6.5 hours (10% to 90%) |
| Battery Access | Battery access door |
| Battery Replacement Description | Replaceable internal batteries (see manual) |
| USER INTERFACE, ALERTS & CONTROLS | |
| Switches | Power off/on switch |
| Audible Alarm | UPS remains silent in battery backup mode; Alarm sounds only to report low-battery, fault, overload and replace-battery conditions |
| LED Indicators | 1 Status LED reports operating mode and fault status |
| SURGE / NOISE SUPPRESSION | |
| UPS AC Suppression Joule Rating | 316 |
| UPS AC Suppression Response Time | Instantaneous |
| EMI / RFI AC Noise Suppression | Yes |
| PHYSICAL | |
| Primary Form Factor | Desktop |
| Installation Form Factors Supported with Included Accessories | Tower; Ultra-compact desktop; Wallmount |
| Primary UPS Depth (mm) | 185 |
| Primary UPS Height (mm) | 105 |
| Primary UPS Width (mm) | 110 |
| Shipping Dimensions (hwd / in.) | 7.36 x 5.67 x 10.86 |
| Shipping Weight (kg) | 2.00 |
| UPS Housing Material | ABS |
| UPS Power Module Dimensions (hwd, in.) | 4.13 x 4.33 x 7.28 |



| | |
|---|--|
| UPS Power Module Weight (kg) | 1.80 |
| UPS Power Module Weight (lbs.) | 3.96 |
| ENVIRONMENTAL | |
| Operating Temperature Range | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius |
| Storage Temperature Range | +5 to +113 degrees Fahrenheit / -15 to +45 degrees Celsius |
| Relative Humidity | 0 to 90%, non-condensing |
| AC Mode BTU / Hr. (Full Load) | 13.1 |
| AC Mode Efficiency Rating (100% Load) | >98% |
| COMMUNICATIONS | |
| Network Management Card Description | Network management not supported |
| Communications Interface | None |
| LINE / BATTERY TRANSFER | |
| Transfer Time | 6 milliseconds typical (10 milliseconds max) |
| Low Voltage Transfer to Battery Power (Setpoint) | 95 |
| High Voltage Transfer to Battery Power (Setpoint) | 145 |
| FEATURES & SPECIFICATIONS | |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported |
| High Availability UPS Features | Surge/noise protection |
| Green Energy-Saving Features | Greater than 95% efficiency - GREEN UPS |
| STANDARDS & COMPLIANCE | |
| Product Certifications | ICES (Canada); RETIE (Colombia); CSA (Canada); CAN/CSA-C22.2 No. 107.3 (Canada); NOM (Mexico); UL 1778 |
| Product Compliance | RoHS; FCC Part 15 Class B (USA) |
| WARRANTY | |
| Product Warranty Period (U.S. & Canada) | 2-year limited warranty |
| Product Warranty Period (Latin America) | 2-year limited warranty |
| Product Warranty Period (International) | 2-year limited warranty |
| Product Warranty Period (Mexico) | 2-year limited warranty |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|---|--|
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$100,000 Ultimate Lifetime Insurance |
|---|--|

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:
<https://www.tripplite.com/products/product-certification-agencies>